

Handling Modifications with *MSnID*

Vladislav A. Petyuk

July 14, 2026

Contents

1	Introduction	1
2	Reading and Brief Info on Present Mods	1
3	Encoding Mods with Characters	2
4	Mapping Sites to Protein Sequence	3
5	Re-Doing Mapping with Gene IDs	4

1 Introduction

This vignette describes handling modifications of the peptides. Modifications can be biologically-relevant and introduced after protein translation, thus post-tranlational modifications or PTMs. Modification can also be introduced as artifact during sample processing. Here we use more general term - modification, that encompasses both PTMs, artifacts and intential modifications during the sample preparation.

2 Reading and Brief Info on Present Mods

```
> m <- MSnID(".")
> mzids <- system.file("extdata", "phospho.mzid.gz", package="MSnID")
> m <- read_mzIDs(m, mzids)

reading phospho.mzid.gz... DONE!
```

Method `report_mods` returns the table with masses and their counts within the dataset. This is a quick way to get insight on what is present. The other useful piece of information is the exact masses of modifications. In the later steps we will be using them to encode with characters, typically asterisk, which is a rather common representation of modified peptides.

```
> # to know the present mod masses
> report_mods(m)

      229.1629 57.021463735 79.966330925
           164           15           142
```

3 Encoding Mods with Characters

A common way to denote the position and type of modification is with a non-alphanumeric character. E.g. X.XXXX*XXXX.X means the modification at 4th residue. Typically it is most interest to map modifications that were dynamic in the MS/MS search. In this example TMT (229.1629) and cystein alkylation (57.021463735) are static modifications. The 79.966330925 is dynamic (that is may or maynot be present) phosphorylation.

Note, `add_mod_symbol` added `peptide_mod` column.

```
> m <- add_mod_symbol(m, mod_mass="79.966330925", symbol="*")
> x <- psms(m) %>%
+   distinct(modification, peptide, peptide_mod)
```

Sample of the table:

modification	peptide	peptide_mod
229.1629 (0), 79.966330925 (3), 79.966330925 (5)	R.SRTHSTSSSLGSGESPF.S	R.SRT*HS*TSSSLGSGESPF.S
229.1629 (0), 79.966330925 (8)	R.ASAVSELS.P.E	R.ASAVSELS*P.R.E
229.1629 (0), 79.966330925 (1), 79.966330925 (3)	R.SRSPLAIR.R	R.S*RS*PLAIR.R
229.1629 (0), 57.021463735 (8), 229.1629 (10)	R.ILPNPDECDK.V	R.ILPNPDECDK.V
229.1629 (0), 57.021463735 (15)	R.NTTSDVAVVVNDEHCR.T	R.NTTSDVAVVVNDEHCR.T

We can map additional modifications. Although typically, a given study focuses on one PTM at a time. Nonetheless:

```
> m <- add_mod_symbol(m, mod_mass="229.1629", symbol="#")
> m <- add_mod_symbol(m, mod_mass="57.021463735", symbol="^")
> x <- psms(m) %>%
+   distinct(modification, peptide, peptide_mod)
```

Sample of the table:

modification	peptide	peptide_mod
229.1629 (0), 79.966330925 (3), 79.966330925 (5)	R.SRTHSTSSSLGSGESPFGR.S	R.#SRT*HS*TSSSLGSGESPFGR.S
229.1629 (0), 79.966330925 (8)	R.ASAVSELSPR.E	R.#ASAVSELS*PR.E
229.1629 (0), 79.966330925 (1), 79.966330925 (3)	R.SRSPLAIR.R	R.#S*RS*PLAIR.R
229.1629 (0), 57.021463735 (8), 229.1629 (10)	R.ILPNPDECDK.V	R.#ILPNPDEC^DK#.V
229.1629 (0), 57.021463735 (15)	R.NTTSDVAVVVNDEHCR.T	R.#NTTSDVAVVVNDEHC^R.T

4 Mapping Sites to Protein Sequence

Somewhat conventional form of PTM notation (or non-synonymous mutations) is gene/protein ID followed by AA code in upper case, position in the sequence and original AA shows as low case. For example, phosphorylation of serine at position 473 of AKT1 would look like AKT1-S473s.

Besides *MSnID* object, the key component to mapping the modifications is the FASTA file with protein sequences.

```
> fst_path <- system.file("extdata", "for_phospho.fasta.gz", package="MSnID")
> fst <- readAAStringSet(fst_path)
```

When we link accession IDs with FASTA entry names, obviously they need to be in the same format. So in this case we have to trip the names in FASTA.

```
> names(fst) <- sub("(^[^ ]*) .*$", "\\1", names(fst))
```

The core method for mapping modification sites. The warning message it gives about extra characters in peptide sequences is about "#" and "^" we used to denote TMT modification and alkylation. They are ignored during mapping.

```
> m <- map_mod_sites(m, fst,
+                     accession_col = "accession",
+                     peptide_mod_col = "peptide_mod",
+                     mod_char = "*",
+                     site_delimiter = "lower")
> x <- psms(m) %>%
+   distinct(peptide_mod, SiteID)
```

peptide_mod	SiteID
R.#SRT*HS*TSSSLGSGESPFGR.S	sp Q9UGV2 NDRG3_HUMAN-T329tS331s
R.#ASAVSELS*PR.E	sp Q9Y2W1 TR150_HUMAN-S243s
R.#S*RS*PLAIR.R	sp Q9UQ35 SRRM2_HUMAN-S2044sS2046s
K.#NGVAAEVS*PAK#.E	sp Q9BW71 HIRP3_HUMAN-S125s
R.#S*GPRSAQRR.N	sp P84996 ALEX_HUMAN-S593s

5 Re-Doing Mapping with Gene IDs

The most common (human readable and somewhat comprehensible) identifier of proteins and corresponding genes is gene symbol. For example, **sp|P84996|ALEX_HUMAN** UniProt ID corresponds to **GNAS** gene symbol. In this section we'll remap UniProt IDs to gene symbols and report Site IDs in a more human readable way.

First, we'll download a table converting from one ID to another. There are multiple ways how one can get this type of table. In this example we implicitly use *AnnotationHub* package.

```
> conv_tab <- fetch_conversion_table("Homo sapiens", "UNIPROT", "SYMBOL")
> head(conv_tab)
```

	UNIPROT	SYMBOL
1	A8K052	A1BG
2	P04217	A1BG
3	Q68CK0	A1BG
4	Q8IYJ6	A1BG
5	Q96P39	A1BG
6	V9HWD8	A1BG

Re-mapping accessions from IDs indicated in the first columns of the `conv_tab` to the second. The accessions in the *MSnID* object may not be in exactly in the same form as in the database used to fetch `conv_tab` conversion table. Thus, there is the `extraction_pttrn` argument. It extracts the first matching group "\\1" as the proper ID. There are three suggested extraction patterns for UniProt, RefSeq and ENSEMBL. In case the accession is more complicated than that, user can provide a custom extraction pattern.

```
> head(accessions(m))

[1] "sp|Q9UGV2|NDRG3_HUMAN" "sp|075533|SF3B1_HUMAN" "sp|Q13442|HAP28_HUMAN"
[4] "sp|015075|DCLK1_HUMAN" "sp|Q9Y2W1|TR150_HUMAN" "sp|076094|SRP72_HUMAN"

> m <- remap_accessions(m, conv_tab, extraction_pttrn = "\\|([^-]+)(-\\d+)?\\|")
> head(accessions(m))

[1] "NDRG3" "SF3B1" "PDAP1" "DCLK1" "THRAP3" "SRP72"
```

Since we updated the accessions in the *MSnID* object, we need to provide FASTA file with corresponding entry names if we want to map the PTM sites. If such FASTA file isn't readily available, which is very likely if the *MSnID* object accessions converted to gene symbols. Entry names can be updated using the same conversion table.

```
> fst_path <- system.file("extdata", "for_phospho.fasta.gz", package="MSnID")
> fst_path_2 <- remap_fasta_entry_names(fst_path, conv_tab, "\\|([^-]+)(-\\d+)?\\|")
> library(Biostrings)
> readAAStringSet(fst_path)
```

Handling Modifications with *MSnID*

```
AAStringSet object of length 45:
      width seq                      names
[1]   715 MSSPKRSSKPSMSLAPSGSSMPT...DATTSKATLPGERSSSSSSSKLA sp|B3KS81|SRRM5_H...
[2]   740 MSFGRDMELEHFDERDKAQRYSR...NSESEDYSPSSSETVRSPNSPF sp|015075|DCLK1_H...
[3]   508 MTQTLKYASRVFHRVWAPELGA...VRPKTRTVLVPERSINLQFLDR sp|015528|CP27B_H...
[4]   247 MDAFTRFTNQTQGRDRLFRATQY...GLVSSIAGMITVAYPQMCLKTR sp|075192|PX11A_H...
[5]  1304 MAKIAKTHEDIEAQIREIQGKKA...HYPRIYNDDKNTYIRYELDYIL sp|075533|SF3B1_H...
...   ...   ...
[41]  2752 MYNGIGLPTPRSGTGNGYVQRNL...SHKRRRETSPRPMRHRSSRSP sp|Q9UQ35|SRRM2_H...
[42]  1087 MTTESGSDSESKPDQEAEPQAAA...DMSVTKVVVHKETEITPEDGED sp|Q9Y2J2|E41L3_H...
[43]   955 MSKTNKSKSGSRSSRSASRSR...IEDDESGTENREEKDNIQPTTE sp|Q9Y2W1|TR150_H...
[44]  1467 MSDESASGSDPDLDPDVELEDAE...EVGFSSNDDKDDDVIEVTGK sp|Q9Y4B4|ARIP4_H...
[45]   313 MSDLLLLGLIGGLTLLLLLTLLA...GTEPLGTTKWLWEPTAPEKGKE sp|Q9Y6I9|TX264_H...
```

```
> readAAStringSet(fst_path_2)
```

```
AAStringSet object of length 45:
      width seq                      names
[1]  1439 MASSETEIRWAEPGLGKGPQRRR...QMRSSLSADLRQAHSLRGSCLF AKNA
[2]  1491 MNGVAFCLVGIPRPEPRPPQLP...DTGSLQSQPPRRSAASRLHQCL ARHGAP23
[3]  3046 MRGRRRPPKQPAAPAAERCAPA...VQKLKGFKASRSHNNKLQSTAS BPTF
[4]  1249 MSSMWSEYTIIGVKIYFPYKAYP...EIEIKNFKSPSPSKNGMFPFGFK BRIP1
[5]   619 MAAAPPLSKAEYLKRYLSGADAG...FARLASKKAVEELAYKWSVEDM BUD13
...   ...   ...
[41]  313 MSDLLLLGLIGGLTLLLLLTLLA...GTEPLGTTKWLWEPTAPEKGKE TEX264
[42]  955 MSKTNKSKSGSRSSRSASRSR...IEDDESGTENREEKDNIQPTTE THRAP3
[43]  843 MDKENS DVSAAPADLKISNISVQ...PGVYTRVSNFVPIHKYVPSLL TMRSS7
[44]  979 MSPLKIHGPIRIRSMQTGITKWK...LETEKNSQSLSTEVGKTTRQAL USP37
[45]  241 MNSGRPETMENLPALYTIFQGEV...SKDSKAAKKKKKKKKKKKKHKE ZCCHC17
```

Now we can execute the same remapping, but using gene symbols as protein IDs.

```
> fst <- readAAStringSet(fst_path_2)
> m <- map_mod_sites(m, fst,
+                   accession_col = "accession",
+                   peptide_mod_col = "peptide_mod",
+                   mod_char = "*",
+                   site_delimiter = "lower")
> x <- psms(m) %>%
+   distinct(peptide_mod, SiteID)
```

Handling Modifications with *MSnID*

peptide_mod	SiteID
R.#SRT*HS*TSSSLGSGESPF.S	NDRG3-T329tS331s
R.#ASAVSELS*PR.E	THRAP3-S243s
R.#S*RS*PLAIR.R	SRRM2-S2044sS2046s
K.#NGVAAEVS*PAK#.E	HIRIP3-S125s
R.#S*GPRSAQRR.N	GNAS-S593s