

Package ‘AMARETTO’

October 15, 2019

Type Package

Title Regulatory Network Inference and Driver Gene Evaluation using Integrative Multi-Omics Analysis and Penalized Regression

Version 1.0.0

Date 2016-06-06

Author Jayendra Shinde, Celine Everaert, Shaimaa Bakr, Mohsen Nabian, Jishu Xu, Vincent Carey, Nathalie Pochet and Olivier Gevaert

Maintainer Olivier Gevaert <olivier.gevaert@gmail.com>

Depends R (>= 3.6), impute, doParallel, grDevices, dplyr, methods, ComplexHeatmap

Description Integrating an increasing number of available multi-omics cancer data remains one of the main challenges to improve our understanding of cancer. One of the main challenges is using multi-omics data for identifying novel cancer driver genes. We have developed an algorithm, called AMARETTO, that integrates copy number, DNA methylation and gene expression data to identify a set of driver genes by analyzing cancer samples and connects them to clusters of co-expressed genes, which we define as modules. We applied AMARETTO in a pancancer setting to identify cancer driver genes and their modules on multiple cancer sites. AMARETTO captures modules enriched in angiogenesis, cell cycle and EMT, and modules that accurately predict survival and molecular subtypes. This allows AMARETTO to identify novel cancer driver genes directing canonical cancer pathways.

License Apache License (== 2.0) + file LICENSE

LazyLoad yes

LazyData true

Encoding UTF-8

biocViews

StatisticalMethod,DifferentialMethylation,GeneRegulation,GeneExpression,MethylationArray,Transcription,Preproc

Suggests testthat, MASS, knitr

NeedsCompilation no

Imports callr (>= 3.0.0.9001), Matrix, Rcpp, BiocFileCache, DT, MultiAssayExperiment, circlize, curatedTCGADData, foreach, glmnet, httr, limma, matrixStats, readr, reshape2, tibble, rmarkdown, graphics, grid, parallel, stats, utils

Roxygen list(markdown = TRUE)

RoxygenNote 6.1.1.9000

LinkingTo Rcpp

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/AMARETTO>

git_branch RELEASE_3_9

git_last_commit a67539e

git_last_commit_date 2019-05-02

Date/Publication 2019-10-15

R topics documented:

AMARETTO_CreateModuleData	2
AMARETTO_CreateRegulatorPrograms	3
AMARETTO_Download	3
AMARETTO_EvaluateTestSet	4
AMARETTO_ExportResults	5
AMARETTO_HTMLreport	5
AMARETTO_Initialize	6
AMARETTO_Preprocess	8
AMARETTO_Run	8
AMARETTO_VisualizeModule	9
BatchData	10
Driver_Genes	10
ProcessedDataLIHC	11
Index	12

AMARETTO_CreateModuleData

AMARETTO_CreateModuleData

Description

AMARETTO_CreateModuleData

Usage

AMARETTO_CreateModuleData(AMARETTOinit, AMARETTOresults)

Arguments

AMARETTOinit List output from AMARETTO_Initialize().

AMARETTOresults

List output from AMARETTO_Run()

Value

result

Examples

```
data('ProcessedDataLIHC')
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
                                   NrModules = 2, VarPercentage = 50)
AMARETTOresults <- AMARETTO_Run(AMARETTOinit)
AMARETTO_MD <- AMARETTO_CreateModuleData(AMARETTOinit, AMARETTOresults)
```

AMARETTO_CreateRegulatorPrograms

AMARETTO_CreateRegulatorPrograms

Description

AMARETTO_CreateRegulatorPrograms

Usage

```
AMARETTO_CreateRegulatorPrograms(AMARETTOinit, AMARETTOresults)
```

Arguments

AMARETTOinit List output from AMARETTO_Initialize().
AMARETTOresults List output from AMARETTO_Run()

Value

result

Examples

```
data('ProcessedDataLIHC')
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
                                   NrModules = 2, VarPercentage = 50)
AMARETTOresults <- AMARETTO_Run(AMARETTOinit)
AMARETTO_RP <- AMARETTO_CreateRegulatorPrograms(AMARETTOinit,AMARETTOresults)
```

AMARETTO_Download

AMARETTO_Download

Description

Downloading TCGA dataset for AMARETTO analysis

Usage

```
AMARETTO_Download(CancerSite = "CHOL",
                  TargetDirectory = TargetDirectory)
```

Arguments

CancerSite TCGA cancer code for data download
 TargetDirectory Directory path to download data

Value

result

Examples

```
TargetDirectory <- file.path(getwd(),"Downloads/");dir.create(TargetDirectory)
CancerSite <- 'CHOL'
DataSetDirectories <- AMARETTO_Download(CancerSite,TargetDirectory = TargetDirectory)
```

AMARETTO_EvaluateTestSet

AMARETTO_EvaluateTestSet

Description

Code to evaluate AMARETTO on a new gene expression test set. Uses output from AMARETTO_Run() and CreateRegulatorData().

Usage

```
AMARETTO_EvaluateTestSet(AMARETTOresults = AMARETTOresults,
  MA_Data_TestSet = MA_Data_TestSet,
  RegulatorData_TestSet = RegulatorData_TestSet)
```

Arguments

AMARETTOresults AMARETTO output from AMARETTO_Run().
 MA_Data_TestSet Gene expression matrix from a test set (that was not used in AMARETTO_Run()).
 RegulatorData_TestSet Test regulator data from CreateRegulatorData().

Value

result

Examples

```
data('ProcessedDataLIHC')
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
  NrModules = 2, VarPercentage = 50)

AMARETTOresults <- AMARETTO_Run(AMARETTOinit)
AMARETTOtestReport <- AMARETTO_EvaluateTestSet(AMARETTOresults = AMARETTOresults,
  MA_Data_TestSet = AMARETTOinit$MA_matrix_Var,
  RegulatorData_TestSet = AMARETTOinit$RegulatorData)
```

 AMARETTO_ExportResults

AMARETTO_ExportResults

Description

Retrieve a download of all the data linked with the run (including heatmaps)

Usage

```
AMARETTO_ExportResults(AMARETTOinit, AMARETTOresults, data_address,
  Heatmaps = TRUE, CNV_matrix = NULL, MET_matrix = NULL)
```

Arguments

AMARETTOinit	AMARETTO initialize output
AMARETTOresults	AMARETTO results output
data_address	Directory to save data folder
Heatmaps	Output heatmaps as pdf
CNV_matrix	CNV_matrix
MET_matrix	MET_matrix

Value

result

Examples

```
data('ProcessedDataLIHC')
TargetDirectory <- file.path(getwd(),"Downloads/");dir.create(TargetDirectory)
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
  NrModules = 2, VarPercentage = 50)

AMARETTOresults <- AMARETTO_Run(AMARETTOinit)
AMARETTO_ExportResults(AMARETTOinit,AMARETTOresults,TargetDirectory,Heatmaps = FALSE)
```

 AMARETTO_HTMLreport

AMARETTO_HTMLreport

Description

Retrieve an interactive html report, including gene set enrichment analysis if asked for.

Usage

```
AMARETTO_HTMLreport(AMARETTOinit, AMARETTOresults, ProcessedData,
  SAMPLE_annotation = NULL, ID = NULL, VarPercentage,
  hyper_geo_test_bool = FALSE, hyper_geo_reference = NULL,
  output_address = "./", MSIGDB = FALSE, GMTURL = FALSE)
```

Arguments

AMARETTOinit	AMARETTO initialize output
AMARETTOresults	AMARETTO results output
ProcessedData	List of processed input data
SAMPLE_annotation	SAMPLE annotation will be added to heatmap
ID	ID column of the SAMPLE annotation data frame
VarPercentage	Original Var Percentage used
hyper_geo_test_bool	Boolean if a hyper geometric test needs to be performed. If TRUE provide a GMT file in the hyper_geo_reference parameter.
hyper_geo_reference	GMT file with gene sets to compare with.
output_address	Output directory for the html files.
MSIGDB	TRUE if gene sets were retrieved from MSIGDB. Links will be created in the report.
GMTURL	TRUE if second column of gmt contains URLs to gene set, FALSE if it contains a description

Value

result

Examples

```
## Not run:
data('ProcessedDataLIHC')
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
                                   NrModules = 2, VarPercentage = 50)

AMARETTOresults <- AMARETTO_Run(AMARETTOinit)

AMARETTO_HTMLreport(AMARETTOinit= AMARETTOinit,AMARETTOresults= AMARETTOresults,
                    ProcessedData = ProcessedDataLIHC,
                    VarPercentage=10,hyper_geo_test_bool=FALSE,
                    output_address='./')

## End(Not run)
```

AMARETTO_Initialize *AMARETTO_Initialize (version: reorder and filter MA_Matrix)*

Description

Code used to initialize the seed clusters for an AMARETTO run. Requires processed gene expressions (rna-seq or microarray), CNV (usually from a GISTIC run), and methylation (from MethylMix, provided in this package) data. Uses the function CreateRegulatorData() and results are fed into the function AMARETTO_Run().

Usage

```
AMARETTO_Initialize(ProcessedData = ProcessedData, Driver_list = NULL,
  NrModules, VarPercentage, PvalueThreshold = 0.001,
  RsquareThreshold = 0.1, pmax = 10, NrCores = 1, OneRunStop = 0,
  method = "union")
```

Arguments

ProcessedData	List of Expression, CNV and MethylMix data matrices, with genes in rows and samples in columns.
Driver_list	Custom list of driver genes to be considered in analysis
NrModules	How many gene co-expression modules should AMARETTO search for? Usually around 100 is acceptable, given the large number of possible driver-passenger gene combinations.
VarPercentage	Minimum percentage by variance for filtering of genes; for example, 75% would indicate that the CreateRegulatorData() function only analyses genes that have a variance above the 75th percentile across all samples.
PvalueThreshold	Threshold used to find relevant driver genes with CNV alterations: maximal p-value.
RsquareThreshold	Threshold used to find relevant driver genes with CNV alterations: minimal R-square value between CNV and gene expression data.
pmax	'pmax' variable for glmnet function from glmnet package; the maximum number of variables aver to be nonzero. Should not be changed by user unless she/he fully understands the AMARETTO algorithm and how its parameters choices affect model output.
NrCores	A numeric variable indicating the number of computer/server cores to use for parallelization. Default is 1, i.e. no parallelization. Please check your computer or server's computing capacities before increasing this number. Parallelization is done via the RParallel package. Mac vs. Windows environments may behave differently when using parallelization.
OneRunStop	OneRunStop
method	Perform union or intersection of the driver genes evaluated from the input data matrices and custom driver gene list provided.

Value

result

Examples

```
data('ProcessedDataLIHC')
data('Driver_Genes')
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
  NrModules = 2, VarPercentage = 50)

## Not run:
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
  Driver_list = Driver_Genes[['MSigDB']],
  NrModules = 2, VarPercentage = 50)

## End(Not run)
```

AMARETTO_Preprocess *AMARETTO_Preprocess*

Description

Wrapper code that analyzes process TCGA GISTIC (CNV) and gene expression (rna-seq or microarray) data via one call

Usage

```
AMARETTO_Preprocess(DataSetDirectories = DataSetDirectories,
  BatchData = BatchData)
```

Arguments

```
DataSetDirectories     DataSetDirectories
BatchData             BatchData
```

Value

result

Examples

```
## Not run:
TargetDirectory <- "Downloads" # path to data download directory
CancerSite <- 'CHOL'
DataSetDirectories <- AMARETTO_Download(CancerSite,TargetDirectory)
ProcessedData <- AMARETTO_Preprocess(DataSetDirectories,BatchData)

## End(Not run)
```

AMARETTO_Run *AMARETTO_Run Function to run AMARETTO, a statistical algorithm to identify cancer drivers by integrating a variety of omics data from cancer and normal tissue.*

Description

AMARETTO_Run Function to run AMARETTO, a statistical algorithm to identify cancer drivers by integrating a variety of omics data from cancer and normal tissue.

Usage

```
AMARETTO_Run(AMARETTOinit)
```

Arguments

```
AMARETTOinit     List output from AMARETTO_Initialize().
```


Value

result

Examples

```
data('ProcessedDataLIHC')
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
                                   NrModules = 2, VarPercentage = 50)
AMARETTOresults <- AMARETTO_Run(AMARETTOinit)
```

AMARETTO_VisualizeModule

AMARETTO_VisualizeModule

Description

Function to visualize the gene modules

Usage

```
AMARETTO_VisualizeModule(AMARETTOinit, AMARETTOresults, ProcessedData,
                          ModuleNr, SAMPLE_annotation = NULL, ID = NULL,
                          order_samples = NULL, printhM = FALSE)
```

Arguments

AMARETTOinit	List output from AMARETTO_Initialize().
AMARETTOresults	List output from AMARETTO_Run().
ProcessedData	List of processed input data
ModuleNr	Module number to visualize
SAMPLE_annotation	Matrix or Dataframe with sample annotation
ID	Column used as sample name
order_samples	Order samples in heatmap by mean or by clustering
printhM	Boolean print heatmap directly

Value

result

Examples

```
data('ProcessedDataLIHC')
AMARETTOinit <- AMARETTO_Initialize(ProcessedData = ProcessedDataLIHC,
                                   NrModules = 2, VarPercentage = 50)

AMARETTOresults <- AMARETTO_Run(AMARETTOinit)

AMARETTO_VisualizeModule(AMARETTOinit = AMARETTOinit, AMARETTOresults = AMARETTOresults,
                          ProcessedData = ProcessedDataLIHC, ModuleNr = 1)
```

BatchData

BatchData

Description

A dataset for conducting batch corection in TCGA samples

Usage

BatchData

Format

A data frame with 23263 observations and 3 variables:

Source

AMARETTO

Driver_Genes

Driver_Genes

Description

A list of cancer driver genes described in literature.

Usage

Driver_Genes

Format

List

Source

AMARETTO

ProcessedDataLIHC *ProcessedDataLIHC*

Description

A list of dataframes of processed toy example dataset from TCGA-LIHC.

Usage

ProcessedDataLIHC

Format

List

Source

AMARETTO

Index

*Topic **datasets**

BatchData, [10](#)

Driver_Genes, [10](#)

ProcessedDataLIHC, [11](#)

AMARETTO_CreateModuleData, [2](#)

AMARETTO_CreateRegulatorPrograms, [3](#)

AMARETTO_Download, [3](#)

AMARETTO_EvaluateTestSet, [4](#)

AMARETTO_ExportResults, [5](#)

AMARETTO_HTMLreport, [5](#)

AMARETTO_Initialize, [6](#)

AMARETTO_Preprocess, [8](#)

AMARETTO_Run, [8](#)

AMARETTO_VisualizeModule, [9](#)

BatchData, [10](#)

Driver_Genes, [10](#)

ProcessedDataLIHC, [11](#)