

# Package ‘HiCParser’

November 14, 2025

**Type** Package

**Title** Parser for HiC data in R

**Date** 2025-07-22

**Version** 1.3.0

**URL** <https://github.com/emaigne/HiCParser>

**BugReports** <https://github.com/emaigne/HiCParser/issues>

**Description** This package is a parser to import HiC data into R.  
It accepts several type of data: tabular files, Cooler `.cool`` or `.mcool`` files, Juicer `.hic`` files or HiC-Pro `.matrix`` and `.bed`` files.  
The HiC data can be several files, for several replicates and conditions.  
The data is formatted in an InteractionSet object.

**License** LGPL

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2

**biocViews** Software, HiC, DataImport

**Imports** data.table, InteractionSet, GenomicRanges,  
SummarizedExperiment, Rcpp (>= 1.0.12), S4Vectors, gtools,  
pbapply, BiocGenerics, Seqinfo

**LinkingTo** Rcpp

**Suggests** rhdf5, BiocStyle, knitr, sessioninfo, testthat (>= 3.0.0)

**Config/testthat/edition** 3

**VignetteBuilder** knitr

**git\_url** <https://git.bioconductor.org/packages/HiCParser>

**git\_branch** devel

**git\_last\_commit** a19d833

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.23

**Date/Publication** 2025-11-13

**Author** Zytnicki Matthias [aut],  
Maigné Élise [aut, cre]

**Maintainer** Maigné Élise <elise.maigne@inrae.fr>

## Contents

|                               |          |
|-------------------------------|----------|
| HiCParser-package . . . . .   | 2        |
| mergeInteractionSet . . . . . | 3        |
| parseCool . . . . .           | 3        |
| parseHiC . . . . .            | 5        |
| parseHiCPro . . . . .         | 6        |
| parseTabular . . . . .        | 7        |
| <b>Index</b>                  | <b>9</b> |

---

|                   |                                           |
|-------------------|-------------------------------------------|
| HiCParser-package | <i>A multiple format Hi-C data parser</i> |
|-------------------|-------------------------------------------|

---

## Description

This package is a parser to import HiC data into R. It accepts several type of data: tabular files, Cooler ‘.cool’ or ‘.mcool’ files, Juicer ‘.hic’ files or HiC-Pro ‘.matrix’ and ‘.bed’ files. The HiC data can be several files, for several replicates and conditions. The data is formatted in an InteractionSet object.

## Author(s)

**Maintainer:** Maigné Élise <elise.maigne@inrae.fr>

Authors:

- Zytnicki Matthias <matthias.zytnicki@inrae.fr>

## See Also

Useful links:

- <https://github.com/emaigne/HiCParser>
- Report bugs at <https://github.com/emaigne/HiCParser/issues>

---

|                     |                                         |
|---------------------|-----------------------------------------|
| mergeInteractionSet | <i>Merge two InteractionSet objects</i> |
|---------------------|-----------------------------------------|

---

**Description**

Merge two different [InteractionSet](#).

**Usage**

```
mergeInteractionSet(interactionSet1, interactionSet2, fill = NA)
```

**Arguments**

|                 |                                             |
|-----------------|---------------------------------------------|
| interactionSet1 | The first <a href="#">InteractionSet</a> .  |
| interactionSet2 | The second <a href="#">InteractionSet</a> . |
| fill            | Fill missing values with this.              |

**Value**

The merged [InteractionSet](#).

**Examples**

```
path <- system.file("extdata", "hicsample_21.cool", package = "HiCParser")
object1 <- parseCool(path, conditions = 1, replicates = 1)
# Creating an object with a different condition
object2 <- parseCool(path, conditions = 2, replicates = 1)
objectMerged <- mergeInteractionSet(object1, object2)
```

---

|           |                                       |
|-----------|---------------------------------------|
| parseCool | <i>Parser for data in cool format</i> |
|-----------|---------------------------------------|

---

**Description**

Parses interactions in .cool or .mcool format and returns an InteractionSet object.

**Usage**

```
parseCool(paths, binSize = NA, conditions, replicates)
```

**Arguments**

|            |                                                                                                                                                        |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| paths      | A vector of paths to .cool or .mcool files.                                                                                                            |
| binSize    | The resolution (span of each position in number of bases). Optionally provided to select the appropriate resolution in .mcool files. Defaults to NULL. |
| conditions | A vector of condition names repeated along the replicates.                                                                                             |
| replicates | A vector of replicate names repeated along the conditions.                                                                                             |

**Details**

To read .cool or .mcool files, the rhdf5 package is required. Please install it before running the function.

**Value**

An InteractionSet.

**Examples**

```
# EXAMPLE FOR .cool FORMAT
# Path to each file
pathsCool <- c(
  "path/to/condition-1.replicate-1.cool",
  "path/to/condition-1.replicate-2.cool",
  "path/to/condition-1.replicate-3.cool",
  "path/to/condition-2.replicate-1.cool",
  "path/to/condition-2.replicate-2.cool",
  "path/to/condition-2.replicate-3.cool"
)
# Condition and replicate of each file. Can be names instead of numbers.
conditions <- c(1, 1, 1, 2, 2, 2)
replicates <- c(1, 2, 3, 1, 2, 3)
if (FALSE) {
  library(rhdf5)
  object <- parseCool(
    paths,
    conditions = conditions,
    replicates = replicates
  )
}

# EXAMPLE FOR .mcool FORMAT
# Resolution
binSize <- 500000
# Path to each file
paths <- c(
  "path/to/condition-1.replicate-1.mcool",
  "path/to/condition-1.replicate-2.mcool",
  "path/to/condition-1.replicate-3.mcool",
  "path/to/condition-2.replicate-1.mcool",
  "path/to/condition-2.replicate-2.mcool",

```

```

    "path/to/condition-2.replicate-3.mcool"
  )
  # Condition and replicate of each file. Can be names instead of numbers.
  conditions <- c(1, 1, 1, 2, 2, 2)
  replicates <- c(1, 2, 3, 1, 2, 3)
  if (FALSE) {
    # Instantiation of data set
    library(rhdf5)
    object <- parseCool(
      paths,
      conditions = conditions,
      replicates = replicates,
      binSize = binSize
    )
  }
}

```

---

 parseHiC

*Parser for data in hic format*


---

## Description

Parses interactions in .hic format and returns an InteractionSet object.

## Usage

```
parseHiC(paths, binSize, conditions, replicates)
```

## Arguments

|            |                                                                                            |
|------------|--------------------------------------------------------------------------------------------|
| paths      | A vector of paths to .hic files.                                                           |
| binSize    | The resolution (span of each position in number of bases) to select within the .hic files. |
| conditions | A vector of condition names repeated along the replicates.                                 |
| replicates | A vector of replicate names repeated along the conditions.                                 |

## Value

An InteractionSet.

## Examples

```

# Path to each file
paths <- c(
  "path/to/condition-1.replicate-1.hic",
  "path/to/condition-1.replicate-2.hic",
  "path/to/condition-1.replicate-3.hic",
  "path/to/condition-2.replicate-1.hic",
  "path/to/condition-2.replicate-2.hic",

```

```

    "path/to/condition-2.replicate-3.hic"
  )
  # Replicate and condition of each file. Can be names instead of numbers.
  conditions <- c(1, 1, 1, 2, 2, 2)
  replicates <- c(1, 2, 3, 1, 2, 3)
  # Resolution to select
  binSize <- 500000
  if (FALSE) {
    # Instantiation of data set
    hic.experiment <- parseHiC(
      paths,
      conditions = conditions,
      replicates = replicates,
      binSize = binSize
    )
  }
}

```

---

 parseHiCPro

*Parser for HiCPro data*


---

## Description

Parses interactions in pairs of .matrix and .bed files and returns an InteractionSet object.

## Usage

```
parseHiCPro(matrixPaths, bedPaths, conditions, replicates)
```

## Arguments

|             |                                                            |
|-------------|------------------------------------------------------------|
| matrixPaths | A vector of paths to HiC-Pro matrix files.                 |
| bedPaths    | A vector of paths to HiC-Pro bed files.                    |
| conditions  | A vector of condition names repeated along the replicates. |
| replicates  | A vector of replicate names repeated along the conditions. |

## Value

An InteractionSet.

## Examples

```

# Path to each matrix file
matrixPaths <- c(
  "path/to/condition-1.replicate-1.matrix",
  "path/to/condition-1.replicate-2.matrix",
  "path/to/condition-1.replicate-3.matrix",
  "path/to/condition-2.replicate-1.matrix",
  "path/to/condition-2.replicate-2.matrix",
  "path/to/condition-2.replicate-3.matrix"
)

```

```

)

# Path to each bed file
bedPaths <- c(
  "path/to/condition-1.replicate-1.bed",
  "path/to/condition-1.replicate-2.bed",
  "path/to/condition-1.replicate-3.bed",
  "path/to/condition-2.replicate-1.bed",
  "path/to/condition-2.replicate-2.bed",
  "path/to/condition-2.replicate-3.bed"
)

# Condition and replicate of each file. Can be names instead of numbers.
conditions <- c(1, 1, 1, 2, 2, 2)
replicates <- c(1, 2, 3, 1, 2, 3)

if (FALSE) {
  # Instantiation of data set
  hic.experiment <- parseHiCPro(
    matrixPaths = matrixPaths,
    bedPaths = bedPaths,
    conditions = conditions,
    replicates = replicates
  )
}

```

---

parseTabular

*Parser for tabular data*


---

## Description

Read the file, produce an InteractionSet object.

## Usage

```
parseTabular(path, sep = '\t')
```

## Arguments

|      |                                                           |
|------|-----------------------------------------------------------|
| path | A path to a tabular file.                                 |
| sep  | The separator of the tabular file. Default to tabulation. |

## Details

Accepts a tabular file with chromosome, position 1, position 2, and multiple replicate columns listing interaction counts. Null interactions do not have to be listed. Values must be separated by tabulations. The header must be chromosome position 1 position 2 x.y x.y x.y ... with x replaced by condition names and y replaced by replicate names.

**Value**

An InteractionSet object.

**Examples**

```
path <- system.file("extdata", "hicsample_21.tsv", package = "HiCParser")
object <- parseTabular(path, sep = "\t")
```

# Index

HiCParser (HiCParser-package), [2](#)

HiCParser-package, [2](#)

InteractionSet, [3](#)

mergeInteractionSet, [3](#)

parseCool, [3](#)

parseHiC, [5](#)

parseHiCPro, [6](#)

parseTabular, [7](#)