Package 'biobroom'

November 13, 2025

Title Turn Bioconductor objects into tidy data frames

Version 1.43.0

Author Andrew J. Bass, David G. Robinson, Steve Lianoglou, Emily Nelson, John D. Storey, with contributions from Laurent Gatto

Maintainer John D. Storey <jstorey@princeton.edu> and Andrew J. Bass <ajbass@emory.edu>

Description This package contains methods for converting standard objects constructed by bioinformatics packages, especially those in Bioconductor, and converting them to tidy data. It thus serves as a complement to the broom package, and follows the same the tidy, augment, glance division of tidying methods. Tidying data makes it easy to recombine, reshape and visualize bioinformatics analyses.

biocViews MultipleComparison, DifferentialExpression, Regression, GeneExpression, Proteomics, DataImport

Depends R (>= 3.0.0), broom

License LGPL

LazyData true

Imports dplyr, tidyr, Biobase

Suggests limma, DESeq2, airway, ggplot2, plyr, GenomicRanges, testthat, magrittr, edgeR, qvalue, knitr, data.table, MSnbase, rmarkdown, SummarizedExperiment

VignetteBuilder knitr

URL https://github.com/StoreyLab/biobroom

BugReports https://github.com/StoreyLab/biobroom/issues

RoxygenNote 5.0.1

git_url https://git.bioconductor.org/packages/biobroom

git_branch devel

git_last_commit 825b1c8

git_last_commit_date 2025-10-29

Repository Bioconductor 3.23

Date/Publication 2025-11-13

Contents

augment_sva . . . 2
biobroom . . . 3
DESeq2_tidiers . . . 3
edgeR_tidiers . . . 5
ExpressionSet_tidiers . . . 6
hammer . . . 7
limma_tidiers . . . 8
list_tidiers . . . 10
MSnSet_tidiers . . . 11
qvalue_tidiers . . . 12
SummarizedExperiment_tidiers . . . 14
tidy.deSet . . . 15
tidy.GRanges . . . 16

Index **18**

`augment_sva` *Tidying methods for a sva list*

Description

These are methods for turning a sva list, from the sva package, into a tidy data frame. `tidy` returns a data.frame of the estimated surrogate variables, `glance` returns a data.frame of the posterior probabilities, and `glance` returns a data.frame with only the number of surrogate variables.

Usage

```
augment_sva(x, data, ...)

tidy_sva(x, addVar = NULL, ...)

glance_sva(x, ...)
```

Arguments

`x`	sva list
`data`	Original data
`...`	extra arguments (not used)
`addVar`	add additional coefficients to the estimated surrogate variables

Value

All tidying methods return a `data.frame` without rownames. The structure depends on the method chosen.

`augment` returns one row per gene. It always contains the columns

`pprob.gam`	Posterior probability each gene is affected by heterogeneity
`pprob.b`	Posterior probability each gene is affected by model

`tidy` returns the estimate surrogate variables.

`glance` returns the estimate surrogate variables.

`biobroom` *Convert Bioconductor Object into Tidy Data Frames*

Description

This package contains methods for converting standard objects constructed by bioinformatics packages, especially those in Bioconductor, and converting them to tidy data. It thus serves as a complement to the broom package, and follows the same the tidy, augment, glance division of tidying methods. Tidying data makes it easy to recombine, reshape and visualize bioinformatics analyses.

`DESeq2_tidiers` *Tidying methods for DESeq2 DESeqDataSet objects*

Description

This reshapes a DESeq2 expressionset object into a tidy format. If the dataset contains hypothesis test results (p-values and estimates), this summarizes one row per gene per possible contrast.

Usage

```
## S3 method for class 'DESeqDataSet'
tidy(x, colData = FALSE, intercept = FALSE, ...)

## S3 method for class 'DESeqResults'
tidy(x, ...)
```

Arguments

`x`	DESeqDataSet object
`colData`	whether colData should be included in the tidied output for those in the DESeqDataSet object. If dataset includes hypothesis test results, this is ignored
`intercept`	whether to include hypothesis test results from the (Intercept) term. If dataset does not include hypothesis testing, this is ignored
`...`	extra arguments (not used)

Details

`colDat=TRUE` adds covariates from colData to the data frame.

Value

If the dataset contains results (p-values and log2 fold changes), the result is a data frame with the columns

`term`	The contrast being tested, as given to `results`
`gene`	gene ID
`baseMean`	mean abundance level
`estimate`	estimated log2 fold change
`stderror`	standard error in log2 fold change estimate
`statistic`	test statistic
`p.value`	p-value
`p.adjusted`	adjusted p-value

If the dataset does not contain results (`DESeq` has not been run on it), `tidy` defaults to tidying the counts in the dataset:

`gene`	gene ID
`sample`	sample ID
`count`	number of reads in this gene in this sample

If `colData = TRUE`, it also merges this with the columns present in `colData(x)`.

Examples

```
# From DESeq2 documentation

if (require("DESeq2")) {
    dds <- makeExampleDESeqDataSet(betaSD = 1)

    tidy(dds)
    # With design included
    tidy(dds, colData=TRUE)

    # add a noise confounding effect
    colData(dds)$noise <- rnorm(nrow(colData(dds)))
    design(dds) <- (~ condition + noise)

    # perform differential expression tests
    ddsres <- DESeq(dds, test = "Wald")
    # now results are per-gene, per-term
    tidied <- tidy(ddsres)
    tidied

    if (require("ggplot2")) {
        ggplot(tidied, aes(p.value)) + geom_histogram(binwidth = .05) +
```

```
            facet_wrap(~ term, scale = "free_y")
    }
}
```

---

edgeR_tidiers *Tidiers for edgeR's differential expression objects*

Description

Tidy, augment and glance methods for turning edgeR objects into tidy data frames, where each row represents one observation and each column represents one column.

Usage

```
## S3 method for class 'DGEExact'
tidy(x, ...)

## S3 method for class 'DGEList'
tidy(x, addSamples = FALSE, ...)

## S3 method for class 'DGEList'
augment(x, data = NULL, ...)

## S3 method for class 'DGEExact'
glance(x, alpha = 0.05, p.adjust.method = "fdr",
  ...)
```

Arguments

x	DGEExact, DGEList object
...	extra arguments (not used)
addSamples	Merge information from samples. Default is FALSE.
data	merge data to augment. This is particularly useful when merging gene names or other per-gene information. Default is NULL.
alpha	Confidence level to test for significance
p.adjust.method	Method for adjusting p-values to determine significance; can be any in p.adjust.methods

Value

tidy defaults to tidying the counts in the dataset:

gene	gene ID
sample	sample ID
count	number of reads in this gene in this sample

If addSamples = TRUE, it also merges this with the sample information present in x$samples.

augment returns per-gene information (DGEList only)

glance returns one row with the columns (DGEExact only)

significant	number of significant genes using desired adjustment method and confidence level
comparison	The pair of groups compared by edgeR, delimited by /

Examples

```
if (require("edgeR")) {
    library(Biobase)
    data(hammer)
    hammer.counts <- exprs(hammer)[, 1:4]
    hammer.treatment <- phenoData(hammer)$protocol[1:4]

    y <- DGEList(counts=hammer.counts,group=hammer.treatment)
    y <- calcNormFactors(y)
    y <- estimateCommonDisp(y)
    y <- estimateTagwiseDisp(y)
    et <- exactTest(y)

    head(tidy(et))
    head(glance(et))
}
```

ExpressionSet_tidiers *Tidying methods for Biobase's ExpressionSet objects*

Description

Tidying methods for Biobase's ExpressionSet objects

Usage

```
## S3 method for class 'ExpressionSet'
tidy(x, addPheno = FALSE,
  assay = Biobase::assayDataElementNames(x)[1L], ...)
```

Arguments

x	ExpressionSet object
addPheno	whether columns should be included in the tidied output for those in the ExpressionSet's phenoData
assay	The name of the assayDataElement to use as the values to tidy. Defaults to assayDataElementNames(x)[1L], which is usually equivalent to exprs(x).
...	extra arguments (not used)

Details

addPheno=TRUE adds columns that are redundant (since they add per-sample information to a per-sample-per-gene data frame), but that are useful for some kinds of graphs and analyses.

Value

tidy returns a data frame with one row per gene-sample combination, with columns

gene	gene name
sample	sample name (from column names)
value	expressions on log2 scale

Examples

```
library(Biobase)
# import ExpressionSet object
data(hammer)

# Use tidy to extract genes, sample ids and measured value
tidy(hammer)
# add phenoType data
tidy(hammer, addPheno=TRUE)
```

---

hammer *ExpressionSet results from Hammer et al 2010*

Description

An ExpressionSet containing the results of the Hammer et al 2010 RNA-Seq study on the nervous system of rats (Hammer et al 2010).

This was downloaded from the ReCount database of analysis-ready RNA-Seq datasets (Frazee et al 2011).

Hammer, P., Banck, M. S., Amberg, R., Wang, C., Petznick, G., Luo, S., Khrebtukova, I., Schroth, G. P., Beyerlein, P., and Beutler, A. S. (2010). mRNA-seq with agnostic splice site discovery for nervous system transcriptomics tested in chronic pain. Genome research, 20(6), 847-860. http://www.ncbi.nlm.nih.gov/pmc/articles/PMC2877581/

Frazee, A. C., Langmead, B., and Leek, J. T. (2011). ReCount: a multi-experiment resource of analysis-ready RNA-seq gene count datasets. BMC Bioinformatics, 12, 449. http://bowtie-bio.sourceforge.net/recount/

Usage

```
hammer
```

Format

An object of class `ExpressionSet` with 29516 rows and 8 columns.

Value

ExpressionSet

`limma_tidiers` *Tidiers for the output of limma (linear models for microarray analysis)*

Description

Tidy, augment, and glance methods for MArrayLM objects, which contain the results of gene-wise linear models to microarray datasets. This class is the output of the lmFit and eBayes functions.

Usage

```
## S3 method for class 'MArrayLM'
tidy(x, intercept = FALSE, ...)

## S3 method for class 'MArrayLM'
augment(x, data, ...)

## S3 method for class 'MArrayLM'
glance(x, ...)

## S3 method for class 'MAList'
tidy(x, ...)

## S3 method for class 'EList'
tidy(x, addTargets = FALSE, ...)
```

Arguments

`x`	`MArrayLM`, `MAList`, `Elist` object
`intercept`	whether the `(Intercept)` term should be included (default FALSE)
`...`	extra arguments, not used
`data`	original expression matrix; if missing, `augment` returns only the computed per-gene statistics
`addTargets`	Add sample level information. Default is FALSE.

Details

Tidying this fit computes one row per coefficient per gene, while augmenting returns one row per gene, with per-gene statistics included. (This is thus a rare case where the `augment` output has more rows than the `tidy` output. This is a side effect of the fact that the input to limma is not tidy but rather a one-row-per-gene matrix).

Value

The output of tidying functions is always a data frame without rownames.

`tidy` returns one row per gene per coefficient. It always contains the columns

`gene`	The name of the gene (extracted from the rownames of the input matrix)
`term`	The coefficient being estimated
`estimate`	The estimate of each per-gene coefficient

Depending on whether the object comes from `eBayes`, it may also contain

`statistic`	Empirical Bayes t-statistic
`p.value`	p-value computed from t-statistic
`lod`	log-of-odds score

`augment` returns one row per gene, containing the original gene expression matrix if provided. It then adds columns containing the per-gene statistics included in the MArrayLM object, each prepended with a .:

`.gene`	gene ID, obtained from the rownames of the input
`.sigma`	per-gene residual standard deviation
`.df.residual`	per-gene residual degrees of freedom

The following columns may also be included, depending on which have been added by `lmFit` and `eBayes`:

`.AMean`	average intensity across probes
`.statistic`	moderated F-statistic
`.p.value`	p-value generated from moderated F-statistic
`.df.total`	total degrees of freedom per gene
`.df.residual`	residual degrees of freedom per gene
`.s2.prior`	prior estimate of residual variance
`.s2.post`	posterior estimate of residual variance

`glance` returns one row, containing

`rank`	rank of design matrix
`df.prior`	empirical Bayesian prior degrees of freedom
`s2.prior`	empirical Bayesian prior residual standard deviation

`tidy` returns a data frame with one row per gene-sample combination, with columns

`gene`	gene name
`sample`	sample name (from column names)
`value`	expressions on log2 scale

`tidy` returns a data frame with one row per gene-sample combination, with columns

gene	gene name
sample	sample name (from column names)
value	expressions on log2 scale
weight	present if weights is set
other columns	if present and if addTargets is set

Examples

```
if (require("limma")) {
    # create random data and design
    set.seed(2014)
    dat <- matrix(rnorm(1000), ncol=4)
    dat[, 1:2] <- dat[, 1:2] + .5  # add an effect
    rownames(dat) <- paste0("g", 1:nrow(dat))
    des <- data.frame(treatment = c("a", "a", "b", "b"),
                      confounding = rnorm(4))

    lfit <- lmFit(dat, model.matrix(~ treatment + confounding, des))
    eb <- eBayes(lfit)
    head(tidy(lfit))
    head(tidy(eb))

    if (require("ggplot2")) {
        # the tidied form puts it in an ideal form for plotting
        ggplot(tidy(lfit), aes(estimate)) + geom_histogram(binwidth=1) +
            facet_wrap(~ term)
        ggplot(tidy(eb), aes(p.value)) + geom_histogram(binwidth=.2) +
            facet_wrap(~ term)
    }
}
```

---

list_tidiers *Tidiers for return values from functions that aren't S3 objects*

Description

This method handles the return values of functions that return lists rather than S3 objects, such as sva, and therefore cannot be handled by S3 dispatch.

Usage

```
## S3 method for class 'list'
tidy(x, ...)

## S3 method for class 'list'
glance(x, ...)
```

Arguments

x	list object
...	extra arguments, passed to the tidying function

Details

Those tiders themselves are implemented as functions of the form tidy_<function> that are not exported.

MSnSet_tidiers *Tidying methods for Biobase's ExpressionSet objects*

Description

Tidying methods for Biobase's ExpressionSet objects

Usage

```
## S3 method for class 'MSnSet'
tidy(x, addPheno = FALSE, ...)
```

Arguments

x	MSnSet object
addPheno	whether columns should be included in the tidied output for those in the MSnSet's phenoData
...	extra arguments (not used)

Details

addPheno=TRUE adds columns that are redundant (since they add per-sample information to a per-sample-per-gene data frame), but that are useful for some kinds of graphs and analyses.

Value

tidy returns a data frame with one row per gene-sample combination, with columns

protein	protein name
sample	sample name (from column names)
value	protein quantitation data

Examples

```
if (require("MSnbase")) {
  library(MSnbase)
  # import MSnSet object
  data(msnset)

  # Use tidy to extract genes, sample ids and measured value
  tidy(msnset)
  # add phenoType data
  tidy(msnset, addPheno=TRUE)
}
```

`qvalue_tidiers` *Tidying methods for a qvalue object*

Description

These are methods for turning a qvalue object, from the qvalue package for false discovery rate control, into a tidy data frame. `augment` returns a data.frame of the original p-values combined with the computed q-values and local false discovery rates, `tidy` constructs a table showing how the estimate of pi0 (the proportion of true nulls) depends on the choice of the tuning parameter lambda, and `glance` returns a data.frame with only the chosen pi0 value.

Usage

```
## S3 method for class 'qvalue'
tidy(x, ...)

## S3 method for class 'qvalue'
augment(x, data, ...)

## S3 method for class 'qvalue'
glance(x, ...)
```

Arguments

`x`	qvalue object
`...`	extra arguments (not used)
`data`	Original data

Value

All tidying methods return a `data.frame` without rownames. The structure depends on the method chosen.

`tidy` returns one row for each choice of the tuning parameter lambda that was considered (argument `lambda` to qvalue), containing

lambda	the tuning parameter
pi0	corresponding estimate of pi0
smoothed	whether the estimate has been spline-smoothed)

If pi0.method="smooth", the pi0 estimates and smoothed values both appear in the table. If pi0.method="bootstrap", smoothed is FALSE for all entries.

augment returns a data.frame with

p.value	the original p-values given to qvalue
q.value	the computed q-values
lfdr	the local false discovery rate

glance returns a one-row data.frame containing

pi0	the estimated pi0 (proportion of nulls)
lambda	lambda used to compute pi0. Note that if pi0 is 1, this may be NA since it can be ambiguous which lambda was used

Examples

```
library(ggplot2)
if (require("qvalue")) {
set.seed(2014)

# generate p-values from many one sample t-tests: half of them null
oracle <- rep(c(0, .5), each=1000)
pvals <- sapply(oracle, function(mu) t.test(rnorm(15, mu))$p.value)
qplot(pvals)

q <- qvalue(pvals)

tidy(q)
head(augment(q))
glance(q)

# use augmented data to compare p-values to q-values
ggplot(augment(q), aes(p.value, q.value)) + geom_point()

# use tidy see how pi0 estimate changes with lambda, comparing
# to smoothed version
g <- ggplot(tidy(q), aes(lambda, pi0, color=smoothed)) + geom_line()
g

# show the chosen value
g + geom_hline(yintercept=q$pi0, lty=2)
}
```

SummarizedExperiment_tidiers *Tidying methods for Biobase's SummarizedExperiment objects*

Description

Tidying methods for Biobase's SummarizedExperiment objects

Usage

```
## S3 method for class 'RangedSummarizedExperiment'
tidy(x, addPheno = FALSE,
  assay = SummarizedExperiment::assayNames(x)[1L], ...)
```

Arguments

x	SummarizedExperiment object
addPheno	whether columns should be included in the tidied output for those in the SummarizedExperiment colData
assay	Which assay to return as the value column. Defaults to assays(x)[[1L]]
...	extra arguments (not used)

Details

addPheno=TRUE adds columns that are redundant (since they add per-sample information to a per-sample-per-gene data frame), but that are useful for some kinds of graphs and analyses.

Value

tidy returns a data frame with one row per gene-sample combination, with columns

gene	gene name
sample	sample name (from column names)
value	expressions

If addPheno is TRUE then information from colData is added.

Examples

```
if (require("SummarizedExperiment", "airway")) {
    data(airway)

    se <- airway
    tidy(se)
}
```

tidy.deSet *Tidying methods for edge's deSet object*

Description

Tidying methods for edge's deSet object

Usage

```
## S3 method for class 'deSet'
tidy(x, addPheno = FALSE, ...)

## S3 method for class 'deSet'
augment(x, data, ...)

## S3 method for class 'deSet'
glance(x, ...)
```

Arguments

x	deSet object
addPheno	whether columns should be included in the tidied output for those in the ExpressionSet's phenoData
...	extra arguments (not used)
data	Original data can be added. Default is NULL.

Details

addPheno=TRUE adds columns that are redundant (since they add per-sample information to a per-sample-per-gene data frame), but that are useful for some kinds of graphs and analyses.

Value

tidy returns a data frame with one row per gene-sample combination, with columns

gene	gene name
sample	sample name (from column names)
value	expressions on log2 scale

augment returns a data.frame with

p.value	the original p-values given to qvalue
q.value	the computed q-values
lfdr	the local false discovery rate

glance returns a data.frame with the model fits

`tidy.GRanges` *Tidying methods for GRanges and GRangesList objects.*

Description

Tidying methods for GRanges and GRangesList objects.

Usage

```
## S3 method for class 'GRanges'
tidy(x, ...)

## S3 method for class 'GRangesList'
tidy(x, ...)

## S3 method for class 'GRanges'
glance(x, ...)

## S3 method for class 'GRangesList'
glance(x, ...)
```

Arguments

`x`	GRanges or GRangesList object
`...`	Not used.

Value

All tidying methods return a `data.frame` without rownames. `tidy` returns one row for each range, which contains

- start of the range
- end of the range
- width (or length) of the range
- names of the range
- strand
- seqname Name of the sequence from which the range comes (usually the chromosome)
- metadata Any included metadata, (ie, score, GC content)

For `GRangesList`, there will also be a column representing which group the ranges comes from. `glance` returns a `data.frame` with the number of ranges, the number of sequences, and the number of groups (if applicable).

Examples

```
if (require("GenomicRanges", "airway")) {
data(airway)

# GRangesList object
air_gr <- rowRanges(airway)

tidy(air_gr)
glance(air_gr)

# GRanges object
air_gr <- rowRanges(airway)@unlistData

tidy(air_gr)
glance(air_gr)


}
```

Index

∗ **datasets**
    hammer, 7

assayDataElement, *6*
augment.deSet *(*tidy.deSet*)*, 15
augment.DGEList *(*edgeR_tidiers*)*, 5
augment.MArrayLM *(*limma_tidiers*)*, 8
augment.qvalue *(*qvalue_tidiers*)*, 12
augment_sva, 2

biobroom, 3
biobroom-package *(*biobroom*)*, 3

DESeq2_tidiers, 3

edgeR_tidiers, 5
ExpressionSet_tidiers, 6

glance.deSet *(*tidy.deSet*)*, 15
glance.DGEExact *(*edgeR_tidiers*)*, 5
glance.GRanges *(*tidy.GRanges*)*, 16
glance.GRangesList *(*tidy.GRanges*)*, 16
glance.list *(*list_tidiers*)*, 10
glance.MArrayLM *(*limma_tidiers*)*, 8
glance.qvalue *(*qvalue_tidiers*)*, 12
glance_sva *(*augment_sva*)*, 2

hammer, 7

limma_tidiers, 8
list_tidiers, 10

MSnSet_tidiers, 11

qvalue_tidiers, 12

SummarizedExperiment_tidiers, 14

tidy.DESeqDataSet *(*DESeq2_tidiers*)*, 3
tidy.DESeqResults *(*DESeq2_tidiers*)*, 3
tidy.deSet, 15
tidy.DGEExact *(*edgeR_tidiers*)*, 5
tidy.DGEList *(*edgeR_tidiers*)*, 5
tidy.EList *(*limma_tidiers*)*, 8
tidy.ExpressionSet
        *(*ExpressionSet_tidiers*)*, 6
tidy.GRanges, 16
tidy.GRangesList *(*tidy.GRanges*)*, 16
tidy.list *(*list_tidiers*)*, 10
tidy.MAList *(*limma_tidiers*)*, 8
tidy.MArrayLM *(*limma_tidiers*)*, 8
tidy.MSnSet *(*MSnSet_tidiers*)*, 11
tidy.qvalue *(*qvalue_tidiers*)*, 12
tidy.RangedSummarizedExperiment
        *(*SummarizedExperiment_tidiers*)*,
        14
tidy_sva *(*augment_sva*)*, 2