

# Package ‘xenLite’

November 14, 2025

**Date** 2024-09-19

**Title** Simple classes and methods for managing Xenium datasets

**Version** 1.5.0

**Description** Define a relatively light class for managing Xenium data using Bioconductor. Address use of parquet for coordinates, SpatialExperiment for assay and sample data. Address serialization and use of cloud storage.

**License** Artistic-2.0

**Encoding** UTF-8

**Depends** R (>= 4.1)

**Suggests** knitr, testthat, BiocStyle, yesno, terra,  
SpatialFeatureExperiment, SFEDData, tiff

**Imports** SpatialExperiment, BiocFileCache, Matrix, S4Vectors,  
SummarizedExperiment, methods, utils, EBImage, shiny,  
HDF5Array, arrow, ggplot2, SingleCellExperiment, TENxIO, dplyr,  
graphics, stats

**VignetteBuilder** knitr

**biocViews** Infrastructure

**RoxygenNote** 7.3.2

**URL** <https://github.com/vjcitn/xenLite>

**BugReports** <https://github.com/vjcitn/xenLite/issues>

**git\_url** <https://git.bioconductor.org/packages/xenLite>

**git\_branch** devel

**git\_last\_commit** 504f4e0

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.23

**Date/Publication** 2025-11-13

**Author** Vincent Carey [aut, cre] (ORCID:  
<<https://orcid.org/0000-0003-4046-0063>>)

**Maintainer** Vincent Carey <stvjc@channing.harvard.edu>

## Contents

|                                               |           |
|-----------------------------------------------|-----------|
| cacheMtif . . . . .                           | 2         |
| cacheSfeLungNtx . . . . .                     | 3         |
| cacheXenLuad . . . . .                        | 4         |
| cacheXenPdmelLite . . . . .                   | 4         |
| cacheXenProstLite . . . . .                   | 5         |
| clipRect . . . . .                            | 6         |
| demoapp . . . . .                             | 6         |
| e2sym . . . . .                               | 7         |
| e79sym . . . . .                              | 8         |
| getCellBoundaries . . . . .                   | 8         |
| getCellBoundaries,XenSPEP-method . . . . .    | 9         |
| getNucleusBoundaries . . . . .                | 9         |
| getNucleusBoundaries,XenSPEP-method . . . . . | 10        |
| getTranscripts . . . . .                      | 10        |
| getTranscripts,XenSPEP-method . . . . .       | 11        |
| ggprepSeg . . . . .                           | 11        |
| ingest_xen . . . . .                          | 12        |
| loadGeometry . . . . .                        | 13        |
| loadGeometry,XenSPEP-method . . . . .         | 13        |
| plotXenGgprep . . . . .                       | 14        |
| printXenGgprep . . . . .                      | 14        |
| resetParqPaths . . . . .                      | 15        |
| restoreZipXenSPEP . . . . .                   | 15        |
| show,XenSPEP-method . . . . .                 | 16        |
| viewSeg . . . . .                             | 16        |
| viewSegG2 . . . . .                           | 17        |
| XenSPEP . . . . .                             | 18        |
| XenSPEP-class . . . . .                       | 18        |
| zipXenSPEP . . . . .                          | 19        |
| [,XenSPEP,ANY,ANY,ANY-method . . . . .        | 19        |
| <b>Index</b>                                  | <b>21</b> |

---

|           |                                                                        |
|-----------|------------------------------------------------------------------------|
| cacheMtif | <i>cache and/or retrieve path to an ome.tif file for demonstration</i> |
|-----------|------------------------------------------------------------------------|

---

## Description

cache and/or retrieve path to an ome.tif file for demonstration

## Usage

```
cacheMtif(
  cache = BiocFileCache::BiocFileCache(),
  url =
    "https://mghe.osn.xsede.org/bir190004-bucket01/BiocXenData/morphology_focus_0001.ome.tif"
)
```

**Arguments**

|       |                                            |
|-------|--------------------------------------------|
| cache | defaults to BiocFileCache::BiocFileCache() |
| url   | location where tiff file can be retrieved  |

**Value**

path to cached resource

**Note**

The tiff file was retrieved after running `SFEData::XeniumOutput("v2")`, and depicts a pancreas tissue sample.

**Examples**

```
pa <- cacheMtif()
if (!requireNamespace("tiff")) stop("install tiff package to run this example")
x <- tiff::readTIFF(pa)
plot(0, xlim = c(0, 1000), ylim = c(0, 1000), xlab = " ", ylab = " ")
rasterImage(x * 5.5, 0, 0, 1000, 1000)
```

---

|                 |                                                                           |
|-----------------|---------------------------------------------------------------------------|
| cacheSfeLungNtx | <i>cache and/or retrieve path to an SFE of V1 lung demo data from 10x</i> |
|-----------------|---------------------------------------------------------------------------|

---

**Description**

cache and/or retrieve path to an SFE of V1 lung demo data from 10x

**Usage**

```
cacheSfeLungNtx(
  cache = BiocFileCache::BiocFileCache(),
  url = "https://mghp.osn.xsede.org/bir190004-bucket01/BiocXenData/sfeLung.zip"
)
```

**Arguments**

|       |                                            |
|-------|--------------------------------------------|
| cache | defaults to BiocFileCache::BiocFileCache() |
| url   | location where zip file can be retrieved   |

**Value**

path to cached resource

**Note**

Lacks transcript coordinates

---

|              |                                                                                                                  |
|--------------|------------------------------------------------------------------------------------------------------------------|
| cacheXenLuad | <i>cache and/or retrieve path to Xenium Lung Adenocarcinoma example data, zipped SPEP accompanied by parquet</i> |
|--------------|------------------------------------------------------------------------------------------------------------------|

---

### Description

cache and/or retrieve path to Xenium Lung Adenocarcinoma example data, zipped SPEP accompanied by parquet

### Usage

```
cacheXenLuad(
  cache = BiocFileCache::BiocFileCache(),
  url = "https://mgdp.osn.xsede.org/bir190004-bucket01/BiocXenData/luad_lite.zip"
)
```

### Arguments

|       |                                            |
|-------|--------------------------------------------|
| cache | defaults to BiocFileCache::BiocFileCache() |
| url   | location where zip file can be retrieved   |

### Value

path to cached resource

### Examples

```
if (interactive()) {
  pa <- cacheXenLuad()
  luad <- restoreZipXenSPEP(pa)
  print(luad)
  print(slot(luad, "cellbounds_path"))
  viewSeg(luad, xlim = c(4000, 4500), ylim = c(2000, 2500))
}
```

---

|                   |                                                        |
|-------------------|--------------------------------------------------------|
| cacheXenPdmelLite | <i>counts-in-memory version of melanoma 5k dataset</i> |
|-------------------|--------------------------------------------------------|

---

### Description

counts-in-memory version of melanoma 5k dataset

### Usage

```
cacheXenPdmelLite(
  cache = BiocFileCache::BiocFileCache(),
  url = "https://mgdp.osn.xsede.org/bir190004-bucket01/BiocXenData/pdmel_lite.zip"
)
```

**Arguments**

cache defaults to BiocFileCache::BiocFileCache()  
url location where zip file can be retrieved

**Value**

path to cached resource

**Examples**

```
if (interactive()) {  
  pa <- cacheXenPdmelLite()  
  pdmel_lite <- restoreZipXenSPEP(pa)  
  print(pdmel_lite)  
}
```

---

|                   |                                                        |
|-------------------|--------------------------------------------------------|
| cacheXenProstLite | <i>counts-in-memory version of prostate 5k dataset</i> |
|-------------------|--------------------------------------------------------|

---

**Description**

counts-in-memory version of prostate 5k dataset

**Usage**

```
cacheXenProstLite(  
  cache = BiocFileCache::BiocFileCache(),  
  url = "https://mgdp.osn.xsede.org/bir190004-bucket01/BiocXenData/prost_lite.zip"  
)
```

**Arguments**

cache defaults to BiocFileCache::BiocFileCache()  
url location where zip file can be retrieved

**Value**

path to cached resource

**Examples**

```
if (interactive()) {  
  pa <- cacheXenProstLite()  
  prost_lite <- restoreZipXenSPEP(pa)  
  print(prost_lite)  
}
```

---

|          |                                                                                                                                 |
|----------|---------------------------------------------------------------------------------------------------------------------------------|
| clipRect | <i>restrict XenSPEP to cells with centroids in specified rectangle, also restrict boundary and transcript location features</i> |
|----------|---------------------------------------------------------------------------------------------------------------------------------|

---

**Description**

restrict XenSPEP to cells with centroids in specified rectangle, also restrict boundary and transcript location features

**Usage**

```
clipRect(xsce, xlim, ylim)
```

**Arguments**

|      |                  |
|------|------------------|
| xsce | XenSPEP instance |
| xlim | numeric(2)       |
| ylim | numeric(2)       |

**Value**

XenSPEP instance

**Note**

Could be too RAM-hungry.

**Examples**

```
args(clipRect)
```

---

|         |                                       |
|---------|---------------------------------------|
| demoapp | <i>simple app to explore an image</i> |
|---------|---------------------------------------|

---

**Description**

simple app to explore an image

**Usage**

```
demoapp(simple = FALSE)
```

**Arguments**

|        |                                                        |
|--------|--------------------------------------------------------|
| simple | logical(1) if TRUE, use a cached tiff for illustration |
|--------|--------------------------------------------------------|

**Value**

No value returned, run for side effect of app initiation.

**Note**

Navigate file input control to location of tiffs

**Examples**

```
if (interactive()) demoapp(simple = TRUE)
```

---

e2sym

*helper function to map ENS ids to symbols*

---

**Description**

helper function to map ENS ids to symbols

**Usage**

```
e2sym(x)
```

**Arguments**

x                      character() mix of Ensembl Ids and other strings; the latter are left unchanged

**Value**

a vector like x with gene symbols from v79 mapping substituted where possible

**Examples**

```
e2sym(c("ABC", "ENSG00000213088", "ENSG00000107796", "ENSG00000163017"))
```

---

|        |                                                                 |
|--------|-----------------------------------------------------------------|
| e79sym | <i>mapping from ENSG to symbols based on EnsDb.Hsapiens.v79</i> |
|--------|-----------------------------------------------------------------|

---

**Description**

mapping from ENSG to symbols based on EnsDb.Hsapiens.v79

**Usage**

e79sym

**Format**

character()

**Value**

character vector

**Note**

named character vector with values gene symbols, name ENSG ids

**Examples**

data(e79sym)  
head(e79sym)

---

|                   |                                            |
|-------------------|--------------------------------------------|
| getCellBoundaries | <i>method for cell boundary extraction</i> |
|-------------------|--------------------------------------------|

---

**Description**

method for cell boundary extraction

**Usage**

getCellBoundaries(x)

**Arguments**

x                      instance of XenSPEP

**Value**

reference to ingested parquet

Examples

```
showMethods("getCellBoundaries")
```

---

|                                            |
|--------------------------------------------|
| getCellBoundaries,XenSPEP-method           |
| <i>method for cell boundary extraction</i> |

---

Description

method for cell boundary extraction

Usage

```
## S4 method for signature 'XenSPEP'  
getCellBoundaries(x)
```

Arguments

x                    instance of XenSPEP

Value

reference to ingested parquet

---

|                      |                                               |
|----------------------|-----------------------------------------------|
| getNucleusBoundaries | <i>method for nucleus boundary extraction</i> |
|----------------------|-----------------------------------------------|

---

Description

method for nucleus boundary extraction

Usage

```
getNucleusBoundaries(x)
```

Arguments

x                    instance of XenSPEP

Value

reference to ingested parquet

Examples

```
showMethods("getNucleusBoundaries")
```

---

|                                     |                                               |
|-------------------------------------|-----------------------------------------------|
| getNucleusBoundaries,XenSPEP-method |                                               |
|                                     | <i>method for nucleus boundary extraction</i> |

---

**Description**

method for nucleus boundary extraction

**Usage**

```
## S4 method for signature 'XenSPEP'  
getNucleusBoundaries(x)
```

**Arguments**

x                    instance of XenSPEP

**Value**

reference to ingested parquet

---

|                |                                         |
|----------------|-----------------------------------------|
| getTranscripts | <i>method for transcript extraction</i> |
|----------------|-----------------------------------------|

---

**Description**

method for transcript extraction

**Usage**

```
getTranscripts(x)
```

**Arguments**

x                    instance of XenSPEP

**Value**

reference to ingested parquet

**Examples**

```
showMethods("getTranscripts")
```

---

getTranscripts,XenSPEP-method  
*method for transcript extraction*

---

**Description**

method for transcript extraction

**Usage**

```
## S4 method for signature 'XenSPEP'  
getTranscripts(x)
```

**Arguments**

x                    instance of XenSPEP

**Value**

reference to ingested parquet

**Examples**

```
showMethods("getTranscripts")
```

---

ggprepSeg                    *prepare a XenSPEP for ggplot2 visualization*

---

**Description**

prepare a XenSPEP for ggplot2 visualization

**Usage**

```
ggprepSeg(xsce, xlim = c(5800, 6200), ylim = c(6300, 6700))
```

**Arguments**

xsce                    XenSPEP instance  
xlim                    numeric(2)  
ylim                    numeric(2)

**Value**

a list with components 'bounds' (data.frame including relevant colData rows (all colData variables) and cell boundary coordinates) and 'txdata', a filtered arrow Table.

**Note**

This is idiosyncratic. Quintiles of cell\_area (values in 'sizq') are produced, and transcript locations are filtered. A more general approach that allows selection of coloring of cells by feature characteristics is needed.

**Examples**

```
pa <- cacheXenLuad()
luad <- restoreZipXenSPEP(pa)
hh <- ggprepSeg(luad, c(4000, 4500), c(2000, 2500))
ggplot2::ggplot(hh$bounds, ggplot2::aes(
  x = vertex_x, y = vertex_y, group = cell_id,
  colour = sizq, fill = sizq
)) +
  ggplot2::geom_polygon(alpha = .5)
```

---

|            |                                                                                 |
|------------|---------------------------------------------------------------------------------|
| ingest_xen | <i>produce a pre-loaded XenSPEP (SpatialExperiment with parquet references)</i> |
|------------|---------------------------------------------------------------------------------|

---

**Description**

produce a pre-loaded XenSPEP (SpatialExperiment with parquet references)

**Usage**

```
ingest_xen(folder)
```

**Arguments**

folder                      character(1) 'standard' Xenium output folder

**Value**

instance of XenSPEP

**Examples**

```
chkns <- function(pkstring) {
  if (!requireNamespace(pkstring)) {
    message(sprintf("install %s to use this feature; returning NULL", pkstring))
    return(NULL)
  }
}
chkns("SFEData")
chkns("HDF5Array")
chkns("SingleCellExperiment")
if (requireNamespace("SFEData")) {
  td <- tempdir()
```

```

z <- SFEData::XeniumOutput("v2", td)
ii <- ingest_xen(file.path(td, "xenium2"))
print(validObject(ii))
plot(SpatialExperiment::spatialCoords(ii), pch = ".")
}

```

---

|              |                                              |
|--------------|----------------------------------------------|
| loadGeometry | <i>read and bind parquet data to XenSPEP</i> |
|--------------|----------------------------------------------|

---

**Description**

read and bind parquet data to XenSPEP

**Usage**

```
loadGeometry(x)
```

**Arguments**

x                      instance of XenSPEP

**Value**

instance of XenSPEP

---

|                                              |
|----------------------------------------------|
| loadGeometry, XenSPEP-method                 |
| <i>read and bind parquet data to XenSPEP</i> |

---

**Description**

read and bind parquet data to XenSPEP

**Usage**

```
## S4 method for signature 'XenSPEP'
loadGeometry(x)
```

**Arguments**

x                      instance of XenSPEP

**Value**

instance of XenSPEP

---

|               |                                                 |
|---------------|-------------------------------------------------|
| plotXenGgprep | <i>plot method for ggplot2-prepared XenSPEP</i> |
|---------------|-------------------------------------------------|

---

**Description**

plot method for ggplot2-prepared XenSPEP

**Usage**

```
plotXenGgprep(x, y, ...)
```

**Arguments**

|     |                                   |
|-----|-----------------------------------|
| x   | instance of S3 class 'xen_ggprep' |
| y   | not used                          |
| ... | not used                          |

**Value**

ggplot

**Note**

roxygen had problems with this

**Examples**

```
pa <- cacheXenLuad()
luad <- restoreZipXenSPEP(pa)
hh <- ggprepSeg(luad, c(4000, 4500), c(2000, 2500))
plotXenGgprep(hh)
```

---

|                |                                                  |
|----------------|--------------------------------------------------|
| printXenGgprep | <i>print method for ggplot2-prepared XenSPEP</i> |
|----------------|--------------------------------------------------|

---

**Description**

print method for ggplot2-prepared XenSPEP

**Usage**

```
printXenGgprep(x, ...)
```

**Arguments**

|     |                                   |
|-----|-----------------------------------|
| x   | instance of S3 class 'xen_ggprep' |
| ... | not used                          |

**Value**

operates with cat()

---

|                |                                                                |
|----------------|----------------------------------------------------------------|
| resetParqPaths | <i>utility for dealing with cached Xen_SPEP in temp folder</i> |
|----------------|----------------------------------------------------------------|

---

**Description**

utility for dealing with cached Xen\_SPEP in temp folder

**Usage**

```
resetParqPaths(xsp, base)
```

**Arguments**

|      |                                           |
|------|-------------------------------------------|
| xsp  | instance of XenSPEP                       |
| base | folder path where parquet files are found |

**Value**

XenSPEP instance

**Note**

Will prepend current folder path to parquet-oriented slot values.

---

|                   |                                                                  |
|-------------------|------------------------------------------------------------------|
| restoreZipXenSPEP | <i>use unzip, readRDS, and loadGeometry to restore a XenSPEP</i> |
|-------------------|------------------------------------------------------------------|

---

**Description**

use unzip, readRDS, and loadGeometry to restore a XenSPEP

**Usage**

```
restoreZipXenSPEP(zipf, exdir = tempdir())
```

**Arguments**

|       |                                                                 |
|-------|-----------------------------------------------------------------|
| zipf  | character(1) path to zip file created with 'zipXenSPEP'         |
| exdir | character(1) defaults to tempdir(), where contents are unpacked |

**Value**

instance of XenSPEP

**Note**

Session folder position will change with `setwd()`, `on.exit` ensures return to position when started.

**Examples**

```
# used implicitly
if (interactive()) {
  example(cacheXenLuad)
}
```

---

|                                  |                                   |
|----------------------------------|-----------------------------------|
| <code>show,XenSPEP-method</code> | <i>display aspects of XenSPEP</i> |
|----------------------------------|-----------------------------------|

---

**Description**

display aspects of XenSPEP

**Usage**

```
## S4 method for signature 'XenSPEP'
show(object)
```

**Arguments**

`object`                    instance of XenSPEP

**Value**

operates with `cat()`

---

|                      |                             |
|----------------------|-----------------------------|
| <code>viewSeg</code> | <i>naive polygon viewer</i> |
|----------------------|-----------------------------|

---

**Description**

naive polygon viewer

**Usage**

```
viewSeg(x, xlim, ylim, show_tx = FALSE, ...)
```

**Arguments**

|         |                                                                     |
|---------|---------------------------------------------------------------------|
| x       | instance of XenSPEP                                                 |
| xlim    | numeric(2) ordered vector of max and min on x                       |
| ylim    | numeric(2) ordered vector of max and min on y                       |
| show_tx | logical(1) display transcript locations if TRUE, defaults to FALSE. |
| ...     | passed to polygon()                                                 |

**Value**

run for side effect of plotting

**Note**

This is more RAM-sparing than clipRect followed by view.

**Examples**

```
luad <- cacheXenLuad()
pa <- cacheXenLuad()
luad <- restoreZipXenSPEP(pa)
rownames(luad) <- make.names(SummarizedExperiment::rowData(luad)$Symbol, unique = TRUE)
out <- viewSeg(luad, c(5800, 6300), c(1300, 1800), lwd = .5)
out$ncells
```

---

|           |                                                                                           |
|-----------|-------------------------------------------------------------------------------------------|
| viewSegG2 | <i>naive polygon viewer, will indicate presence of transcripts for two genes in cells</i> |
|-----------|-------------------------------------------------------------------------------------------|

---

**Description**

naive polygon viewer, will indicate presence of transcripts for two genes in cells

**Usage**

```
viewSegG2(x, xlim, ylim, gene1, gene2, show_tx = FALSE, ...)
```

**Arguments**

|         |                                                                                         |
|---------|-----------------------------------------------------------------------------------------|
| x       | instance of XenSPEP                                                                     |
| xlim    | numeric(2) ordered vector of max and min on x                                           |
| ylim    | numeric(2) ordered vector of max and min on y                                           |
| gene1   | character(1) gene to be checked, cell polygon will be filled if gene has non-zero count |
| gene2   | character(1) gene to be checked, cell polygon will be filled if gene has non-zero count |
| show_tx | logical(1) display transcript locations if TRUE, defaults to FALSE.                     |
| ...     | passed to polygon()                                                                     |

**Value**

Primarily for plotting. A list is invisibly returned with elements polys, ncells and call.

**Note**

This is more RAM-sparing than clipRect followed by view. Colors are pre-assigned for individual and joint occupancies in this draft of this visualizer.

**Examples**

```
luad <- cacheXenLuad()
pa <- cacheXenLuad()
luad <- restoreZipXenSPEP(pa)
rownames(luad) <- make.names(SummarizedExperiment::rowData(luad)$Symbol, unique = TRUE)
out <- viewSegG2(luad, c(5800, 6300), c(1300, 1800), lwd = .5, gene1 = "CD4", gene2 = "EPCAM")
legend(5800, 1370, fill = c("purple", "cyan", "pink"), legend = c("CD4", "EPCAM", "both"))
out$ncells
```

---

|         |                                                                        |
|---------|------------------------------------------------------------------------|
| XenSPEP | <i>XenSPEP (SpatialExperiment with parquet references) constructor</i> |
|---------|------------------------------------------------------------------------|

---

**Description**

XenSPEP (SpatialExperiment with parquet references) constructor

**Usage**

```
XenSPEP(folder)
```

**Arguments**

folder                      character(1) 'standard' Xenium output folder

**Value**

instance of XenSPEP

**Examples**

```
# is not used yet
args(XenSPEP)
```

---

|               |                                                         |
|---------------|---------------------------------------------------------|
| XenSPEP-class | <i>manage SpatialExperiment with parquet references</i> |
|---------------|---------------------------------------------------------|

---

**Description**

manage SpatialExperiment with parquet references

---

|            |                                                                 |
|------------|-----------------------------------------------------------------|
| zipXenSPEP | <i>serialize the collection of XenSPEP and parquet with zip</i> |
|------------|-----------------------------------------------------------------|

---

**Description**

serialize the collection of XenSPEP and parquet with zip

**Usage**

zipXenSPEP(xsp, targetfile)

**Arguments**

|            |                                          |
|------------|------------------------------------------|
| xsp        | instance of XenSPEP with geometry loaded |
| targetfile | character(1) destination of zip process  |

**Value**

output of zip()

**Note**

a .rds and three parquet files are zipped together for restoration by 'restoreZipXenSPEP'. The outcome is 'paste0(targetfile, ".zip")'.

**Examples**

zipXenSPEP

---

|                              |                                                                                   |
|------------------------------|-----------------------------------------------------------------------------------|
| [,XenSPEP,ANY,ANY,ANY-method | <i>formal bracket definition, that leaves parquet geometry information alone.</i> |
|------------------------------|-----------------------------------------------------------------------------------|

---

**Description**

formal bracket definition, that leaves parquet geometry information alone.

**Usage**

```
## S4 method for signature 'XenSPEP,ANY,ANY,ANY'
x[i, j, ..., drop = TRUE]
```

**Arguments**

|      |                                     |
|------|-------------------------------------|
| x    | instance of XenSPEP                 |
| i    | feature selection                   |
| j    | cell selection                      |
| ...  | passed to SpatialExperiment methods |
| drop | logical(1)                          |

**Value**

XenSPEP instance

**Note**

Gives a message and calls callNextMethod.

# Index

\* **datasets**  
    e79sym, [8](#)  
    [,XenSPEP,ANY,ANY,ANY-method, [19](#)

cacheMtif, [2](#)  
cacheSfeLungNtx, [3](#)  
cacheXenLuad, [4](#)  
cacheXenPdmelLite, [4](#)  
cacheXenProstLite, [5](#)  
clipRect, [6](#)

demoapp, [6](#)

e2sym, [7](#)  
e79sym, [8](#)

getCellBoundaries, [8](#)  
getCellBoundaries,XenSPEP-method, [9](#)  
getNucleusBoundaries, [9](#)  
getNucleusBoundaries,XenSPEP-method,  
    [10](#)  
getTranscripts, [10](#)  
getTranscripts,XenSPEP-method, [11](#)  
ggprepSeg, [11](#)

ingest\_xen, [12](#)

loadGeometry, [13](#)  
loadGeometry,XenSPEP-method, [13](#)

plotXenGgprep, [14](#)  
printXenGgprep, [14](#)

resetParqPaths, [15](#)  
restoreZipXenSPEP, [15](#)

show,XenSPEP-method, [16](#)

viewSeg, [16](#)  
viewSegG2, [17](#)

XenSPEP, [18](#)

XenSPEP-class, [18](#)  
zipXenSPEP, [19](#)