

Package ‘alabaster.string’

November 13, 2025

Title Save and Load Biostrings to/from File

Version 1.10.0

Date 2023-12-29

Description Save Biostrings objects to file artifacts, and load them back into memory.
This is a more portable alternative to serialization of such objects into RDS files.
Each artifact is associated with metadata for further interpretation;
downstream applications can enrich this metadata with context-specific properties.

License MIT + file LICENSE

Depends Biostrings, alabaster.base

Imports utils, methods, S4Vectors

Suggests BiocStyle, rmarkdown, knitr, testthat

VignetteBuilder knitr

RoxygenNote 7.2.3

biocViews DataImport, DataRepresentation

git_url <https://git.bioconductor.org/packages/alabaster.string>

git_branch RELEASE_3_22

git_last_commit 1014c54

git_last_commit_date 2025-10-29

Repository Bioconductor 3.22

Date/Publication 2025-11-13

Author Aaron Lun [aut, cre]

Maintainer Aaron Lun <infinite.monkeys.with.keyboards@gmail.com>

Contents

| | |
|--|----------|
| readXStringSet | 2 |
| saveObject,XStringSet-method | 2 |
| Index | 4 |

readXStringSet *Read an XStringSet from disk.*

Description

Read a [XStringSet](#) object from its on-disk representation. This is usually not directly called by users, but is instead called by dispatch in [readObject](#).

Usage

```
readXStringSet(path, metadata, ...)
```

Arguments

| | |
|----------|---|
| path | String containing a path to a directory, itself created using the saveObject method for XStringSet objects. |
| metadata | Named list of metadata for this object, see readObjectFile for details. |
| ... | Further arguments passed to internal altReadObject calls. |

Value

An [XStringSet](#) subclass containing DNA, RNA, protein or custom sequences. This may also be a [QualityScaledDNAStrngSet](#) with quality scores.

See Also

"[saveObject,XStringSet-method](#)", to save an [XStringSet](#) to disk.

Examples

```
library(Biostrings)
stuff <- DNAStrngSet(c("AAA", "CC", "G", "TTTT"))

tmp <- tempfile()
saveObject(stuff, tmp)
readObject(tmp)
```

saveObject,XStringSet-method
Save a XStringSet to disk

Description

Save a [XStringSet](#) to its on-disk representation.

Usage

```
## S4 method for signature 'XStringSet'
saveObject(x, path, ...)
```

Arguments

`x` A [XStringSet](#) or any of its subclasses such as a [QualityScaledXStringSet](#).
`path` String containing the path to a directory in which to save `x`.
`...` Further arguments to pass to specific methods.

Value

The contents of `x` are saved into a `path`, and `NULL` is invisibly returned.

Author(s)

Aaron Lun

See Also

[readXStringSet](#), to read the `XStringSet` back into the R session.

Examples

```
library(Biostrings)
stuff <- DNASTringSet(c("AAA", "CC", "G", "TTTT"))

tmp <- tempfile()
saveObject(stuff, tmp)
list.files(tmp, recursive=TRUE)
```

Index

altReadObject, [2](#)

loadXStringSet (readXStringSet), [2](#)

QualityScaledDNAStrngSet, [2](#)

QualityScaledXStringSet, [3](#)

readObject, [2](#)

readObjectFile, [2](#)

readXStringSet, [2, 3](#)

saveObject, [2](#)

saveObject, XStringSet-method, [2](#)

stageObject, XStringSet-method
(saveObject, XStringSet-method),
[2](#)

XStringSet, [2, 3](#)