

Package ‘DAPARdata’

November 13, 2025

Type Package

Title Data accompanying the DAPAR and Prostar packages

Version 1.40.0

Date 2023-01-14

Author Samuel Wieczorek [cre,aut],
Thomas Burger [aut],
Enora Fremy [aut]

Maintainer Samuel Wieczorek <samuel.wieczorek@cea.fr>

Description Mass-spectrometry based UPS proteomics data sets from Ramus C, Hovasse A, Marcellin M, Hesse AM, Mouton-Barbosa E, Bouyssie D, Vaca S, Carapito C, Chaoui K, Bruley C, Garin J, Cianferani S, Ferro M, Dorssaeler AV, Burllet-Schiltz O, Schaeffer C, Coute Y, Gonzalez de Peredo A.
Spiked proteomic standard dataset for testing label-free quantitative software and statistical methods. Data Brief. 2015 Dec 17;6:286-94 and Giai Gianetto, Q., Combes, F., Ramus, C., Bruley, C., Coute, Y., Burger, T. (2016). Calibration plot for proteomics: A graphical tool to visually check the assumptions underlying FDR control in quantitative experiments. Proteomics, 16(1), 29-32.

Depends R (>= 4.4.0), MSnbase

Suggests knitr, DAPAR, BiocStyle

Imports utils

License GPL-2

biocViews ExperimentData, MassSpectrometryData, Proteome

NeedsCompilation no

RoxygenNote 7.2.3

Encoding UTF-8

URL <http://www.prostar-proteomics.org/>

BugReports <https://github.com/edyp-lab/DAPARdata/issues>

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/DAPARdata>

git_branch RELEASE_3_22

git_last_commit 27fe19a

git_last_commit_date 2025-10-29

Repository Bioconductor 3.22

Date/Publication 2025-11-13

Contents

DAPARdata	2
Exp1_R25_pept	3
Exp1_R25_prot	4
Exp1_R2_pept	5
Exp1_R2_prot	6
Exp2_R100_pept	7
Exp2_R100_prot	8
Exp2_R10_pept	9
Exp2_R10_prot	10
Exp2_R2_pept	11
Exp2_R2_prot	12
Index	13

DAPARdata

Lists the datasets embebbedin DAPARdata

Description

Lists the datasets embebbedin DAPARdata

Usage

DAPARdata()

Examples

DAPARdata()

Exp1_R25_pept

Exp1_R25_pept dataset

Description

This dataset is the final outcome of a quantitative mass spectrometry-based proteomic analysis of two samples containing different concentrations of 48 human proteins (UPS1 standard from Sigma-Aldrich) within a constant yeast background (see Gai Gianetto et al. (2016) for details). It contains the abundance values of the different human and yeast peptides identified and quantified in these two conditions. The two conditions represent the measured abundances of peptides when respectively 25 fmol and 10 fmol of UPS1 human proteins were mixed with the yeast extract before mass spectrometry analyses. This results in a concentration ratio of 2.5. Three technical replicates were acquired for each condition.

The dataset is either available as a CSV file (see `inst/extdata/Exp1_R25_pept.txt`), or as a MSnSet structure (`Exp1_R25_pept`). In the latter case, the quantitative data are those of the raw intensities.

Usage

```
data(Exp1_R25_pept)
```

Format

An object of class MSnSet related to peptide quantification. It contains 6 samples divided into two conditions (25fmol and 10fmol) and 13918 peptides.

The data frame `exprs(Exp1_R25_pept)` contains six columns that are the quantitation of peptides for the six replicates.

The data frame `fData(Exp1_R25_pept)` contains the meta data about the peptides.

The data frame `pData(Exp1_R25_pept)` contains the experimental design and gives few informations about the samples.

Value

An object of class MSnSet related to peptides quantification.

References

Cox J., Hein M.Y., Lubner C.A., Paron I., Nagaraj N., Mann M. Accurate proteome-wide label-free quantification by delayed normalization and maximal peptide ratio extraction, termed MaxLFQ. *Mol Cell Proteomics*. 2014 Sep, 13(9):2513-26.

Gai Gianetto, Q., Combes, F., Ramus, C., Bruley, C., Coute, Y., Burger, T. (2016). Calibration plot for proteomics: A graphical tool to visually check the assumptions underlying FDR control in quantitative experiments. *Proteomics*, 16(1), 29-32.

Exp1_R25_prot

Exp1_R25_prot dataset

Description

This dataset is the final outcome of a quantitative mass spectrometry-based proteomic analysis of two samples containing different concentrations of 48 human proteins (UPS1 standard from Sigma-Aldrich) within a constant yeast background (see Gai Gianetto et al. (2016) for details). It contains the abundance values of the different human and yeast proteins identified and quantified in these two conditions. The two conditions represent the measured abundances of proteins when respectively 25 fmol and 10 fmol of UPS1 human proteins were mixed with the yeast extract before mass spectrometry analyses. This results in a concentration ratio of 2.5. Three technical replicates were acquired for each condition.

The dataset is either available as a CSV file (see `inst/extdata/Exp1_R25_prot.txt`), or as a MSnSet structure (`Exp1_R25_prot.MSnset`). In the latter case, the quantitative data are those of the raw intensities.

Usage

```
data(Exp1_R25_prot)
```

Format

An object of class MSnSet related to proteins quantification. It contains 6 samples divided into two conditions (25 fmol and 10 fmol) and 2384 proteins.

The data frame `exprs(Exp1_R25_prot)` contains six columns that are the quantitation of proteins for the six replicates.

The data frame `fData(Exp1_R25_prot)` contains the meta data about the proteins.

The data frame `pData(Exp1_R25_prot)` contains the experimental design and gives few informations about the samples.

Value

An object of class MSnSet related to proteins quantification.

References

Cox J., Hein M.Y., Lubner C.A., Paron I., Nagaraj N., Mann M. Accurate proteome-wide label-free quantification by delayed normalization and maximal peptide ratio extraction, termed MaxLFQ. *Mol Cell Proteomics*. 2014 Sep, 13(9):2513-26.

Gai Gianetto, Q., Combes, F., Ramus, C., Bruley, C., Coute, Y., Burger, T. (2016). Calibration plot for proteomics: A graphical tool to visually check the assumptions underlying FDR control in quantitative experiments. *Proteomics*, 16(1), 29-32.

Exp1_R2_pept

Exp1_R2_pept dataset

Description

This dataset is the final outcome of a quantitative mass spectrometry-based proteomic analysis of two samples containing different concentrations of 48 human proteins (UPS1 standard from Sigma-Aldrich) within a constant yeast background (see Gai Gianetto et al. (2016) for details). It contains the abundance values of the different human and yeast peptides identified and quantified in these two conditions. The two conditions represent the measured abundances of peptides when respectively 5 fmol and 10 fmol of UPS1 human proteins were mixed with the yeast extract before mass spectrometry analyses. This results in a concentration ratio of 2. Three technical replicates were acquired for each condition.

The dataset is either available as a CSV file (see `inst/extdata/Exp1_R2_pept.txt`), or as a MSnSet structure (`Exp1_R2_pept`). In the latter case, the quantitative data are those of the raw intensities.

Usage

```
data(Exp1_R2_pept)
```

Format

An object of class MSnSet related to peptide quantification. It contains 6 samples divided into two conditions (10fmol and 5fmol) and 14048 peptides.

The data frame `exprs(Exp1_R2_pept)` contains six columns that are the quantitation of peptides for the six replicates.

The data frame `fData(Exp1_R2_pept)` contains the meta data about the peptides.

The data frame `pData(Exp1_R2_pept)` contains the experimental design and gives few informations about the samples.

Value

An object of class MSnSet related to peptides quantification.

References

Cox J., Hein M.Y., Lubner C.A., Paron I., Nagaraj N., Mann M. Accurate proteome-wide label-free quantification by delayed normalization and maximal peptide ratio extraction, termed MaxLFQ. *Mol Cell Proteomics*. 2014 Sep, 13(9):2513-26.

Gai Gianetto, Q., Combes, F., Ramus, C., Bruley, C., Coute, Y., Burger, T. (2016). Calibration plot for proteomics: A graphical tool to visually check the assumptions underlying FDR control in quantitative experiments. *Proteomics*, 16(1), 29-32.

Exp1_R2_prot

Exp1_R2_prot dataset

Description

This dataset is the final outcome of a quantitative mass spectrometry-based proteomic analysis of two samples containing different concentrations of 48 human proteins (UPS1 standard from Sigma-Aldrich) within a constant yeast background (see Gaii Gianetto et al. (2016) for details). It contains the abundance values of the different human and yeast proteins identified and quantified in these two conditions. The two conditions represent the measured abundances of proteins when respectively 5 fmol and 10 fmol of UPS1 human proteins were mixed with the yeast extract before mass spectrometry analyses. This results in a concentration ratio of 2. Three technical replicates were acquired for each condition.

The dataset is either available as a CSV file (see `inst/extdata/Exp1_R2_prot.txt`), or as a MSnSet structure (`Exp1_R2_prot.MSnset`). In the latter case, the quantitative data are those of the raw intensities.

Usage

```
data(Exp1_R2_prot)
```

Format

An object of class MSnSet related to proteins quantification. It contains 6 samples divided into two conditions (10fmol and 5fmol) and 2394 proteins.

The data frame `exprs(Exp1_R2_prot)` contains six columns that are the quantitation of proteins for the six replicates.

The data frame `fData(Exp1_R2_prot)` contains the meta data about the proteins.

The data frame `pData(Exp1_R2_prot)` contains the experimental design and gives few informations about the samples.

Value

An object of class MSnSet related to proteins quantification.

References

Cox J., Hein M.Y., Lubner C.A., Paron I., Nagaraj N., Mann M. Accurate proteome-wide label-free quantification by delayed normalization and maximal peptide ratio extraction, termed MaxLFQ. *Mol Cell Proteomics*. 2014 Sep, 13(9):2513-26.

Gaii Gianetto, Q., Combes, F., Ramus, C., Bruley, C., Coute, Y., Burger, T. (2016). Calibration plot for proteomics: A graphical tool to visually check the assumptions underlying FDR control in quantitative experiments. *Proteomics*, 16(1), 29-32.

`Exp2_R100_pept`*Exp2_R100_pept dataset*

Description

This dataset is the final outcome of a quantitative mass spectrometry-based proteomic analysis of two samples containing different concentrations of 48 human proteins (UPS1 standard from Sigma-Aldrich) within a constant yeast background (see Ramus et al. (2015) for details). It contains the abundance values of the different human and yeast peptides identified and quantified in these two conditions. The two conditions represent the measured abundances of peptides when respectively 1 fmol and 100 fmol of UPS1 human proteins were mixed with the yeast extract before mass spectrometry analyses. This results in a concentration ratio of 100. Three technical replicates were acquired for each condition.

The dataset is either available as a CSV file (see `inst/extdata/Exp2_R100_pept.txt`), or as a `MSnSet` structure (`Exp2_R100_peptt.MSnset`). In the latter case, the quantitative data are those of the raw intensities.

Usage

```
data(Exp2_R100_pept)
```

Format

An object of class `MSnSet` related to peptides quantification. It contains 6 samples divided into two conditions (1 fmol and 100 fmol) and 5684 peptides.

The data frame `exprs(Exp2_R100_pept)` contains six columns that are the quantitation of peptides for the six replicates.

The data frame `fData(Exp2_R100_pept)` contains the meta data about the peptides

The data frame `pData(Exp2_R100_pept)` contains the experimental design and gives few informations about the samples.

Value

An object of class `MSnSet` related to peptides quantification.

References

Ramus C, Hovasse A, Marcellin M, Hesse AM, Mouton-Barbosa E, Bouyssie D, Vaca S, Carapito C, Chaoui K, Bruley C, Garin J, Cianferani S, Ferro M, Dorssaeler AV, Burlet-Schiltz O, Schaeffer C, Coute Y, Gonzalez de Peredo A. Spiked proteomic standard dataset for testing label-free quantitative software and statistical methods. *Data Brief*. 2015 Dec 17;6:286-94. PMID: 26862574.

Exp2_R100_prot

Exp2_R100_prot dataset

Description

This dataset is the final outcome of a quantitative mass spectrometry-based proteomic analysis of two samples containing different concentrations of 48 human proteins (UPS1 standard from Sigma-Aldrich) within a constant yeast background (see Ramus et al. (2015) for details). It contains the abundance values of the different human and yeast peptides identified and quantified in these two conditions. The two conditions represent the measured abundances of peptides when respectively 1 fmol and 100 fmol of UPS1 human proteins were mixed with the yeast extract before mass spectrometry analyses. This results in a concentration ratio of 100. Three technical replicates were acquired for each condition.

The dataset is either available as a CSV file (see `inst/extdata/Exp2_R100_prot.txt`), or as a MSnSet structure (`Exp2_R100_prot.MSnset`). In the latter case, the quantitative data are those of the raw intensities.

Usage

```
data(Exp2_R100_prot)
```

Format

An object of class MSnSet related to proteins quantification. It contains 6 samples divided into two conditions (1 fmol and 100 fmol) and 923 proteins.

The data frame `exprs(Exp2_R100_prot)` contains six columns that are the quantitation of proteins for the six replicates.

The data frame `fData(Exp2_R100_prot)` contains the meta data about the proteins.

The data frame `pData(Exp2_R100_prot)` contains the experimental design and gives few informations about the samples.

Value

An object of class MSnSet related to proteins quantification.

References

Ramus C, Hovasse A, Marcellin M, Hesse AM, Mouton-Barbosa E, Bouyssie D, Vaca S, Carapito C, Chaoui K, Bruley C, Garin J, Cianferani S, Ferro M, Dorssaeler AV, Burlet-Schiltz O, Schaeffer C, Coute Y, Gonzalez de Peredo A. Spiked proteomic standard dataset for testing label-free quantitative software and statistical methods. *Data Brief*. 2015 Dec 17;6:286-94. PMID: 26862574.

Exp2_R10_pept

Exp2_R10_pept dataset

Description

This dataset is the final outcome of a quantitative mass spectrometry-based proteomic analysis of two samples containing different concentrations of 48 human proteins (UPS1 standard from Sigma-Aldrich) within a constant yeast background (see Ramus et al. (2015) for details). It contains the abundance values of the different human and yeast peptides identified and quantified in these two conditions. The two conditions represent the measured abundances of peptides when respectively 10 fmol and 100 fmol of UPS1 human proteins were mixed with the yeast extract before mass spectrometry analyses. This results in a concentration ratio of 10. Three technical replicates were acquired for each condition.

The dataset is either available as a CSV file (see `inst/extdata/Exp2_R10_pept.txt`), or as a MSnSet structure (`Exp2_R10_pept.MSnset`). In the latter case, the quantitative data are those of the raw intensities.

Usage

```
data(Exp2_R10_pept)
```

Format

An object of class MSnSet related to peptides quantification. It contains 6 samples divided into two conditions (10 fmol and 100 fmol) and 5633 peptides.

The data frame `exprs(Exp2_R10_pept)` contains six columns that are the quantitation of peptides for the six replicates.

The data frame `fData(Exp2_R10_pept)` contains the meta data about the peptides.

The data frame `pData(Exp2_R10_pept)` contains the experimental design and gives few informations about the samples.

Value

An object of class MSnSet related to peptides quantification.

References

Ramus C, Hovasse A, Marcellin M, Hesse AM, Mouton-Barbosa E, Bouyssie D, Vaca S, Carapito C, Chaoui K, Bruley C, Garin J, Cianferani S, Ferro M, Dorssaeler AV, Burlet-Schiltz O, Schaeffer C, Coute Y, Gonzalez de Peredo A. Spiked proteomic standard dataset for testing label-free quantitative software and statistical methods. *Data Brief*. 2015 Dec 17;6:286-94. PMID: 26862574.

Exp2_R10_prot

Exp2_R10_prot dataset

Description

This dataset is the final outcome of a quantitative mass spectrometry-based proteomic analysis of two samples containing different concentrations of 48 human proteins (UPS1 standard from Sigma-Aldrich) within a constant yeast background (see Ramus et al. (2015) for details). It contains the abundance values of the different human and yeast peptides identified and quantified in these two conditions. The two conditions represent the measured abundances of peptides when respectively 10 fmol and 100 fmol of UPS1 human proteins were mixed with the yeast extract before mass spectrometry analyses. This results in a concentration ratio of 10. Three technical replicates were acquired for each condition.

The dataset is either available as a CSV file (see `inst/extdata/Exp2_R10_prot.txt`), or as a `MSnSet` structure (`Exp2_R10_prot.MSnset`). In the latter case, the quantitative data are those of the raw intensities.

Usage

```
data(Exp2_R10_prot)
```

Format

An object of class `MSnSet` related to proteins quantification. It contains 6 samples divided into two conditions (10 fmol and 100 fmol) and 948 proteins.

The data frame `exprs(Exp2_R10_prot)` contains six columns that are the quantitation of proteins for the six replicates.

The data frame `fData(Exp2_R10_prot)` contains the meta data about the proteins.

The data frame `pData(Exp2_R10_prot)` contains the experimental design and gives few informations about the samples.

Value

An object of class `MSnSet` related to proteins quantification.

References

Ramus C, Hovasse A, Marcellin M, Hesse AM, Mouton-Barbosa E, Bouyssie D, Vaca S, Carapito C, Chaoui K, Bruley C, Garin J, Cianferani S, Ferro M, Dorssaeler AV, Burlet-Schiltz O, Schaeffer C, Coute Y, Gonzalez de Peredo A. Spiked proteomic standard dataset for testing label-free quantitative software and statistical methods. *Data Brief*. 2015 Dec 17;6:286-94. PMID: 26862574.

Exp2_R2_pept

Exp2_R2_pept dataset

Description

This dataset is the final outcome of a quantitative mass spectrometry-based proteomic analysis of two samples containing different concentrations of 48 human proteins (UPS1 standard from Sigma-Aldrich) within a constant yeast background (see Ramus et al. (2015) for details). It contains the abundance values of the different human and yeast peptides identified and quantified in these two conditions. The two conditions represent the measured abundances of peptides when respectively 25 fmol and 50 fmol of UPS1 human proteins were mixed with the yeast extract before mass spectrometry analyses. This results in a concentration ratio of 2. Three technical replicates were acquired for each condition.

The dataset is either available as a CSV file (see `inst/extdata/Exp2_R2_pept.txt`), or as a MSnSet structure (`Exp2_R2_pept.MSnset`). In the latter case, the quantitative data are those of the raw intensities.

Usage

```
data(Exp2_R2_pept)
```

Format

An object of class MSnSet related to peptides quantification. It contains 6 samples divided into two conditions (25fmol and 50fmol) and 5390 peptides.

The data frame `exprs(Exp2_R2_pept)` contains six columns that are the quantitation of peptides for the six replicates.

The data frame `fData(Exp2_R2_pept)` contains the meta data about the peptides

The data frame `pData(Exp2_R2_pept)` contains the experimental design and gives few informations about the samples.

Value

An object of class MSnSet related to peptides quantification.

References

Ramus C, Hovasse A, Marcellin M, Hesse AM, Mouton-Barbosa E, Bouyssie D, Vaca S, Carapito C, Chaoui K, Bruley C, Garin J, Cianferani S, Ferro M, Dorssaeler AV, Burlet-Schiltz O, Schaeffer C, Coute Y, Gonzalez de Peredo A. Spiked proteomic standard dataset for testing label-free quantitative software and statistical methods. *Data Brief*. 2015 Dec 17;6:286-94. PMID: 26862574.

Exp2_R2_prot

Exp2_R2_prot dataset

Description

This dataset is the final outcome of a quantitative mass spectrometry-based proteomic analysis of two samples containing different concentrations of 48 human proteins (UPS1 standard from Sigma-Aldrich) within a constant yeast background (see Ramus et al. (2015) for details). It contains the abundance values of the different human and yeast peptides identified and quantified in these two conditions. The two conditions represent the measured abundances of peptides when respectively 25 fmol and 50 fmol of UPS1 human proteins were mixed with the yeast extract before mass spectrometry analyses. This results in a concentration ratio of 2. Three technical replicates were acquired for each condition.

The dataset is either available as a CSV file (see `inst/extdata/Exp2_R2_prot.txt`), or as a MSnSet structure (`Exp2_R2_prot.MSnset`). In the latter case, the quantitative data are those of the raw intensities.

Usage

```
data(Exp2_R2_prot)
```

Format

An object of class MSnSet related to proteins quantification. It contains 6 samples divided into two conditions (25 fmol and 50 fmol) and 948 proteins.

The data frame `exprs(Exp2_R2_prot)` contains six columns that are the quantitation of proteins for the six replicates.

The data frame `fData(Exp2_R2_prot)` contains the meta data about the proteins.

The data frame `pData(Exp2_R2_prot)` contains the experimental design and gives few informations about the samples.

Value

An object of class MSnSet related to proteins quantification.

References

Ramus C, Hovasse A, Marcellin M, Hesse AM, Mouton-Barbosa E, Bouyssie D, Vaca S, Carapito C, Chaoui K, Bruley C, Garin J, Cianferani S, Ferro M, Dorssaele AV, Burlet-Schiltz O, Schaeffer C, Coute Y, Gonzalez de Peredo A. Spiked proteomic standard dataset for testing label-free quantitative software and statistical methods. *Data Brief*. 2015 Dec 17;6:286-94. PMID: 26862574.

Index

* datasets

- Exp1_R25_pept, [3](#)
- Exp1_R25_prot, [4](#)
- Exp1_R2_pept, [5](#)
- Exp1_R2_prot, [6](#)
- Exp2_R100_pept, [7](#)
- Exp2_R100_prot, [8](#)
- Exp2_R10_pept, [9](#)
- Exp2_R10_prot, [10](#)
- Exp2_R2_pept, [11](#)
- Exp2_R2_prot, [12](#)

* data

- Exp1_R25_pept, [3](#)
- Exp1_R25_prot, [4](#)
- Exp1_R2_pept, [5](#)
- Exp1_R2_prot, [6](#)
- Exp2_R100_pept, [7](#)
- Exp2_R100_prot, [8](#)
- Exp2_R10_pept, [9](#)
- Exp2_R10_prot, [10](#)
- Exp2_R2_pept, [11](#)
- Exp2_R2_prot, [12](#)

DAPARdata, [2](#)

- Exp1_R25_pept, [3](#)
- Exp1_R25_prot, [4](#)
- Exp1_R2_pept, [5](#)
- Exp1_R2_prot, [6](#)
- Exp2_R100_pept, [7](#)
- Exp2_R100_prot, [8](#)
- Exp2_R10_pept, [9](#)
- Exp2_R10_prot, [10](#)
- Exp2_R2_pept, [11](#)
- Exp2_R2_prot, [12](#)