

# Package ‘harbChIP’

November 13, 2025

**Title** Experimental Data Package: harbChIP

**Description** data from a yeast ChIP-chip experiment

**Version** 1.48.0

**Author** VJ Carey

**Maintainer** VJ Carey <stvjc@channing.harvard.edu>

**Depends** R (>= 2.10.0), tools, utils, IRanges, Biobase (>= 2.5.5),  
Biostrings

**Imports** methods, stats

**License** Artistic-2.0

**biocViews** ExperimentData, Saccharomyces\_cerevisiae\_Data,  
SequencingData

**git\_url** <https://git.bioconductor.org/packages/harbChIP>

**git\_branch** RELEASE\_3\_22

**git\_last\_commit** f26dab5

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.22

**Date/Publication** 2025-11-13

## Contents

|                              |          |
|------------------------------|----------|
| allhex . . . . .             | 2        |
| buildUpstreamSeqs2 . . . . . | 2        |
| chkMotif4TF . . . . .        | 3        |
| harbChIP . . . . .           | 4        |
| sceUpstr . . . . .           | 4        |
| upstreamSeqs-class . . . . . | 5        |
| <b>Index</b>                 | <b>7</b> |

---

|        |   |
|--------|---|
| allhex | <i>utility function: get all hexamers in upstream sequence for an ORF</i> |
|--------|---|

---

**Description**

utility function: get all hexamers in upstream sequence for an ORF

**Usage**

```
allhex(orf, usobj)
```

**Arguments**

|       |                            |
|-------|----------------------------|
| orf   | character string, ORF name |
| usobj | upstreamSeqs object        |

**Details**

computes Biostrings Views

**Value**

computes Biostrings Views

**Author(s)**

Vince Carey <stvjc@channing.harvard.edu>

**Examples**

```
data(sceUpstr)
allhex("YAL001C", sceUpstr)
```

---

|                    |  |
|--------------------|--|
| buildUpstreamSeqs2 | <i>workflow component – build an upstreamSeqs instance from a FASTA read</i> |
|--------------------|--|

---

**Description**

workflow component – build an upstreamSeqs instance from a FASTA read

**Usage**

```
buildUpstreamSeqs2(fastaRead, organism="sce", provenance="harmen")
```

**Arguments**

|            |   |
|------------|---|
| fastaRead  | results of a readFASTA from Biostrings    |
| organism   | string naming organism                    |
| provenance | string or structure describing provenance |

**Details**

generates an instance of upstreamSeqs

**Value**

generates an instance of upstreamSeqs

**Author(s)**

Vince Carey <stvjc@channing.harvard.edu>

**Examples**

```
# x = readFASTA(...)
# y = buildUpstreamSeqs2(x)
```

---

|             |   |
|-------------|---|
| chkMotif4TF | <i>analyze relationship between motif frequency and binding intensity for selected motif and TF</i> |
|-------------|---|

---

**Description**

analyze relationship between motif frequency and binding intensity for selected motif and TF

**Usage**

```
chkMotif4TF(motif, TF, chset, upstr, bthresh=2, countthresh=0)
```

**Arguments**

|             |  |
|-------------|--|
| motif       | character string in alphabet known to Biostrings                                     |
| TF          | name of a TF (sample name in the ChIP-chip data structure chset)                     |
| chset       | an ExpressionSet instance harboring ChIP-chip data                                   |
| upstr       | an instance of upstreamSeqs  |
| bthresh     | threshold for binding intensity results to declare TF 'bound' to the upstream region |
| countthresh | threshold for motif count to be considered 'present' in upstream region              |

**Details**

Uses [countPattern](#) to perform motif count.

**Value**

a list with elements call, table, and test, the latter providing the result of [fisher.test](#)

**Author(s)**

Vince Carey <stvjc@channing.harvard.edu>

**Examples**

```
# slow
## Not run:
data(harbChIP)
data(sceUpstr)
chkMotif4TF("CGGCCG", "RDS1", harbChIP, sceUpstr)

## End(Not run)
```

---

 harbChIP

*Experimental Data Package: harbChIP*


---

**Description**

binding ratios and intergenic region data from a ChIP-chip experiment in yeast

**Usage**

```
data(harbChIP)
```

**Format**

The format is: An ExpressionSetObject with covariates:

- txFac: transcription factor symbol from Harbison website CSV file columnnames

**Note**

derived from web site [jura.wi.mit.edu/young\\_public/regulatory\\_code/GWLD.html](http://jura.wi.mit.edu/young_public/regulatory_code/GWLD.html), binding ratios

**Examples**

```
data(harbChIP)
harbChIP
experimentData(harbChIP)
exprs(harbChIP)[1:6,1:7]
dim(exprs(harbChIP))
pData(featureData(harbChIP))[1:6,]
```

---

 sceUpstr

*Biostrings representations of S. cerevisiae upstream regions*


---

**Description**

Biostrings representations of S. cerevisiae upstream regions

**Usage**

```
data(sceUpstr)
```

**Details**

environment-based S4 object with DNAstring elements

**Value**

environment-based S4 object with DNAstring elements

**Author(s)**

Vince Carey <stvjc@channing.harvard.edu>

**Examples**

```
data(sceUpstr)
sceUpstr
getUpstream("YAL001C", sceUpstr)
```

---

upstreamSeqs-class     *Class "upstreamSeqs"*

---

**Description**

Container for a collection of upstream sequences

**Objects from the Class**

Objects can be created by calls of the form `new("upstreamSeqs", ...)`. Environments are used to store collections of DNAstrings.

**Slots**

```
seqs: Object of class "environment" ~~
chrom: Object of class "environment" ~~
revComp: Object of class "environment" ~~
type: Object of class "environment" ~~
organism: Object of class "character" ~~
provenance: Object of class "ANY" ~~
```

**Methods**

```
Nmers signature(n = "numeric", orf = "character", usobj = "upstreamSeqs"): obtain all
subsequences of length n as view elements of a DNA string
keys signature(x = "upstreamSeqs"): ...
organism signature(x = "upstreamSeqs"): ...
seqs signature(x = "upstreamSeqs"): ...
show signature(object = "upstreamSeqs"): ...
```

**Author(s)**

Vince Carey <stvjc@channing.harvard.edu>

**Examples**

```
showClass("upstreamSeqs")  
data(sceUpstr)  
sceUpstr  
keys(sceUpstr)[1:5]
```

# Index

- \* **classes**
  - upstreamSeqs-class, 5
- \* **datasets**
  - harbChIP, 4
- \* **models**
  - allhex, 2
  - buildUpstreamSeqs2, 2
  - chkMotif4TF, 3
  - sceUpstr, 4
- allhex, 2
- buildUpstreamSeqs2, 2
- chkAllUS (chkMotif4TF), 3
- chkMotif4TF, 3
- countPattern, 3
- fisher.test, 3
- getUpstream (upstreamSeqs-class), 5
- harbChIP, 4
- keys (upstreamSeqs-class), 5
- keys, upstreamSeqs-method
  - (upstreamSeqs-class), 5
- Nmers (upstreamSeqs-class), 5
- Nmers, numeric, character, upstreamSeqs-method
  - (upstreamSeqs-class), 5
- organism (upstreamSeqs-class), 5
- organism, upstreamSeqs-method
  - (upstreamSeqs-class), 5
- sceUpstr, 4
- seqs (upstreamSeqs-class), 5
- seqs, upstreamSeqs-method
  - (upstreamSeqs-class), 5
- show, upstreamSeqs-method
  - (upstreamSeqs-class), 5
- upstreamSeqs-class, 5