

# Package ‘MSstatsPTM’

December 2, 2025

**Type** Package

**Title** Statistical Characterization of Post-translational Modifications

**Version** 2.12.0

**Date** 2024-11-25

**Description** MSstatsPTM provides general statistical methods for quantitative characterization of post-translational modifications (PTMs). Supports DDA, DIA, SRM, and tandem mass tag (TMT) labeling. Typically, the analysis involves the quantification of PTM sites (i.e., modified residues) and their corresponding proteins, as well as the integration of the quantification results. MSstatsPTM provides functions for summarization, estimation of PTM site abundance, and detection of changes in PTMs across experimental conditions.

**License** Artistic-2.0

**Depends** R (>= 4.3)

**Imports** dplyr, gridExtra, stringr, stats, ggplot2, stringi, grDevices, MSstatsTMT, MSstatsConvert, MSstats, data.table, Rcpp, Biostrings, checkmate, ggrepel, plotly, htmltools

**Suggests** knitr, rmarkdown, tinytest, covr, mockery, testthat (>= 3.0.0)

**LazyData** true

**LinkingTo** Rcpp

**VignetteBuilder** knitr

**biocViews** ImmunoOncology, MassSpectrometry, Proteomics, Software, DifferentialExpression, OneChannel, TwoChannel, Normalization, QualityControl

**BugReports** <https://github.com/Vitek-Lab/MSstatsPTM/issues>

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.3

**Config/testthat/edition** 3

**git\_url** <https://git.bioconductor.org/packages/MSstatsPTM>

**git\_branch** RELEASE\_3\_22

**git\_last\_commit** 6245a63

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.22

**Date/Publication** 2025-12-01

**Author** Devon Kohler [aut],  
 Tsung-Heng Tsai [aut],  
 Anthony Wu [aut, cre],  
 Deril Raju [aut],  
 Ting Huang [aut],  
 Mateusz Staniak [aut],  
 Meena Choi [aut],  
 Olga Vitek [aut]

**Maintainer** Anthony Wu <wu.anthon@northeastern.edu>

## Contents

.calculatePowerPTM . . . . .	3
.fixTerminus . . . . .	4
.getNumSamplePTM . . . . .	4
.joinFasta . . . . .	5
.locateSites . . . . .	5
.removeCutoffSites . . . . .	6
annotSite . . . . .	6
dataProcessPlotsPTM . . . . .	7
dataProcessPTM . . . . .	9
dataSummarizationPTM . . . . .	10
dataSummarizationPTM_TMT . . . . .	13
designSampleSizePTM . . . . .	14
DIANNtoMSstatsPTMFormat . . . . .	16
FragPipeToMSstatsPTMFormat . . . . .	18
fragpipe_annotation . . . . .	21
fragpipe_annotation_protein . . . . .	22
fragpipe_input . . . . .	23
fragpipe_input_protein . . . . .	23
groupComparisonPlotsPTM . . . . .	24
groupComparisonPTM . . . . .	26
locateMod . . . . .	27
locatePTM . . . . .	28
MaxQtoMSstatsPTMFormat . . . . .	29
maxq_lf_annotation . . . . .	32
maxq_lf_evidence . . . . .	32
maxq_tmt_annotation . . . . .	33
maxq_tmt_evidence . . . . .	34
MetamorpheusToMSstatsPTMFormat . . . . .	34
MSstatsPTM . . . . .	36
MSstatsPTMSiteLocator . . . . .	38
PDtoMSstatsPTMFormat . . . . .	39
pd_annotation . . . . .	42
pd_psm_input . . . . .	43
pd_testing_output . . . . .	44
ProgenesisToMSstatsPTMFormat . . . . .	44

<i>.calculatePowerPTM</i>	3
ProteinProspectortoMSstatsPTMFormat . . . . .	46
PStoMSstatsPTMFormat . . . . .	48
raw.input . . . . .	49
raw.input.tmt . . . . .	50
SkylinetoMSstatsPTMFormat . . . . .	51
SpectronauttoMSstatsPTMFormat . . . . .	52
spectronaut_annotation . . . . .	55
spectronaut_input . . . . .	55
summary.data . . . . .	56
summary.data.tmt . . . . .	57
tidyFasta . . . . .	58
<b>Index</b>	<b>59</b>

---

<i>.calculatePowerPTM</i>	<i>Power calculation for PTM experiment</i>
---------------------------	---

---

## Description

Power calculation for PTM experiment

## Usage

```
.calculatePowerPTM(
  desiredFC,
  FDR,
  delta,
  ptm_median_sigma_error,
  protein_median_sigma_error,
  ptm_median_sigma_subject,
  protein_median_sigma_subject,
  numSample
)
```

## Arguments

desiredFC	the range of a desired fold change which includes the lower and upper values of the desired fold change.
FDR	a pre-specified false discovery ratio (FDR) to control the overall false positive rate. Default is 0.05
numSample	minimal number of biological replicates per condition. TRUE represents you require to calculate the sample size for this category, else you should input the exact number of biological replicates.

## Value

float of power

---

<code>.fixTerminus</code>	<i>Fix terminus location adjustments</i>
---------------------------	--

---

**Description**

Fix terminus location adjustments

**Usage**

```
.fixTerminus(data, terminus_id, unmod_pep_col)
```

**Arguments**

<code>data</code>	data.table containing peptide data
<code>terminus_id</code>	character string identifying the terminus (e.g. N-terminus)
<code>unmod_pep_col</code>	character string specifying the column name containing unmodified peptide sequences

**Value**

data.table with corrected Start positions

---

<code>.getNumSamplePTM</code>	<i>Get sample size for PTM experiment</i>
-------------------------------	---

---

**Description**

Get sample size for PTM experiment

**Usage**

```
.getNumSamplePTM(
  desiredFC,
  power,
  alpha,
  delta,
  ptm_median_sigma_error,
  protein_median_sigma_error,
  ptm_median_sigma_subject,
  protein_median_sigma_subject
)
```

**Arguments**

<code>desiredFC</code>	the range of a desired fold change which includes the lower and upper values of the desired fold change.
<code>power</code>	a pre-specified statistical power which defined as the probability of detecting a true fold change. TRUE represent you require to calculate the power for this category, else you should input the average of power you expect. Default is 0.9

### Value

int of samples

---

.joinFasta	Add FASTA data into dataframe
------------	-------------------------------

---

### Description

Add FASTA data into dataframe

### Usage

```
.joinFasta(  
  data,  
  fasta_file,  
  fasta_protein_name,  
  protein_name_col,  
  unmod_pep_col,  
  mod_pep_col  
)
```

### Arguments

data	data.table
fasta_file	string or data.table

### Value

data.table

---

.locateSites	Add site location and aa
--------------	--------------------------

---

### Description

Add site location and aa

### Usage

```
.locateSites(  
  data,  
  mod_id,  
  protein_name_col,  
  unmod_pep_col,  
  mod_pep_col,  
  mod_id_is_numeric,  
  replace_text = FALSE  
)
```

**Arguments**

data	data.table
mod_id	string

**Value**

data.table

---

.removeCutoffSites	<i>Remove sites below cutoff probability</i>
--------------------	--

---

**Description**

Remove sites below cutoff probability

**Usage**

```
.removeCutoffSites(data, mod_pep_col, cutoff, remove_unlocalized_peptides)
```

**Arguments**

data	data.table
mod_pep_col	column in data with modified sites
cutoff	numeric cutoff. Default is .75.
remove_unlocalized_peptides	Boolean if to remove peptides that could not be fully localized.

**Value**

data.table with modifications below cutoff removed

---

annotSite	<i>Annotate modification site</i>
-----------	-----------------------------------

---

**Description**

annotSite annotates modified sites as their residues and locations.

**Usage**

```
annotSite(aaIndex, residue, lenIndex = NULL)
```

**Arguments**

aaIndex	An integer vector. Location of the sites.
residue	A string vector. Amino acid residue.
lenIndex	An integer. Default is NULL

**Value**

A string.

**Examples**

```
annotSite(10, "K")
annotSite(10, "K", 3L)
```

---

dataProcessPlotsPTM	<i>Visualization for explanatory data analysis</i>
---------------------	--

---

**Description**

To illustrate the quantitative data and quality control of MS runs, `dataProcessPlotsPTM` takes the quantitative data from `dataSummarizationPTM` or `dataSummarizationPTM_TMT` to plot the following : (1) profile plot (specify "ProfilePlot" in option type), to identify the potential sources of variation for each protein; (2) quality control plot (specify "QCPlot" in option type), to evaluate the systematic bias between MS runs.

**Usage**

```
dataProcessPlotsPTM(  
  data,  
  type = "PROFILEPLOT",  
  ylimUp = FALSE,  
  ylimDown = FALSE,  
  x.axis.size = 10,  
  y.axis.size = 10,  
  text.size = 4,  
  text.angle = 90,  
  legend.size = 7,  
  dot.size.profile = 2,  
  ncol.guide = 5,  
  width = 10,  
  height = 12,  
  ptm.title = "All PTMs",  
  protein.title = "All Proteins",  
  which.PTM = "all",  
  which.Protein = NULL,  
  originalPlot = TRUE,  
  summaryPlot = TRUE,  
  address = "",  
  isPlotly = FALSE  
)
```

**Arguments**

data	name of the list with PTM and (optionally) Protein data, which can be the output of the <code>MSstatsPTM</code> <a href="#">dataSummarizationPTM</a> or <a href="#">dataSummarizationPTM_TMT</a> functions.
------	---

type	choice of visualization. "ProfilePlot" represents profile plot of log intensities across MS runs. "QCPlot" represents box plots of log intensities across channels and MS runs.
ylimUp	upper limit for y-axis in the log scale. FALSE(Default) for Profile Plot and QC Plot uses the upper limit as rounded off maximum of log2(intensities) after normalization + 3..
ylimDown	lower limit for y-axis in the log scale. FALSE(Default) for Profile Plot and QC Plot uses 0..
x.axis.size	size of x-axis labeling for "Run" and "channel in Profile Plot and QC Plot.
y.axis.size	size of y-axis labels. Default is 10.
text.size	size of labels represented each condition at the top of Profile plot and QC plot. Default is 4.
text.angle	angle of labels represented each condition at the top of Profile plot and QC plot. Default is 0.
legend.size	size of legend above Profile plot. Default is 7.
dot.size.profile	size of dots in Profile plot. Default is 2.
ncol.guide	number of columns for legends at the top of plot. Default is 5.
width	width of the saved pdf file. Default is 10.
height	height of the saved pdf file. Default is 10.
ptm.title	title of overall PTM QC plot
protein.title	title of overall Protein QC plot
which.PTM	PTM list to draw plots. List can be names of PTMs or order numbers of PTMs. Default is "all", which generates all plots for each protein. For QC plot, "allonly" will generate one QC plot with all proteins.
which.Protein	List of proteins to plot. Will plot all PTMs associated with listed Proteins. Default is NULL which will default to which.PTM.
originalPlot	TRUE(default) draws original profile plots, without normalization.
summaryPlot	TRUE(default) draws profile plots with protein summarization for each channel and MS run.
address	the name of folder that will store the results. Default folder is the current working directory.
isPlotly	Parameter to use Plotly or ggplot2. If set to TRUE, MSstats will save Plotly plots as HTML files. If set to FALSE MSstats will save ggplot2 plots as PDF files The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "ProfilePlot.pdf" or "QCplot.pdf". The command address can help to specify where to store the file as well as how to modify the beginning of the file name. If address=FALSE, plot will be not saved as pdf file but showed in window.

**Value**

plot or pdf



## Examples

```
# QCPlot
dataProcessPlotsPTM(summary.data,
                     type = 'QCPlot',
                     which.PTM = "allonly",
                     address = FALSE)

#ProfilePlot
dataProcessPlotsPTM(summary.data,
                     type = 'PROFILEPLOT',
                     which.PTM = "Q9UQ80_K376",
                     address = FALSE)
```

---

dataProcessPTM	<i>Data processing and summarization of peptide-level quantification to PTM and protein level quantification</i>
----------------	--

---

## Description

Function to perform data processing and summarization on an experiment targeting post-translational modifications. Performs normalization, missing value imputation, feature selection, and summarization. Can optionally take an additional global protein quantification experiment for protein-level correction of PTM changes. Can take either label free or tandem mass tag (TMT) labeled data.

## Usage

```
dataProcessPTM(
  data,
  ptm_label_type,
  protein_label_type,
  MBimpute_ptm = FALSE,
  MBimpute_protein = TRUE,
  use_log_file = TRUE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL,
  ...
)
```

## Arguments

data	Name of the output of MSstatsPTM converter function or peptide-level quantified data from other tools. It should be a list containing one or two data tables, named PTM and PROTEIN for modified and unmodified datasets. The list must at least contain the PTM dataset, however the PROTEIN dataset is optional.
ptm_label_type	Indicator of labeling type for PTM dataset. Must be one of LF or TMT
protein_label_type	Indicator of labeling type for PROTEIN dataset. Must be one of LF or TMT
MBimpute_ptm	Missing value imputation on the feature-level for the PTM dataset. TRUE (default) imputes missing values by Accelerated failure model. FALSE uses minimum value to impute the missing value for each peptide precursor ion.

MBimpute\_protein Missing value imputation on the feature-level for the PROTEIN dataset. TRUE (default) imputes missing values by Accelerated failure model. FALSE uses minimum value to impute the missing value for each peptide precursor ion.

... Additional parameters passed to either the [dataProcess](#) function from MSstats or the [proteinSummarization](#) function from MSstatsTMT.

---

dataSummarizationPTM *Data summarization function for label-free MS experiments targeting PTMs.*

---

## Description

Utilizes functionality from MSstats to clean, summarize, and normalize PTM and protein level data. Imputes missing values, performs normalization, and summarizes data. PTM data is summarized up to the modification and protein data is summarized up to the protein level. Takes as input the output of the included converters (see included `raw.input` data object for required input format).

## Usage

```
dataSummarizationPTM(
  data,
  logTrans = 2,
  normalization = "equalizeMedians",
  normalization.PTM = "equalizeMedians",
  nameStandards = NULL,
  nameStandards.PTM = NULL,
  featureSubset = "all",
  featureSubset.PTM = "all",
  remove_uninformative_feature_outlier = FALSE,
  remove_uninformative_feature_outlier.PTM = FALSE,
  min_feature_count = 2,
  min_feature_count.PTM = 1,
  n_top_feature = 3,
  n_top_feature.PTM = 3,
  summaryMethod = "TMP",
  equalFeatureVar = TRUE,
  censoredInt = "NA",
  MBimpute = TRUE,
  MBimpute.PTM = TRUE,
  remove50missing = FALSE,
  fix_missing = NULL,
  maxQuantileforCensored = 0.999,
  use_log_file = TRUE,
  append = TRUE,
  verbose = TRUE,
  log_file_path = NULL,
  base = "MSstatsPTM_log_"
)
```

**Arguments**

<code>data</code>	name of the list with PTM and (optionally) unmodified protein data.tables, which can be the output of the MSstatsPTM converter functions
<code>logTrans</code>	logarithm transformation with base 2(default) or 10
<code>normalization</code>	normalization for the protein level dataset, to remove systematic bias between MS runs. There are three different normalizations supported. 'equalizeMedians'(default) represents constant normalization (equalizing the medians) based on reference signals is performed. 'quantile' represents quantile normalization based on reference signals is performed. 'globalStandards' represents normalization with global standards proteins. FALSE represents no normalization is performed
<code>normalization.PTM</code>	normalization for PTM level dataset. Default is "equalizeMedians" Can be adjusted to any of the options described above.
<code>nameStandards</code>	vector of global standard peptide names for protein dataset. only for normalization with global standard peptides.
<code>nameStandards.PTM</code>	Same as above for PTM dataset.
<code>featureSubset</code>	"all" (default) uses all features that the data set has. "top3" uses top 3 features which have highest average of log-intensity across runs. "topN" uses top N features which has highest average of log-intensity across runs. It needs the input for <code>n_top_feature</code> option. "highQuality" flags uninformative feature and outliers.
<code>featureSubset.PTM</code>	For PTM dataset only. Options same as above.
<code>remove_uninformative_feature_outlier</code>	For protein dataset only. It only works after users used <code>featureSubset="highQuality"</code> in <code>dataProcess</code> . TRUE allows to remove 1) the features are flagged in the column, <code>feature_quality="Uninformative"</code> which are features with bad quality, 2) outliers that are flagged in the column, <code>is_outlier=TRUE</code> , for run-level summarization. FALSE (default) uses all features and intensities for run-level summarization.
<code>remove_uninformative_feature_outlier.PTM</code>	For PTM dataset only. Options same as above.
<code>min_feature_count</code>	optional. Only required if <code>featureSubset = "highQuality"</code> . Defines a minimum number of informative features a protein needs to be considered in the feature selection algorithm.
<code>min_feature_count.PTM</code>	For PTM dataset only. Options the same as above. Default is 1 due to low average feature count for PTMs.
<code>n_top_feature</code>	For protein dataset only. The number of top features for <code>featureSubset='topN'</code> . Default is 3, which means to use top 3 features.
<code>n_top_feature.PTM</code>	For PTM dataset only. Options same as above.
<code>summaryMethod</code>	"TMP"(default) means Tukey's median polish, which is robust estimation method. "linear" uses linear mixed model.

equalFeatureVar	only for summaryMethod="linear". default is TRUE. Logical variable for whether the model should account for heterogeneous variation among intensities from different features. Default is TRUE, which assume equal variance among intensities from features. FALSE means that we cannot assume equal variance among intensities from features, then we will account for heterogeneous variation from different features.
censoredInt	Missing values are censored or at random. 'NA' (default) assumes that all 'NA's in 'Intensity' column are censored. '0' uses zero intensities as censored intensity. In this case, NA intensities are missing at random. The output from Skyline should use '0'. Null assumes that all NA intensities are randomly missing.
MBimpute	For protein dataset only. only for summaryMethod="TMP" and censoredInt='NA' or '0'. TRUE (default) imputes 'NA' or '0' (depending on censoredInt option) by Accelerated failure model. FALSE uses the values assigned by cutoffCensored.
MBimpute.PTM	For PTM dataset only. Options same as above.
remove50missing	only for summaryMethod="TMP". TRUE removes the runs which have more than 50% missing values. FALSE is default.
fix_missing	Default is Null. Optional, same as the 'fix_missing' parameter in MSstatsConvert::MSstatsBalancedDesign function
maxQuantileforCensored	Maximum quantile for deciding censored missing values. default is 0.999
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If append = TRUE, has to be a valid path to a file.
base	start of the file name.

## Value

list of summarized PTM and Protein results. These results contain the reformatted input to the summarization function, as well as run-level summarization results.

## Examples

```
head(raw.input$PTM)
head(raw.input$PROTEIN)

quant.lf.msstatsptm = dataSummarizationPTM(raw.input, verbose = FALSE)
head(quant.lf.msstatsptm$PTM$ProteinLevelData)
```

---

dataSummarizationPTM\_TMT

*Data summarization function for TMT labelled MS experiments targeting PTMs.*

---

## Description

Utilizes functionality from MSstatsTMT to clean, summarize, and normalize PTM and protein level data. Imputes missing values, performs normalization, and summarizes data. PTM data is summarized up to the modification and protein data is summarized up to the protein level. Takes as input the output of the included converters (see included `raw.input.tmt` data object for required input format).

## Usage

```
dataSummarizationPTM_TMT(
  data,
  method = "msstats",
  global_norm = TRUE,
  global_norm.PTM = TRUE,
  reference_norm = TRUE,
  reference_norm.PTM = TRUE,
  remove_norm_channel = TRUE,
  remove_empty_channel = TRUE,
  MBimpute = TRUE,
  MBimpute.PTM = TRUE,
  maxQuantileforCensored = NULL,
  use_log_file = TRUE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL
)
```

## Arguments

data	Name of the output of MSstatsPTM converter function or peptide-level quantified data from other tools. It should be a list containing one or two data tables, named PTM and PROTEIN for modified and unmodified datasets. The list must at least contain the PTM dataset. The data should have columns ProteinName, PeptideSequence, Charge, PSM, Mixture, TechRepMixture, Run, Channel, Condition, BioReplicate, Intensity
method	Four different summarization methods to protein-level can be performed : "msstats"(default), "MedianPolish", "Median", "LogSum".
global_norm	Global median normalization on for unmodified peptide level data (equalizing the medians across all the channels and MS runs). Default is TRUE. It will be performed before protein-level summarization.
global_norm.PTM	Same as above for modified peptide level data. Default is TRUE.

reference_norm	Reference channel based normalization between MS runs on unmodified protein level data. TRUE(default) needs at least one reference channel in each MS run, annotated by 'Norm' in Condition column. It will be performed after protein-level summarization. FALSE will not perform this normalization step. If data only has one run, then reference_norm=FALSE.
reference_norm.PTM	Same as above for modified peptide level data. Default is TRUE.
remove_norm_channel	TRUE(default) removes 'Norm' channels from protein level data.
remove_empty_channel	TRUE(default) removes 'Empty' channels from protein level data.
MBimpute	only for method="msstats". TRUE (default) imputes missing values by Accelerated failure model. FALSE uses minimum value to impute the missing value for each peptide precursor ion.
MBimpute.PTM	Same as above for modified peptide level data. Default is TRUE
maxQuantileforCensored	We assume missing values are censored. maxQuantileforCensored is Maximum quantile for deciding censored missing value, for instance, 0.999. Default is Null.
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If append = TRUE, has to be a valid path to a file.

**Value**

list of two data.tables

**Examples**

```
head(raw.input.tmt$PTM)
head(raw.input.tmt$PROTEIN)

quant.tmt.msstatsptm = dataSummarizationPTM_TMT(raw.input.tmt,
                                                method = "msstats",
                                                verbose = FALSE)

head(quant.tmt.msstatsptm$PTM$ProteinLevelData)
```

---

designSampleSizePTM	<i>Planning future experimental designs of PTM experiments in sample size calculation</i>
---------------------	---

---

**Description**

Calculate sample size for future experiments of a PTM experiment based on intensity-based linear model. Calculation is only available for group comparison experimental designs (not including time series). Two options of the calculation: (1) number of biological replicates per condition, (2) power.

**Usage**

```
designSampleSizePTM(
  data,
  desiredFC,
  FDR = 0.05,
  numSample = TRUE,
  power = 0.8,
  use_log_file = TRUE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL,
  base = "MSstatsPTM_log_"
)
```

**Arguments**

data	output of the groupComparisonPTM function.
desiredFC	the range of a desired fold change which includes the lower and upper values of the desired fold change.
FDR	a pre-specified false discovery ratio (FDR) to control the overall false positive rate. Default is 0.05
numSample	minimal number of biological replicates per condition. TRUE represents you require to calculate the sample size for this category, else you should input the exact number of biological replicates.
power	a pre-specified statistical power which defined as the probability of detecting a true fold change. TRUE represent you require to calculate the power for this category, else you should input the average of power you expect. Default is 0.9
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If append = TRUE, has to be a valid path to a file.
base	start of the file name.

**Details**

The function fits the model and uses variance components to calculate sample size. The underlying model fitting with intensity-based linear model with technical MS run replication. Estimated sample size is rounded to 0 decimal. The function can only obtain either one of the categories of the sample size calculation (numSample, numPep, numTran, power) at the same time.

**Value**

data.frame - sample size calculation results including variables: desiredFC, numSample, FDR, and power.

## Examples

```
model.lf.msstatsptm = groupComparisonPTM(summary.data,
                                         ptm_label_type="LF",
                                         protein_label_type="LF",
                                         verbose = FALSE)

#(1) Minimal number of biological replicates per condition
designSampleSizePTM(data=model.lf.msstatsptm, numSample=TRUE,
                   desiredFC=c(2.0,2.75), FDR=0.05, power=0.8)
#(2) Power calculation
designSampleSizePTM(data=model.lf.msstatsptm, numSample=5,
                   desiredFC=c(2.0,2.75), FDR=0.05, power=TRUE)
```

---

DIANNtoMSstatsPTMFormat

*Convert the output of DIA-NN PSM file into MSstatsPTM format*

---

## Description

Takes as input the `report.tsv` file from DIA-NN and converts it into MSstatsPTM format. Requires PSM and an annotation file. Optionally an additional `report.tsv` file for a corresponding global profiling run can be included.

## Usage

```
DIANNtoMSstatsPTMFormat(
  input,
  annotation,
  input_protein = NULL,
  annotation_protein = NULL,
  fasta_path = NULL,
  use_unmod_peptides = FALSE,
  protein_id_col = "Protein.Group",
  fasta_protein_name = "uniprot_ac",
  global_qvalue_cutoff = 0.01,
  qvalue_cutoff = 0.01,
  pg_qvalue_cutoff = 0.01,
  useUniquePeptide = TRUE,
  removeFewMeasurements = TRUE,
  removeOxidationMpeptides = TRUE,
  removeProtein_with1Feature = FALSE,
  MBR = TRUE,
  use_log_file = TRUE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL
)
```



**Arguments**

<code>input</code>	data.frame of <code>report.tsv</code> file produced by Philosopher
<code>annotation</code>	annotation with Run, Fraction, TechRepMixture, Mixture, Channel, BioReplicate, Condition columns or a path to file. Refer to the example 'annotation' for the meaning of each column.
<code>input_protein</code>	same as <code>input</code> for global profiling run. Default is NULL.
<code>annotation_protein</code>	same as <code>annotation</code> for global profiling run. Default is NULL.
<code>fasta_path</code>	A string of path to a FASTA file, used to match PTM peptides.
<code>use_unmod_peptides</code>	Boolean if the unmodified peptides in the input file should be used to construct the unmodified protein output. Only used if <code>input_protein</code> is not provided. Default is FALSE.
<code>protein_id_col</code>	Use 'Protein.Groups'(default) column for protein name.
<code>fasta_protein_name</code>	Name of column that matches with the protein names in <code>protein_id_col</code> . The protein names in these two columns must match in order to join the FASTA file with the DIA-NN output. Default is "uniprot_ac" for uniprot ID. For uniprot mnemonic ID, use "entry_name"
<code>global_qvalue_cutoff</code>	The global qvalue cutoff. Default is 0.01.
<code>qvalue_cutoff</code>	local qvalue cutoff for library. Default is 0.01.
<code>pg_qvalue_cutoff</code>	local qvalue cutoff for protein groups Run should be the same as filename. Default is 0.01.
<code>useUniquePeptide</code>	logical, if TRUE (default) removes peptides that are assigned for more than one proteins. We assume to use unique peptide for each protein.
<code>removeFewMeasurements</code>	TRUE (default) will remove the features that have 1 or 2 measurements within each Run.
<code>removeOxidationMpeptides</code>	TRUE (default) will remove the peptides including oxidation (M) sequence.
<code>removeProtein_with1Feature</code>	TRUE will remove the proteins which have only 1 peptide and charge. Default is FALSE.
<code>MBR</code>	If analysis was done with match between runs or not. Default is TRUE.
<code>use_log_file</code>	logical. If TRUE, information about data processing will be saved to a file.
<code>append</code>	logical. If TRUE, information about data processing will be added to an existing log file.
<code>verbose</code>	logical. If TRUE, information about data processing will be printed to the console.
<code>log_file_path</code>	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.

**Value**

list of one or two data.frame of class MSstatsTMT, named PTM and PROTEIN

**Examples**

```
# Example from PRIDE ID PXD053502
input = system.file("tinytest/raw_data/DIANN/report.tsv",
                    package = "MSstatsPTM")

input = data.table::fread(input)
annot = system.file("tinytest/raw_data/DIANN/annot.csv",
                    package = "MSstatsPTM")

annot = data.table::fread(annot)
fasta_path = system.file("extdata", "diann.fasta",
                          package="MSstatsPTM")

msstatsptm_format = DIANNtoMSstatsPTMFormat(
  input,
  annot,
  protein_id_col = "Protein.Names",
  fasta_path = fasta_path,
  fasta_protein_name = "entry_name",
  use_log_file = FALSE
)

head(msstatsptm_format$PTM)
```

---

FragPipetoMSstatsPTMFormat

*Convert output of TMT labeled Fragpipe data into MSstatsPTM format.*

---

**Description**

Takes as input TMT experiments which are the output of Fragpipe and converts into MSstatsPTM format. Requires msstats.csv file and an annotation file. Optionally an additional msstats.csv file can be uploaded if a corresponding global profiling run was performed. Site localization is performed and only high probability localizations are kept.

**Usage**

```
FragPipetoMSstatsPTMFormat(
  input,
  annotation = NULL,
  input_protein = NULL,
  annotation_protein = NULL,
  use_unmod_peptides = FALSE,
  label_type = "TMT",
  protein_id_col = "Protein",
  peptide_id_col = "Peptide.Sequence",
  mod_id_col = "STY",
  localization_cutoff = 0.75,
  remove_unlocalized_peptides = TRUE,
  Purity_cutoff = 0.6,
  PeptideProphet_prob_cutoff = 0.7,
  useUniquePeptide = TRUE,
```

```

rmPSM_withfewMea_withinRun = FALSE,
rmPeptide_OxidationM = TRUE,
rmProtein_with1Feature = FALSE,
summaryforMultipleRows = sum,
use_log_file = TRUE,
append = FALSE,
verbose = TRUE,
log_file_path = NULL
)

```

## Arguments

input	data.frame of msstats.csv file produced by Philosopher
annotation	annotation with Run, Fraction, TechRepMixture, Mixture, Channel, BioReplicate, Condition columns or a path to file. Refer to the example 'annotation' for the meaning of each column. Channel column should be consistent with the channel columns (Ignore the prefix "Channel ") in msstats.csv file. Run column should be consistent with the Spectrum.File columns in msstats.csv file.
input_protein	same as input for global profiling run. Default is NULL.
annotation_protein	same as annotation for global profiling run. Default is NULL.
use_unmod_peptides	Boolean if the unmodified peptides in the input file should be used to construct the unmodified protein output. Only used if input_protein is not provided. Default is FALSE.
label_type	Type of labeling used for experiment. Must be one of "LF" or "TMT". Default is "TMT".
protein_id_col	Use 'Protein'(default) column for TMT. This needs to be changed to "Protein-Name" for label free. For TMT, 'Master.Protein.Accessions' can be used instead to get the protein ID with single protein.
peptide_id_col	Use 'Peptide.Sequence'(default) column for TMT. Must be changed to "PeptideSequence" for label free. "Modified.Peptide.Sequence" can be used instead to get the modified peptide sequence.
mod_id_col	Column containing the modified Amino Acids. For example, a Phosphorylation experiment may pass STY. The corresponding column with STY combined with the mass (e.x. STY.79.9663) will be selected. Default is STY.
localization_cutoff	Minimum localization score required to keep modification. Default is .75.
remove_unlocalized_peptides	Boolean indicating if peptides without all sites localized should be kept. Default is TRUE (non-localized sites will be removed).
Purity_cutoff	Cutoff for purity. Default is 0.6. Purity refers to how much of the detected ion signal within a specific inclusion window belongs to the target molecule or its closely related forms, compared to any other unwanted signals or noise. Higher values indicate greater purity.
PeptideProphet_prob_cutoff	Cutoff for the peptide identification probability. Default is 0.7. The probability is confidence score determined by PeptideProphet and higher values indicate greater confidence.

<code>useUniquePeptide</code>	logical, if TRUE (default) removes peptides that are assigned for more than one proteins. We assume to use unique peptide for each protein.
<code>rmPSM_withfewMea_withinRun</code>	TRUE will remove the features that have 1 or 2 measurements within each Run. Default is FALSE.
<code>rmPeptide_OxidationM</code>	TRUE (default) will remove the peptides including oxidation (M) sequence.
<code>rmProtein_with1Feature</code>	TRUE will remove the proteins which have only 1 peptide and charge. Default is FALSE.
<code>summaryforMultipleRows</code>	sum (default) or max - when there are multiple measurements for certain feature in certain run, select the feature with the largest summation or maximal value.
<code>use_log_file</code>	logical. If TRUE, information about data processing will be saved to a file.
<code>append</code>	logical. If TRUE, information about data processing will be added to an existing log file.
<code>verbose</code>	logical. If TRUE, information about data processing will be printed to the console.
<code>log_file_path</code>	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.

## Value

list of one or two data.frame of class MSstatsTMT, named PTM and PROTEIN

## Examples

```
# TMT Example (with global profiling run)
head(fragpipe_input)
head(fragpipe_annotation)
head(fragpipe_input_protein)
head(fragpipe_annotation_protein)

msstats_data = FragPipeToMSstatsPTMFormat(fragpipe_input,
                                           fragpipe_annotation,
                                           fragpipe_input_protein,
                                           fragpipe_annotation_protein,
                                           label_type="TMT",
                                           mod_id_col = "STY",
                                           localization_cutoff=.75,
                                           remove_unlocalized_peptides=TRUE)

head(msstats_data$PTM)
head(msstats_data$PROTEIN)

# LFQ Example
input = system.file("tinytest/raw_data/Fragpipe/MSstats.csv",
                    package = "MSstatsPTM")

input = data.table::fread(input)
annot = system.file("tinytest/raw_data/Fragpipe/experiment_annotation.tsv",
                    package = "MSstatsPTM")

annot = data.table::fread(annot)
```

```

input_protein = system.file("tinytest/raw_data/Fragpipe/msstats_proteome_1f.csv",
                             package = "MSstatsPTM")
input_protein = data.table::fread(input_protein)

msstats_data = FragPipeToMSstatsPTMFormat(input,
                                           annot,
                                           input_protein = input_protein,
                                           label_type="LF",
                                           mod_id_col = "STY",
                                           localization_cutoff=.75,
                                           protein_id_col = "ProteinName",
                                           peptide_id_col = "PeptideSequence")

# If no global profiling run is available, omit input_protein and set:
# msstats_data = FragPipeToMSstatsPTMFormat(input, annot,
#   label_type = "LF", mod_id_col = "STY",
#   localization_cutoff = .75, protein_id_col = "ProteinName",
#   peptide_id_col = "PeptideSequence", use_unmod_peptides = FALSE)

head(msstats_data$PTM)
head(msstats_data$PROTEIN)

```

---

fragpipe\_annotation      *Example annotation file for a TMT FragPipe experiment.*

---

## Description

Automatically created by FragPipe, manually checked by the user and input into the FragPipeToMSstatsPTMFormat converter. Requires the correct columns and maps the experimental design into the MSstats format. Specify unique bioreplicates for group comparison designs, and the same bioreplicate for repeated measure designs. The columns and descriptions are below.

## Usage

```
fragpipe_annotation
```

## Format

A data.table with 7 columns.

## Details

- Run : Run name that matches exactly with FragPipe run. Used to join evidence and metadata in annotation file.
- Fraction : If multiple fractions were used (i.e. the same mixture split into multiple fractions) enter that here. TechRepMixture : Multiple runs using the same bioreplicate
- Channel : Mixture channel used
- Condition : Name of condition that was used for each run.
- Mixture : The unique mixture (plex) name
- BioReplicate : Name of biological replicate. Repeating the same name here will tell MSstatsPTM that the experiment is a repeated measure design.

**Examples**

```
head(fragpipe_annotation)
```

---

```
fragpipe_annotation_protein
```

*Example annotation file for a global profiling run TMT FragPipe experiment.*

---

**Description**

Automatically created by FragPipe, manually checked by the user and input into the FragPipe to MSstatsPTMFormat converter. Requires the correct columns and maps the experimental design into the MSstats format. Specify unique bioreplicates for group comparison designs, and the same bioreplicate for repeated measure designs. The columns and descriptions are below.

**Usage**

```
fragpipe_annotation_protein
```

**Format**

A data.table with 7 columns.

**Details**

- Run : Run name that matches exactly with FragPipe run. Used to join evidence and metadata in annotation file.
- Fraction : If multiple fractions were used (i.e. the same mixture split into multiple fractions) enter that here. TechRepMixture : Multiple runs using the same bioreplicate
- Channel : Mixture channel used
- Condition : Name of condition that was used for each run.
- Mixture : The unique mixture (plex) name
- BioReplicate : Name of biological replicate. Repeating the same name here will tell MSstatsPTM that the experiment is a repeated measure design.

**Examples**

```
head(fragpipe_annotation_protein)
```

---

`fragpipe_input`*Output of FragPipe TMT PTM experiment*

---

**Description**

This dataset was provided by the FragPipe team at the Nesvilab. It was processed using Philosopher and targeted Phosphorylation.

**Usage**`fragpipe_input`**Format**

A data.table with 29 columns and 246 rows.

**Examples**`head(fragpipe_input)`

---

`fragpipe_input_protein`*Output of FragPipe TMT global profiling experiment*

---

**Description**

This dataset was provided by the FragPipe team at the Nesvilab. It was processed using Philosopher and targeted Phosphorylation.

**Usage**`fragpipe_input_protein`**Format**

A data.table with 27 columns and 47 rows.

**Examples**`head(fragpipe_input_protein)`

---

groupComparisonPlotsPTM

*Visualization for model-based analysis and summarization*


---

## Description

To analyze the results of modeling changes in abundance of modified peptides and overall protein, groupComparisonPlotsPTM takes as input the results of the groupComparisonPTM function. It assesses the results of three models: unadjusted PTM, adjusted PTM, and overall protein. To assess the results of the model, the following visualizations can be created: (1) VolcanoPlot (specify "VolcanoPlot" in option type), to plot peptides or proteins and their significance for each model. (2) Heatmap (specify "Heatmap" in option type), to evaluate the fold change between conditions and peptides/proteins

## Usage

```
groupComparisonPlotsPTM(
  data = data,
  type,
  sig = 0.05,
  FCcutoff = FALSE,
  logBase.pvalue = 10,
  ylimUp = FALSE,
  ylimDown = FALSE,
  xlimUp = FALSE,
  x.axis.size = 10,
  y.axis.size = 10,
  dot.size = 3,
  text.size = 4,
  text.angle = 0,
  legend.size = 13,
  ProteinName = TRUE,
  colorkey = TRUE,
  numProtein = NULL,
  width = 10,
  height = 10,
  which.Comparison = "all",
  which.PTM = "all",
  address = "",
  isPlotly = FALSE
)
```

## Arguments

data	name of the list with models, which can be the output of the MSstatsPTM <a href="#">groupComparisonPTM</a> function
type	choice of visualization, one of VolcanoPlot or Heatmap
sig	FDR cutoff for the adjusted p-values in heatmap and volcano plot. level of significance for comparison plot. 100(1-sig)% confidence interval will be drawn. sig=0.05 is default.



FCcutoff	For volcano plot or heatmap, whether involve fold change cutoff or not. FALSE (default) means no fold change cutoff is applied for significance analysis. FC-cutoff = specific value means specific fold change cutoff is applied.
logBase.pvalue	for volcano plot or heatmap, (-) logarithm transformation of adjusted p-value with base 2 or 10(default).
ylimUp	for all three plots, upper limit for y-axis. FALSE (default) for volcano plot/heatmap use maximum of -log2 (adjusted p-value) or -log10 (adjusted p-value). FALSE (default) for comparison plot uses maximum of log-fold change + CI.
ylimDown	for all three plots, lower limit for y-axis. FALSE (default) for volcano plot/heatmap use minimum of -log2 (adjusted p-value) or -log10 (adjusted p-value). FALSE (default) for comparison plot uses minimum of log-fold change - CI.
xlimUp	for Volcano plot, the limit for x-axis. FALSE (default) for use maximum for absolute value of log-fold change or 3 as default if maximum for absolute value of log-fold change is less than 3.
x.axis.size	size of axes labels, e.g. name of the comparisons in heatmap, and in comparison plot. Default is 10.
y.axis.size	size of axes labels, e.g. name of targeted proteins in heatmap. Default is 10.
dot.size	size of dots in volcano plot and comparison plot. Default is 3.
text.size	size of ProteinName label in the graph for Volcano Plot. Default is 4.
text.angle	angle of x-axis labels represented each comparison at the bottom of graph in comparison plot. Default is 0.
legend.size	size of legend for color at the bottom of volcano plot. Default is 7.
ProteinName	for volcano plot only, whether display protein names or not. TRUE (default) means protein names, which are significant, are displayed next to the points. FALSE means no protein names are displayed.
colorkey	TRUE(default) shows colorkey.
numProtein	The number of proteins which will be presented in each heatmap. Default is 50.
width	width of the saved file. Default is 10.
height	height of the saved file. Default is 10.
which.Comparison	list of comparisons to draw plots. List can be labels of comparisons or order numbers of comparisons from levels(data\$Label) , such as levels(testResultMultiComparisons\$Comparison). Default is "all", which generates all plots for each protein.
which.PTM	Protein list to draw comparison plots. List can be names of Proteins or order numbers of Proteins from levels(testResultMultiComparisons\$ComparisonResult\$Protein). Default is "all", which generates all comparison plots for each protein.
address	the name of folder that will store the results. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "VolcanoPlot.pdf" or "Heatmap.pdf". The command address can help to specify where to store the file as well as how to modify the beginning of the file name. If address=FALSE, plot will be not saved as pdf file but showed in window
isPlotly	Parameter to use Plotly or ggplot2. If set to TRUE, MSstats will save Plotly plots as HTML files. If set to FALSE MSstats will save ggplot2 plots as PDF files

**Value**

plot or pdf

**Examples**

```
model.lf.msstatsptm = groupComparisonPTM(summary.data,
                                         ptm_label_type="LF",
                                         protein_label_type="LF")
groupComparisonPlotsPTM(data = model.lf.msstatsptm,
                        type = "VolcanoPlot",
                        FCcutoff= 2,
                        logBase.pvalue = 2,
                        address=FALSE)
```

---

groupComparisonPTM	<i>Perform differential analysis on MS-based proteomics experiments targeting PTMs</i>
--------------------	--

---

**Description**

Takes summarized PTM and protein data from `dataSummarizationPTM` or `dataSummarizationPTM_TMT` functions and performs differential analysis. Leverages unmodified protein data to perform adjustment and deconvolute the effect of the PTM and unmodified protein. If protein data is unavailable, PTM data can still be passed into the function, however adjustment can not be performed. All model results are returned for completeness.

**Usage**

```
groupComparisonPTM(
  data,
  data.type = NULL,
  contrast.matrix = "pairwise",
  moderated = FALSE,
  adj.method = "BH",
  log_base = 2,
  save_fitted_models = TRUE,
  use_log_file = TRUE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL,
  base = "MSstatsPTM_log_",
  ptm_label_type = "LF",
  protein_label_type = "LF"
)
```

**Arguments**

<code>data</code>	list of summarized datasets. Output of <code>MSstatsPTM</code> summarization function <code>dataSummarizationPTM</code> or <code>dataSummarizationPTM_TMT</code> depending on acquisition type.
<code>data.type</code>	Type of data. Must be one of LF or TMT. Will be deprecated in favor of <code>ptm_label_type</code> and <code>protein_label_type</code> .

contrast.matrix	comparison between conditions of interests. Default models full pairwise comparison between all conditions
moderated	For TMT experiments only. TRUE will moderate t statistic; FALSE (default) uses ordinary t statistic. Default is FALSE.
adj.method	For TMT experiments only. Adjusted method for multiple comparison. "BH" is default. "BH" is used for all other experiment types
log_base	For non-TMT experiments only. The base of the logarithm used in summarization.
save_fitted_models	logical, if TRUE, fitted models will be added to the output.
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If append = TRUE, has to be a valid path to a file.
base	start of the file name.
ptm_label_type	Indicator of labeling type for PTM dataset. Must be one of LF or TMT
protein_label_type	Indicator of labeling type for PROTEIN dataset. Must be one of LF or TMT

### Value

list of modeling results. Includes PTM, PROTEIN, and ADJUSTED data.tables with their corresponding model results.

### Examples

```
model.lf.msstatsptm = groupComparisonPTM(summary.data,
                                           ptm_label_type="LF",
                                           protein_label_type="LF",
                                           verbose = FALSE)
```

---

locateMod

*Locate modified sites with a peptide*

---

### Description

locateMod locates modified sites with a peptide.

### Usage

```
locateMod(peptide, aaStart, residueSymbol)
```

**Arguments**

peptide	A string. Peptide sequence.
aaStart	An integer. Starting index of the peptide.
residueSymbol	A string. Modification residue and denoted symbol.

**Value**

A string.

**Examples**

```
locateMod("P*EP*TIDE", 3, "\\*")
```

---

locatePTM

*Annotate modified sites with associated peptides*

---

**Description**

PTMlocate annotates modified sites with associated peptides.

**Usage**

```
locatePTM(peptide, uniprot, fasta, modResidue, modSymbol, rmConfound = FALSE)
```

**Arguments**

peptide	A string vector of peptide sequences. The peptide sequence does not include its preceding and following AAs.
uniprot	A string vector of Uniprot identifiers of the peptides' originating proteins. UniProtKB entry isoform sequence is used.
fasta	A data.table with FASTA information. Output of tidyFasta.
modResidue	A string. Modifiable amino acid residues.
modSymbol	A string. Symbol of a modified site.
rmConfound	A logical. TRUE removes confounded unmodified sites, FALSE otherwise. Default is FALSE.

**Value**

A data frame with three columns: uniprot\_iso, peptide, site.

**Examples**

```
fasta = tidyFasta(system.file("extdata", "013297.fasta", package="MSstatsPTM"))
locatePTM("DRVSYIHNDSC*TR", "013297", fasta, "C", "\\*")
```

---

MaxQtoMSstatsPTMFormat

*Convert output of label-free or TMT MaxQuant experiments into MSstatsPTM format*

---

## Description

Takes as input LF/TMT experiments from MaxQ and converts the data into the format needed for MSstatsPTM. Requires modified evidence.txt file from MaxQ and an annotation file for PTM data. To adjust modified peptides for changes in global protein level, unmodified TMT experimental data must also be returned. Optionally can use Phospho(STY)Sites.txt (or other PTM specific files) from MaxQuant, but this is not recommended. If PTM specific file provided, the raw intensities must be provided, not a ratio.

## Usage

```
MaxQtoMSstatsPTMFormat(
  evidence = NULL,
  annotation = NULL,
  fasta_path,
  fasta_protein_name = "uniprot_ac",
  mod_id = "\\(Phospho \\(STY\\)\\)",
  sites_data = NULL,
  evidence_prot = NULL,
  proteinGroups = NULL,
  annotation_protein = NULL,
  use_unmod_peptides = FALSE,
  labeling_type = "LF",
  mod_num = "Single",
  TMT_keyword = "TMT",
  ptm_keyword = "phos",
  which_proteinid_ptm = "Proteins",
  which_proteinid_protein = "Proteins",
  remove_other_mods = TRUE,
  removeMpeptides = FALSE,
  removeOxidationMpeptides = FALSE,
  removeProtein_with1Peptide = FALSE,
  use_log_file = TRUE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL
)
```

## Arguments

evidence	name of 'evidence.txt' data, which includes feature-level data for enriched (PTM) data.
annotation	data frame annotation file for the ptm level data. Contains column Run, Fraction, TechRepMixture, Mixture, Channel, BioReplicate, Condition.
fasta_path	A string of path to a FASTA file, used to match PTM peptides.

fasta_protein_name	Name of fasta column that matches with protein name in evidence file. Default is uniprot_ac.
mod_id	Character that indicates the modification of interest. Default is \\(Phospho\\). Note \\ must be included before special characters.
sites_data	(Not recommended. Only used if evidence file not provided. Only works for TMT labeled data) Modified peptide output from MaxQuant. For example, a phosphorylation experiment would require the Phospho(STY)Sites.txt file
evidence_prot	name of 'evidence.txt' data, which includes feature-level data for global profiling (unmodified) data.
proteinGroups	name of 'proteinGroups.txt' data. It needs to matching protein group ID in evidence_prot.
annotation_protein	data frame annotation file for the protein level data. Contains column Run, Fraction, TechRepMixture, Mixture, Channel, BioReplicate, Condition.
use_unmod_peptides	Boolean if the unmodified peptides in the input file should be used to construct the unmodified protein output. Only used if input_protein is not provided. Default is FALSE.
labeling_type	Either TMT or LF (Label-Free) depending on experimental design. Default is LF.
mod_num	(Only if sites_data is used) For modified peptide dataset. The number modifications per peptide to be used. If "Single", only peptides with one modification will be used. Otherwise "Total" can be selected which does not cap the number of modifications per peptide. "Single" is the default. Selecting "Total" may confound the effect of different modifications.
TMT_keyword	(Only if sites_data is used) the sub-name of columns in sites.data file. Default is TMT. This corresponds to the columns in the format Reporter.intensity.corrected.1.TMT1phos. Specifically, this parameter indicates the first section of the string TMT1phos (Before the mixture number). If TMT is present in the string, set this value to TMT. Else if TMT is not there (ie string is in the format 1phos) leave this parameter as an empty string ("").
ptm_keyword	(Only if sites_data is used) the sub-name of columns in the sites.data file. Default is phos. This corresponds to the columns in the format Reporter.intensity.corrected.1.TMT1phos. Specifically, this parameter indicates the second section of the string TMT1phos (After the mixture number). If the string is present, set this parameter. Else if this part of the string is empty (ie string is in the format TMT1) leave this parameter as an empty string ("").
which_proteinid_ptm	For PTM dataset, which column to use for protein name. Use 'Proteins' (default) column for protein name. 'Leading.proteins' or 'Leading.razor.protein' or 'Gene.names' can be used instead to get the protein ID with single protein. However, those can potentially have the shared peptides.
which_proteinid_protein	For Protein dataset, which column to use for protein name. Same options as above.
remove_other_mods	Remove peptides which include modifications other than the one listed in mod_id. Default is TRUE. For example, in an experiment targeting Phosphorylation, setting this parameter to TRUE would remove peptides like (Acetyl (Protein N-term))AAAAPDSRVS(Phospho (STY))EEENLK. Set this parameter to FALSE to keep peptides with extraneous modifications.

removeMpeptides	If Oxidation (M) modifications should be removed. Default is TRUE.
removeOxidationMpeptides	TRUE will remove the peptides including 'oxidation (M)' in modification. FALSE is default.
removeProtein_with1Peptide	TRUE will remove the proteins which have only 1 peptide and charge. FALSE is default.
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.

### Value

a list of two data.tables named 'PTM' and 'PROTEIN' in the format required by MSstatsPTM.

### Examples

```
# TMT experiment
head(maxq_tmt_evidence)
head(maxq_tmt_annotation)

msstats_format_tmt = MaxQtoMSstatsPTMFormat(evidence=maxq_tmt_evidence,
      annotation=maxq_tmt_annotation,
      fasta=system.file("extdata", "maxq_tmt_fasta.fasta", package="MSstatsPTM"),
      fasta_protein_name="uniprot_ac",
      mod_id="\\(Phospho \\(STY\\)\\)",
      use_unmod_peptides=TRUE,
      labeling_type = "TMT",
      which_proteinid_ptm = "Proteins")

head(msstats_format_tmt$PTM)
head(msstats_format_tmt$PROTEIN)

# LF experiment
head(maxq_lf_evidence)
head(maxq_lf_annotation)

msstats_format_lf = MaxQtoMSstatsPTMFormat(evidence=maxq_lf_evidence,
      annotation=maxq_lf_annotation,
      fasta=system.file("extdata", "maxq_lf_fasta.fasta", package="MSstatsPTM"),
      fasta_protein_name="uniprot_ac",
      mod_id="\\(Phospho \\(STY\\)\\)",
      use_unmod_peptides=TRUE,
      labeling_type = "LF",
      which_proteinid_ptm = "Proteins")

head(msstats_format_lf$PTM)
head(msstats_format_lf$PROTEIN)
```

---

maxq_lf_annotation	<i>Example annotation file for a label-free MaxQuant experiment.</i>
--------------------	--

---

### Description

Must be manually created by the user and input into the MaxQtoMSstatsPTMFormat converter. Requires the correct columns and maps the experimental design into the MSstats format. Specify unique bioreplicates for group comparison designs, and the same bioreplicate for repeated measure designs. The columns and descriptions are below.

### Usage

```
maxq_lf_annotation
```

### Format

A data.table with 5 columns.

### Details

- Run : Run name that matches exactly with MaxQuant run. Used to join evidence and metadata in annotation file.
- Condition : Name of condition that was used for each run.
- BioReplicate : Name of biological replicate. Repeating the same name here will tell MSstatsPTM that the experiment is a repeated measure design.
- Raw.file : Run name that matches exactly with MaxQuant run. Used to join evidence and metadata in annotation file.
- IsotopeLabelType: Name of isotope label. May be all L or unique depending on experimental design.

### Examples

```
head(maxq_lf_annotation)
```

---

maxq_lf_evidence	<i>Example MaxQuant evidence file from the output of a label free experiment</i>
------------------	--

---

### Description

Experiment was performed by the Olsen lab and published on Nat. Commun. (citation below).

### Usage

```
maxq_lf_evidence
```

### Format

a data.table with 63 columns and 511 rows, the output of MaxQuant



## Details

Bekker-Jensen, D.B., Bernhardt, O.M., Hogrebe, A. et al. Rapid and site-specific deep phospho-proteome profiling by data-independent acquisition without the need for spectral libraries. Nat Commun 11, 787 (2020). <https://doi.org/10.1038/s41467-020-14609-1>

The experiment was processed using MaxQuant by the computational proteomics team at Pfizer (Liang Xue and Pierre Jean).

The experiment did not contain a global profiling run, but we show an example of extracting the unmodified peptides and using them in place of the profiling run.

## Examples

```
head(maxq_1f_evidence)
```

---

maxq_tmt_annotation	<i>Example annotation file for a TMT MaxQuant experiment.</i>
---------------------	---

---

## Description

Must be manually created by the user and input into the MaxQtoMSstatsPTMFormat converter. Requires the correct columns and maps the experimental design into the MSstats format. Specify unique bioreplicates for group comparison designs, and the same bioreplicate for repeated measure designs. The columns and descriptions are below.

## Usage

```
maxq_tmt_annotation
```

## Format

A data.table with 7 columns.

## Details

- Run : Run name that matches exactly with MaxQuant run. Used to join evidence and metadata in annotation file.
- Fraction : If multiple fractions were used (i.e. the same mixture split into multiple fractions) enter that here. TechRepMixture : Multiple runs using the same bioreplicate
- Channel : Mixture channel used
- Condition : Name of condition that was used for each run.
- Mixture : The unique mixture (plex) name
- BioReplicate : Name of biological replicate. Repeating the same name here will tell MSstatsPTM that the experiment is a repeated measure design.

## Examples

```
head(maxq_tmt_annotation)
```

---

maxq_tmt_evidence	<i>Example MaxQuant evidence file from the output of a TMT experiment</i>
-------------------	---

---

### Description

Experiment was performed by the Olsen lab and published on Nat. Commun. (citation below).

### Usage

```
maxq_tmt_evidence
```

### Format

a data.table with 96 columns and 199 rows, the output of MaxQuant

### Details

Hogrebe, A., von Stechow, L., Bekker-Jensen, D.B. et al. Benchmarking common quantification strategies for large-scale phosphoproteomics. Nat Commun 9, 1045 (2018). <https://doi.org/10.1038/s41467-018-03309-6>

The experiment was processed using MaxQuant by the computational proteomics team at Pfizer (Liang Xue and Pierre Jean).

The experiment did not contain a global profiling run, but we show an example of extracting the unmodified peptides and using them in place of the profiling run.

### Examples

```
head(maxq_tmt_evidence)
```

---

MetamorpheusToMSstatsPTMFormat	<i>Import Metamorpheus files into PTM format</i>
--------------------------------	--

---

### Description

Import Metamorpheus files into PTM format

### Usage

```
MetamorpheusToMSstatsPTMFormat(
  input,
  annotation,
  fasta_path,
  input_protein = NULL,
  annotation_protein = NULL,
  use_unmod_peptides = FALSE,
  mod_ids = c("\\[Common Biological:Phosphorylation on S\\]"),
  useUniquePeptide = TRUE,
  removeFewMeasurements = TRUE,
```

```

    removeProtein_with1Feature = FALSE,
    summaryforMultipleRows = max,
    use_log_file = TRUE,
    append = FALSE,
    verbose = TRUE,
    log_file_path = NULL
)

```

## Arguments

input	name of Metamorpheus output file, which is tabular format. Use the AllQuantifiedPeaks.tsv file from the Metamorpheus output.
annotation	name of 'annotation.txt' data which includes Condition, BioReplicate.
fasta_path	string containing path to the corresponding fasta file for the modified peptide dataset.
input_protein	same as input for global profiling run. Default is NULL.
annotation_protein	same as annotation for global profiling run. Default is NULL.
use_unmod_peptides	If protein_input is not provided, unmodified peptides can be extracted from input to be used in place of a global profiling run. Default is FALSE.
mod_ids	List of modifications of interest. Default is a list with only Common Biological:Phosphorylation o Please note that the 'mod_ids' parameter currently supports lists of size 1 only. Future updates aim to extend its functionality to accommodate lists of greater sizes. Note \\ must be included before special characters.
useUniquePeptide	TRUE (default) removes peptides that are assigned for more than one proteins. We assume to use unique peptide for each protein.
removeFewMeasurements	TRUE (default) will remove the features that have 1 or 2 measurements across runs.
removeProtein_with1Feature	TRUE will remove the proteins which have only 1 feature, which is the combination of peptide, precursor charge, fragment and charge. FALSE is default.
summaryforMultipleRows	max(default) or sum - when there are multiple measurements for certain feature and certain run, use highest or sum of multiple intensities.
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.

## Value

a list of two data.tables named 'PTM' and 'PROTEIN' in the format required by MSstatsPTM.

**Author(s)**

Anthony Wu

**Examples**

```

input = system.file("tinytest/raw_data/Metamorpheus/AllQuantifiedPeaks.tsv",
                    package = "MSstatsPTM")
input = data.table::fread(input)
annot = system.file("tinytest/raw_data/Metamorpheus/ExperimentalDesign.tsv",
                    package = "MSstatsPTM")
annot = data.table::fread(annot)
input_protein = system.file("tinytest/raw_data/Metamorpheus/AllQuantifiedPeaksGlobalProteome.tsv",
                            package = "MSstatsPTM")
input_protein = data.table::fread(input_protein)
annot_protein = system.file("tinytest/raw_data/Metamorpheus/ExperimentalDesignGlobalProteome.tsv",
                            package = "MSstatsPTM")
annot_protein = data.table::fread(annot_protein)
fasta_path=system.file("extdata", "metamorpheus_fasta.fasta",
                       package="MSstatsPTM")
metamorpheus_imported = MetamorpheusToMSstatsPTMFormat(
  input,
  annot,
  fasta_path=fasta_path,
  input_protein=input_protein,
  annotation_protein=annot_protein,
  use_unmod_peptides=FALSE,
  mod_ids = c("\\[Common Fixed:Carbamidomethyl on C\\]")
)
head(metamorpheus_imported$PTM)
head(metamorpheus_imported$PROTEIN)

```

MSstatsPTM

*MSstatsPTM: A package for detecting differentially abundant post-translational modifications (PTM) in mass spectrometry-based proteomic experiments.*

**Description**

A set of tools for detecting differentially abundant PTMs and proteins in shotgun mass spectrometry-based proteomic experiments. The package can handle a variety of acquisition types, including label free and TMT experiments, acquired with DDA, DIA, SRM or PRM acquisition methods. The package includes tools to convert raw data from different spectral processing tools, summarize feature intensities, and fit a linear mixed effects model. A major advantage of the package is to leverage a separate global profiling run and adjust the PTM fold change for changes in the unmodified protein, showing the unconvoluted PTM fold change. Finally, the package includes functionality to plot a variety of data visualizations.

**functions**

- [FragPipeToMSstatsPTMFormat](#) : Generates MSstatsPTM required input format for TMT FragePipe outputs.
- [MaxQtoMSstatsPTMFormat](#) : Generates MSstatsPTM required input format for label-free and TMT MaxQuant outputs.

- [ProgenesistoMSstatsPTMFormat](#) : Generates MSstatsPTM required input format for label-free Progenesis outputs.
- [SpectronauttoMSstatsPTMFormat](#) : Generates MSstatsPTM required input format for label-free Spectronaut outputs.
- [SkylinetoMSstatsPTMFormat](#) : Generates MSstatsPTM required input format for Skyline outputs.
- [PStoMSstatsPTMFormat](#) : Generates MSstatsPTM required input format for PEAKS outputs.
- [PDtoMSstatsPTMFormat](#) : Generates MSstatsPTM required input format for Proteome Discoverer outputs.
- [dataSummarizationPTM](#) : Summarizes PSM level quantification to peptide (modification) and protein level quantification. For use in label-free analysis
- [dataSummarizationPTM\\_TMT](#) : Summarizes PSM level quantification to peptide (modification) and protein level quantification. For use in TMT analysis.
- [dataProcessPlotsPTM](#) : Visualization for explanatory data analysis. Specifically gives ability to plot Profile and Quality Control plots.
- [groupComparisonPTM](#) : Tests for significant changes in PTM and protein abundance across conditions. Adjusts PTM fold change for changes in protein abundance.
- [groupComparisonPlotsPTM](#) : Visualization for model-based analysis and summarization

### Author(s)

**Maintainer:** Anthony Wu <wu.anthon@northeastern.edu>

Authors:

- Devon Kohler <kohler.d@northeastern.edu>
- Tsung-Heng Tsai <tsai.tsungheng@gmail.com>
- Deril Raju <raju.d@northeastern.edu>
- Ting Huang <thuang0703@gmail.com>
- Mateusz Staniak <mtst@mstaniak.pl>
- Meena Choi <mnchoi67@gmail.com>
- Olga Vitek <o.vitek@northeastern.edu>

### See Also

Useful links:

- Report bugs at <https://github.com/Vitek-Lab/MSstatsPTM/issues>

---

MSstatsPTMSiteLocator *Locate modification site number and amino acid*


---

## Description

Locate modification site number and amino acid

## Usage

```
MSstatsPTMSiteLocator(
  data,
  protein_name_col = "ProteinName",
  unmod_pep_col = "PeptideSequence",
  mod_pep_col = "PeptideModifiedSequence",
  clean_mod = FALSE,
  fasta_file = NULL,
  fasta_protein_name = "header",
  mod_id = "\\*",
  localization_scores = FALSE,
  localization_cutoff = 0.75,
  remove_unlocalized_peptides = TRUE,
  terminus_included = FALSE,
  terminus_id = "\\.",
  mod_id_is_numeric = FALSE,
  remove_underscores = FALSE,
  remove_other_mods = FALSE,
  bracket = FALSE,
  replace_text = FALSE
)
```

## Arguments

<code>data</code>	<code>data.table</code> of enriched experimental run. Must include ProteinName, PeptideSequence, PeptideModifiedSequence, and (optionally) Start columns.
<code>protein_name_col</code>	Name of column indicating protein. Default is ProteinName.
<code>unmod_pep_col</code>	Name of column indicating unmodified peptide sequence. Default is PeptideSequence.
<code>mod_pep_col</code>	Name of column indicating modified peptide sequence. Default is PeptideModifiedSequence.
<code>clean_mod</code>	Remove special characters and numbers around modification name. Default is FALSE
<code>fasta_file</code>	File path to FASTA file that matches with proteins in data. Can be either string or <code>data.table</code> processed with <code>tidyFasta()</code> function. Default to NULL if peptide number included in data.
<code>fasta_protein_name</code>	Name of fasta file column that matches with <code>protein_name_col</code> . Default is header.
<code>mod_id</code>	String that indicates what amino acid was modified in PeptideSequence.

localization_scores	Boolean indicating if mod id is a localization score. If TRUE, mod_id will be ignored and localization cutoff will be used to determine sites. Default is FALSE.
localization_cutoff	Default is .75. Localization probabilities below cutoffs will be removed. localization_scores must be TRUE.
remove_unlocalized_peptides	Default is TRUE. If localization_scores is TRUE and probabilities are below localization_cutoff, the modification site will not be able to be determined. These unlocalized peptides can be kept or removed. If FALSE the unlocalized peptides will still be used in modeling the sites that could be localized.
terminus_included	Boolean indicating if the PeptideSequence includes the terminus amino acid.
terminus_id	String that indicates what the terminus amino acid is. Default is '.'.
mod_id_is_numeric	Boolean indicating if modification identifier is a number instead of a character (i.e. +80 vs *).
remove_underscores	Boolean indicating if underscores around peptide exist. These should be removed to properly count where in sequence the modification occurred.
remove_other_mods	keeping mods that are not of interest can mess up the amino acid count. Remove them if they are causing issues.
bracket	bracket type that encompasses PTM (usually [ or ()). Always pass opening bracket (there is a function to grab the close bracket). Default is FALSE (i.e. no bracket).
replace_text	If PTM is noted by text (i.e. Phospho) and needs to be replaced by an indicator (*)

## Value

data.table with site location added into Protein column.

## Examples

```
##TODO
```

---

PDtoMSstatsPTMFormat    *Convert Proteome Discoverer output into MSstatsPTM format*

---

## Description

Import Proteome Discoverer files, identify modification site location.

**Usage**

```

PDtoMSstatsPTMFormat(
  input,
  annotation,
  fasta_path,
  protein_input = NULL,
  annotation_protein = NULL,
  labeling_type = "LF",
  mod_id = "\\(Phospho\\)",
  use_localization_cutoff = FALSE,
  keep_all_mods = FALSE,
  use_unmod_peptides = FALSE,
  fasta_protein_name = "uniprot_iso",
  localization_cutoff = 75,
  remove_unlocalized_peptides = TRUE,
  useNumProteinsColumn = FALSE,
  useUniquePeptide = TRUE,
  summaryforMultipleRows = max,
  removeFewMeasurements = TRUE,
  removeOxidationMpeptides = FALSE,
  removeProtein_with1Peptide = FALSE,
  which_quantification = "Precursor.Area",
  which_proteinid = "Protein.Group.Accessions",
  use_log_file = TRUE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL
)

```

**Arguments**

input	PD report corresponding with enriched experimental data.
annotation	name of 'annotation.txt' or 'annotation.csv' data which includes Condition, BioReplicate, Run information. 'Run' will be matched with 'Spectrum.File'
fasta_path	string containing path to the corresponding fasta file for the modified peptide dataset.
protein_input	PD report corresponding with unmodified experimental data.
annotation_protein	Same format as annotation corresponding to unmodified data.
labeling_type	type of experimental design, must be one of LF for label free or TMT for tandem mass tag.
mod_id	Character that indicates the modification of interest. Default is "\\(Phospho\\)". Note \\ must be included before special characters.
use_localization_cutoff	Boolean indicating whether to use a custom localization cutoff or rely on PD's modifications column. TRUE is default and apply custom cutoff localization_cutoff.
keep_all_mods	Boolean indicating whether to keep or remove peptides not in mod_id. Default is FALSE.
use_unmod_peptides	If protein_input is not provided, unmodified peptides can be extracted from input to be used in place of a global profiling run. Default is FALSE.



fasta_protein_name	Name of fasta column that matches with protein name in evidence file. Default is uniprot_iso.
localization_cutoff	Minimum localization score required to keep modification. Default is .75.
remove_unlocalized_peptides	Boolean indicating if peptides without all sites localized should be kept. Default is TRUE (non-localized sites will be removed).
useNumProteinsColumn	TRUE removes peptides which have more than 1 in Proteins column of PD output.
useUniquePeptide	TRUE (default) removes peptides that are assigned for more than one proteins. We assume to use unique peptide for each protein.
summaryforMultipleRows	max(default) or sum - when there are multiple measurements for certain feature and certain run, use highest or sum of multiple intensities.
removeFewMeasurements	TRUE (default) will remove the features that have 1 or 2 measurements across runs.
removeOxidationMpeptides	TRUE will remove the peptides including 'oxidation (M)' in modification. FALSE is default.
removeProtein_with1Peptide	TRUE will remove the proteins which have only 1 peptide and charge. FALSE is default.
which_quantification	Use 'Precursor.Area'(default) column for quantified intensities. 'Intensity' or 'Area' can be used instead.
which_proteinid	Use 'Protein.Accessions'(default) column for protein name. 'Master.Protein.Accessions' can be used instead.
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.

## Value

list of data.table

## Examples

```
# Global profiling example
input = system.file("tinytest/raw_data/PD/pd-ptm-input.csv",
package = "MSstatsPTM")
input = data.table::fread(input)
```

```

annot = system.file("tinytest/raw_data/PD/pd-ptm-annot.csv",
                    package = "MSstatsPTM")
annot = data.table::fread(annot)
input_protein = system.file("tinytest/raw_data/PD/protein-input.csv",
                             package = "MSstatsPTM")
input_protein = data.table::fread(input_protein)
annot_protein = system.file("tinytest/raw_data/PD/protein-annot.csv",
                             package = "MSstatsPTM")
annot_protein = data.table::fread(annot_protein)
fasta_path=system.file("extdata", "pd_with_proteome.fasta",
                        package="MSstatsPTM")
pd_imported = PDtoMSstatsPTMFormat(
  input,
  annotation = annot,
  protein_input = input_protein,
  annotation_protein = annot_protein,
  fasta_path = fasta_path,
  mod_id = "\\(GG\\)",
  labeling_type = "TMT",
  use_localization_cutoff = FALSE,
  which_proteinid = "Master.Protein.Accessions")

head(pd_imported$PTM)
head(pd_imported$PROTEIN)

# No global profiling example
head(pd_psm_input)
head(pd_annotation)

msstats_format = PDtoMSstatsPTMFormat(pd_psm_input,
                                       pd_annotation,
                                       system.file("extdata", "pd_fasta.fasta", package="MSstatsPTM"),
                                       use_unmod_peptides=TRUE,
                                       which_proteinid = "Master.Protein.Accessions")

head(msstats_format$PTM)
head(msstats_format$PROTEIN)

```

---

pd_annotation	<i>Example annotation file for a label-free Proteome Discoverer experiment.</i>
---------------	---

---

## Description

Must be manually created by the user and input into the PDtoMSstatsPTMFormat converter. Requires the correct columns and maps the experimental design into the MSstats format. Specify unique bioreplicates for group comparison designs, and the same bioreplicate for repeated measure designs. The columns and descriptions are below.

## Usage

```
pd_annotation
```

**Format**

A data.table with 3 columns.

**Details**

- Run : Run name that matches exactly with PD run. Used to join evidence and metadata in annotation file.
- Condition : Name of condition that was used for each run.
- BioReplicate : Name of biological replicate. Repeating the same name here will tell MSstatsPTM that the experiment is a repeated measure design.

**Examples**

```
head(pd_annotation)
```

---

pd_psm_input	<i>Example Proteome Discoverer evidence file from the output of a label free experiment</i>
--------------	---

---

**Description**

Experiment was performed by the Olsen lab and published on Nat. Commun. (citation below).

**Usage**

```
pd_psm_input
```

**Format**

a data.table with 60 columns and 1657 rows, the output of PD

**Details**

Bekker-Jensen, D.B., Bernhardt, O.M., Høgrebe, A. et al. Rapid and site-specific deep phosphoproteome profiling by data-independent acquisition without the need for spectral libraries. Nat Commun 11, 787 (2020). <https://doi.org/10.1038/s41467-020-14609-1>

The experiment was processed using Proteome Discoverer by the computational proteomics team at Pfizer (Liang Xue and Pierre Jean).

The experiment did not contain a global profiling run, but we show an example of extracting the unmodified peptides and using them in place of the profiling run.

**Examples**

```
head(pd_psm_input)
```

---

pd_testing_output	<i>Example output of Proteome Discoverer converter</i>
-------------------	--

---

### Description

output using example data provided in package

### Usage

```
pd_testing_output
```

### Format

a list with 2 data.frames

### Details

The experiment did not contain a global profiling run, but we show an example of extracting the unmodified peptides and using them in place of the profiling run.

### Examples

```
head(pd_testing_output)
```

---

ProgenesistoMSstatsPTMFormat

*Converts non-TMT Progenesis output into the format needed for MSstatsPTM*

---

### Description

Converts non-TMT Progenesis output into the format needed for MSstatsPTM

### Usage

```
ProgenesistoMSstatsPTMFormat(
  ptm_input,
  annotation,
  global_protein_input = FALSE,
  fasta_path = FALSE,
  useUniquePeptide = TRUE,
  summaryforMultipleRows = max,
  removeFewMeasurements = TRUE,
  removeOxidationMpeptides = FALSE,
  removeProtein_with1Peptide = FALSE,
  mod.num = "Single"
)
```

**Arguments**

ptm_input	name of Progenesis output with modified peptides, which is wide-format. 'Accession', 'Sequence', 'Modification', 'Charge' and one column for each run are required
annotation	name of 'annotation.txt' or 'annotation.csv' data which includes Condition, BioReplicate, Run, and Type (PTM or Protein) information. It will be matched with the column name of input for MS runs. Please note PTM and global Protein run names are often different, which is why an additional Type column indicating Protein or PTM is required.
global_protein_input	name of Progenesis output with unmodified peptides, which is wide-format. 'Accession', 'Sequence', 'Modification', 'Charge' and one column for each run are required
fasta_path	string containing path to the corresponding fasta file for the modified peptide dataset.
useUniquePeptide	TRUE(default) removes peptides that are assigned for more than one proteins. We assume to use unique peptide for each protein.
summaryforMultipleRows	max(default) or sum - when there are multiple measurements for certain feature and certain run, use highest or sum of multiple intensities.
removeFewMeasurements	TRUE (default) will remove the features that have 1 or 2 measurements across runs.
removeOxidationMpeptides	TRUE will remove the modified peptides including 'Oxidation (M)' sequence. FALSE is default.
removeProtein_with1Peptide	TRUE will remove the proteins which have only 1 peptide and charge. FALSE is default.
mod.num	For modified peptide dataset, must be one of Single or Total. The default is Single. The number modifications per peptide to be used. If "Single", only peptides with one modification will be used. Otherwise "Total" includes peptides with more than one modification. Selecting "Total" may confound the effect of different modifications.

**Value**

a list of two data.tables named 'PTM' and 'PROTEIN' in the format required by MSstatsPTM.

**Examples**

```
input = system.file("tinytest/raw_data/Progenesis/progenesis_peptide.csv",
                    package = "MSstatsPTM")
input = data.table::fread(input)
colnames(input) = unlist(input[1,])
input = input[-1,]
annot = system.file("tinytest/raw_data/Progenesis/phospho_annotation.csv",
                    package = "MSstatsPTM")
annot = data.table::fread(annot)
prog_imported = ProgenisistoMSstatsPTMFormat(
  input,
```

```

    annot
  )
  head(prog_imported$PTM)

```

---

ProteinProspectortoMSstatsPTMFormat

*Generate MSstatsPTM required input format from Protein Prospector output*

---

## Description

Generate MSstatsPTM required input format from Protein Prospector output

## Usage

```

ProteinProspectortoMSstatsPTMFormat(
  input,
  annotation,
  input_protein = NULL,
  annotation_protein = NULL,
  use_unmod_peptides = FALSE,
  mod_ids = c("Phospho"),
  useUniquePeptide = TRUE,
  removeFewMeasurements = TRUE,
  removeProtein_with1Feature = FALSE,
  summaryforMultipleRows = sum,
  use_log_file = TRUE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL
)

```

## Arguments

input	Input txt peptide report file from Protein Prospector with "Keep Replicates", "Mods in Peptide", and "Protein Mods" options selected.
annotation	data frame which contains column Run, Fraction, TechRepMixture, Mixture, Channel, BioReplicate, Condition.
input_protein	same as input for global profiling run. Default is NULL.
annotation_protein	same as annotation for global profiling run. Default is NULL.
use_unmod_peptides	If protein_input is not provided, unmodified peptides can be extracted from input to be used in place of a global profiling run. Default is FALSE.
mod_ids	List of modifications of interest. Default is a list with only Phospho. Please note that the 'mod_ids' parameter currently supports lists of size 1 only. Future updates aim to extend its functionality to accommodate lists of greater sizes.
useUniquePeptide	TRUE (default) removes peptides that are assigned for more than one proteins. We assume to use unique peptide for each protein.

removeFewMeasurements	TRUE (default) will remove the features that have 1 or 2 measurements across runs.
removeProtein_with1Feature	TRUE will remove the proteins which have only 1 feature, which is the combination of peptide, precursor charge, fragment and charge. FALSE is default.
summaryforMultipleRows	sum(default) or max - when there are multiple measurements for certain feature and certain run, use highest or sum of multiple intensities.
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.

**Value**

a list of two data.tables named 'PTM' and 'PROTEIN' in the format required by MSstatsPTM.

**Author(s)**

Anthony Wu

**Examples**

```
input = system.file("tinytest/raw_data/ProteinProspector/Prospector_PhosphoTMT.txt",
  package = "MSstatsPTM")
input = data.table::fread(input)
annot = system.file("tinytest/raw_data/ProteinProspector/Annotation.csv",
  package = "MSstatsPTM")
annot = data.table::fread(annot)
input_protein = system.file("tinytest/raw_data/ProteinProspector/Prospector_TotalTMT.txt",
  package = "MSstatsConvert")
input_protein = data.table::fread(input_protein)
annot_protein = system.file("tinytest/raw_data/ProteinProspector/Annotation.csv",
  package = "MSstatsConvert")
annot_protein = data.table::fread(annot_protein)
output <- ProteinProspectortoMSstatsPTMFormat(
  input,
  annot,
  input_protein,
  annot_protein
)
head(output)
```

---

PStoMSstatsPTMFormat    *Convert Peaks Studio output into MSstatsPTM format*


---

## Description

Currently only supports label-free quantification.

## Usage

```
PStoMSstatsPTMFormat(
  input,
  annotation,
  input_protein = NULL,
  annotation_protein = NULL,
  use_unmod_peptides = FALSE,
  target_modification = NULL,
  remove_oxidation_peptides = FALSE,
  remove_multi_mod_types = FALSE,
  summaryforMultipleRows = max,
  use_log_file = TRUE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL
)
```

## Arguments

input	name of Peaks Studio PTM output
annotation	name of annotation file which includes Raw.file, Condition, BioReplicate, Run. For example annotation see example below.
input_protein	name of Peaks Studio unmodified protein output (optional)
annotation_protein	name of annotation file which includes Raw.file, Condition, BioReplicate, Run for unmodified protein output.
use_unmod_peptides	Boolean if the unmodified peptides in the input file should be used to construct the unmodified protein output. Only used if input_protein is not provided. Default is FALSE
target_modification	Character name of modification of interest. To use all mod types, leave as NULL. Default is NULL. Note that if the name includes special characters, you must include "\" before the characters. Ex. "Phosphorylation \\$(STY)"
remove_oxidation_peptides	Boolean if Oxidation (M) modifications should be removed. Default is FALSE
remove_multi_mod_types	Used if target_modification is not NULL. TRUE will remove peptides with multiple types of modifications (ie acetylation and phosphorylation). FALSE will keep these peptides and summarize them seperately.



summaryforMultipleRows	max(default) or sum - when there are multiple measurements for certain feature and certain run, use highest or sum of multiple intensities.
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.

**Value**

list of data.table

**Examples**

```
# The output should be in the following format.
head(raw.input$PTM)
head(raw.input$PROTEIN)
```

---

raw.input	<i>Example of input PTM dataset for LabelFree/DDA/DIA experiments.</i>
-----------	--

---

**Description**

It can be the output of MSstatsPTM converter ProgenesistoMSstatsPTMFormat or other MSstats converter functions (Please see MSstatsPTM\_LabelFree\_Workflow vignette). The dataset is formatted as a list with two data.tables named PTM and PROTEIN. In each data.table the variables are as follows:

**Usage**

```
raw.input
```

**Format**

A list of two data.tables named PTM and PROTEIN with 1745 and 478 rows respectively.

**Details**

```
#'
```

ProteinName : Name of protein with modification site mapped in with an underscore. ie "Protein\_4\_Y474"

- PeptideSequence
- Condition : Condition (ex. Healthy, Cancer, Time0)
- BioReplicate : Unique ID for biological subject.
- Run : MS run ID.

- Intensity
- PrecursorCharge
- FragmentIon
- ProductCharge
- IsotopeLabelType

## Examples

```
head(raw.input$PTM)
head(raw.input$PROTEIN)
```

---

raw.input.tmt	<i>Example of input PTM dataset for TMT experiments.</i>
---------------	--

---

## Description

It can be the output of MSstatsPTM converter MaxQtoMSstatsPTMFormat or other MSstatsTMT converter functions (Please see MSstatsPTM\_TMT\_Workflow vignette). The dataset is formatted as a list with two data.tables named PTM and PROTEIN. In each data.table the variables are as follows:

## Usage

```
raw.input.tmt
```

## Format

A list of two data.tables named PTM and PROTEIN with 1716 and 29221 rows respectively.

## Details

- ProteinName : Name of protein with modification site mapped in with an underscore. ie "Protein\_4\_Y474"
- PeptideSequence
- Charge
- PSM
- Mixture : Mixture of samples labeled with different TMT reagents, which can be analyzed in a single mass spectrometry experiment. If the channel doesn't have sample, please add Empty' under Condition. \item TechRepMixture : Technical replicate of one mixture. One mixture m Mixture' = 1, 2 are the two technical replicates of one mixture, then they should match with same Mixture' value. \item Run : MS run ID. \item Channel : Labeling information (126, ... 131). under BioReplicate.
- Intensity

## Examples

```
head(raw.input.tmt$PTM)
head(raw.input.tmt$PROTEIN)
```

---

SkylinetoMSstatsPTMFormat

*Convert Skyline output into MSstatsPTM format*


---

## Description

Currently only supports label-free quantification.

## Usage

```
SkylinetoMSstatsPTMFormat(
  input,
  fasta_path,
  fasta_protein_name = "uniprot_iso",
  annotation = NULL,
  input_protein = NULL,
  annotation_protein = NULL,
  use_unmod_peptides = FALSE,
  removeiRT = TRUE,
  filter_with_Qvalue = TRUE,
  qvalue_cutoff = 0.01,
  use_unique_peptide = TRUE,
  remove_few_measurements = FALSE,
  remove_oxidation_peptides = FALSE,
  removeProtein_with1Feature = FALSE,
  use_log_file = TRUE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL
)
```

## Arguments

input	name of Skyline PTM output
fasta_path	A string of path to a FASTA file, used to match PTM peptides.
fasta_protein_name	Name of fasta column that matches with protein name in evidence file. Default is uniprot_iso.
annotation	name of 'annotation.txt' data which includes Condition, BioReplicate, Run. If annotation is already complete in Skyline, use annotation=NULL (default). It will use the annotation information from input.
input_protein	name of Skyline unmodified protein output (optional)
annotation_protein	name of 'annotation.txt' data which includes Condition, BioReplicate, Run for unmodified protein output. This can be the same as annotation.
use_unmod_peptides	Boolean if the unmodified peptides in the input file should be used to construct the unmodified protein output. Only used if input_protein is not provided. Default is FALSE.

removeiRT	TRUE (default) will remove the proteins or peptides which are labeled 'iRT' in 'StandardType' column. FALSE will keep them.
filter_with_Qvalue	TRUE(default) will filter out the intensities that have greater than qvalue_cutoff in DetectionQValue column. Those intensities will be replaced with zero and will be considered as censored missing values for imputation purpose.
qvalue_cutoff	Cutoff for DetectionQValue. default is 0.01.
use_unique_peptide	TRUE (default) removes peptides that are assigned for more than one proteins. We assume to use unique peptide for each protein.
remove_few_measurements	TRUE will remove the features that have 1 or 2 measurements across runs. FALSE is default.
remove_oxidation_peptides	TRUE will remove the peptides including 'oxidation (M)' in modification. FALSE is default.
removeProtein_with1Feature	TRUE will remove the proteins which have only 1 feature, which is the combination of peptide, precursor charge, fragment and charge. FALSE is default.
use_log_file	logical. If TRUE, information about data processing will be saved to a file.
append	logical. If TRUE, information about data processing will be added to an existing log file.
verbose	logical. If TRUE, information about data processing will be printed to the console.
log_file_path	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.

**Value**

list of data.table

**Examples**

```
# The output should be in the following format.
head(raw.input$PTM)
head(raw.input$PROTEIN)
```

---

SpectronauttoMSstatsPTMFormat

*Convert Spectronaut output into MSstatsPTM format*

---

**Description**

Converters label-free Spectronaut data into MSstatsPTM format. Requires PSM output from Spectronaut and a custom made annotation file, mapping the run name to the condition and bioreplicate. Can optionally take a separate PSM file for a global profiling run. If no global profiling run provided, the function can extract the unmodified peptides from the PTM PSM file and use them as a global profiling run (not recommended).

**Usage**

```

SpectronauttoMSstatsPTMFormat(
  input,
  annotation = NULL,
  fasta_path = NULL,
  protein_input = NULL,
  annotation_protein = NULL,
  use_unmod_peptides = FALSE,
  intensity = "PeakArea",
  mod_id = "\\[Phospho \\(STY\\)\\]",
  fasta_protein_name = "uniprot_iso",
  remove_other_mods = TRUE,
  filter_with_Qvalue = TRUE,
  qvalue_cutoff = 0.01,
  useUniquePeptide = TRUE,
  removeFewMeasurements = TRUE,
  removeProtein_with1Feature = FALSE,
  summaryforMultipleRows = max,
  use_log_file = TRUE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL
)

```

**Arguments**

input	name of Spectronaut PTM output, which is long-format. ProteinName, PeptideSequence, PrecursorCharge, FragmentIon, ProductCharge, IsotopeLabelType, Condition, BioReplicate, Run, Intensity, F.ExcludedFromQuantification are required. Rows with F.ExcludedFromQuantification=True will be removed.
annotation	name of 'annotation.txt' data which includes Condition, BioReplicate, Run. If annotation is already complete in Spectronaut, use annotation=NULL (default). It will use the annotation information from input.
fasta_path	string containing path to the corresponding fasta file for the modified peptide dataset.
protein_input	name of Spectronaut global protein output, which is as in the same format as input parameter.
annotation_protein	name of annotation file for global protein data, in the same format as above.
use_unmod_peptides	If protein_input is not provided, unmodified peptides can be extracted from input to be used in place of a global profiling run. Default is FALSE.
intensity	'PeakArea' (default) uses not normalized peak area. 'NormalizedPeakArea' uses peak area normalized by Spectronaut. Default is NULL
mod_id	Character that indicates the modification of interest. Default is \\(Phospho\\). Note \\ must be included before special characters.
fasta_protein_name	Name of fasta column that matches with protein name in evidence file. Default is uniprot_iso.

<code>remove_other_mods</code>	Remove peptides which include modifications other than the one listed in <code>mod_id</code> . Default is TRUE. For example, in an experiment targeting Phosphorylation, setting this parameter to TRUE would remove peptides like (Acetyl (Protein N-term))AAAAPDSRVS(Phospho (STY))EEENLK. Set this parameter to FALSE to keep peptides with extraneous modifications.
<code>filter_with_Qvalue</code>	TRUE(default) will filter out the intensities that have greater than <code>qvalue_cutoff</code> in EG.Qvalue column. Those intensities will be replaced with zero and will be considered as censored missing values for imputation purpose.
<code>qvalue_cutoff</code>	Cutoff for EG.Qvalue. Default is 0.01.
<code>useUniquePeptide</code>	TRUE (default) removes peptides that are assigned for more than one proteins. We assume to use unique peptide for each protein.
<code>removeFewMeasurements</code>	TRUE (default) will remove the features that have 1 or 2 measurements across runs.
<code>removeProtein_with1Feature</code>	TRUE will remove the proteins which have only 1 feature, which is the combination of peptide, precursor charge, fragment and charge. FALSE is default.
<code>summaryforMultipleRows</code>	max(default) or sum - when there are multiple measurements for certain feature and certain run, use highest or sum of multiple intensities.
<code>use_log_file</code>	logical. If TRUE, information about data processing will be saved to a file.
<code>append</code>	logical. If TRUE, information about data processing will be added to an existing log file.
<code>verbose</code>	logical. If TRUE, information about data processing will be printed to the console.
<code>log_file_path</code>	character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If 'append = TRUE', has to be a valid path to a file.

### Value

a list of two data.tables named 'PTM' and 'PROTEIN' in the format required by MSstatsPTM.

### Examples

```
head(spectronaut_input)
head(spectronaut_annotation)

msstats_input = SpectronauttoMSstatsPTMFormat(spectronaut_input,
  annotation=spectronaut_annotation,
  fasta_path=system.file("extdata", "spectronaut_fasta.fasta", package="MSstatsPTM"),
  use_unmod_peptides=TRUE,
  mod_id = "\\[Phospho \\(STY\\)\\]",
  fasta_protein_name = "uniprot_iso"
)

head(msstats_input$PTM)
head(msstats_input$PROTEIN)
```

---

spectronaut\_annotation

*Example annotation file for a label-free Spectronaut experiment.*


---

### Description

Must be manually created by the user and input into the SpectronauttoMSstatsPTMFormat converter. Requires the correct columns and maps the experimental design into the MSstats format. Specify unique bioreplicates for group comparison designs, and the same bioreplicate for repeated measure designs. The columns and descriptions are below.

### Usage

```
spectronaut_annotation
```

### Format

A data.table with 5 columns.

### Details

- Run : Run name that matches exactly with Spectronaut run. Used to join evidence and meta-data in annotation file.
- Condition : Name of condition that was used for each run.
- BioReplicate : Name of biological replicate. Repeating the same name here will tell MSstatsPTM that the experiment is a repeated measure design.
- Raw.file : Run name that matches exactly with Spectronaut run. Used to join evidence and metadata in annotation file.

### Examples

```
head(spectronaut_annotation)
```

---

spectronaut\_input

*Example Spectronaut evidence file from the output of a label free experiment*


---

### Description

Experiment was performed by the Olsen lab and published on Nat. Commun. (citation below).

### Usage

```
spectronaut_input
```

### Format

a data.table with 23 columns and 2683 rows, the output of Spectronaut

## Details

Bekker-Jensen, D.B., Bernhardt, O.M., Høgrebe, A. et al. Rapid and site-specific deep phosphoproteome profiling by data-independent acquisition without the need for spectral libraries. *Nat Commun* 11, 787 (2020). <https://doi.org/10.1038/s41467-020-14609-1>

The experiment was processed using Spectronaut by the computational proteomics team at Pfizer (Liang Xue and Pierre Jean).

The experiment did not contain a global profiling run, but we show an example of extracting the unmodified peptides and using them in place of the profiling run.

## Examples

```
head(spectronaut_input)
```

---

summary.data	<i>Example of output from dataSummarizationPTM function for non-TMT data</i>
--------------	--

---

## Description

It is made from [raw.input](#). It is the output of dataSummarizationPTM function from MSstatsPTM. It should include a list with two names PTM and PROTEIN. Each of these list values is also a list with two names ProteinLevelData and FeatureLevelData, which correspond to two data.tables. The columns in these two data.tables are listed below. The variables are as follows:

- FeatureLevelData :
  - PROTEIN : Protein ID with modification site mapped in. Ex. Protein\_1002\_S836
  - PEPTIDE : Full peptide with charge
  - TRANSITION: Charge
  - FEATURE : Combination of Protein, Peptide, and Transition Columns
  - LABEL :
  - GROUP : Condition (ex. Healthy, Cancer, Time0)
  - RUN : Unique ID for technical replicate of one TMT mixture.
  - SUBJECT : Unique ID for biological subject.
  - FRACTION : Unique Fraction ID
  - originalRUN : Run name
  - censored :
  - INTENSITY : Unique ID for TMT mixture.
  - ABUNDANCE : Unique ID for TMT mixture.
  - newABUNDANCE : Unique ID for TMT mixture.
  - predicted : Unique ID for TMT mixture.
- ProteinLevelData :
  - RUN : MS run ID
  - Protein : Protein ID with modification site mapped in. Ex. Protein\_1002\_S836
  - LogIntensities: Protein-level summarized abundance
  - originalRUN : Labeling information (126, ... 131)
  - GROUP : Condition (ex. Healthy, Cancer, Time0)



- SUBJECT : Unique ID for biological subject.
- TotalGroupMeasurements : Unique ID for technical replicate of one TMT mixture.
- NumMeasuredFeature : Unique ID for TMT mixture.
- MissingPercentage : Unique ID for TMT mixture.
- more50missing : Unique ID for TMT mixture.
- NumImputedFeature : Unique ID for TMT mixture.

## Usage

```
summary.data
```

## Format

A list of two lists with four data.tables.

## Examples

```
head(summary.data)
```

---

```
summary.data.tmt
```

*Example of output from dataSummarizationPTM\_TMT function for TMT data*

---

## Description

It is made from `raw.input.tmt`. It is the output of `dataSummarizationPTM_TMT` function from `MSstatsPTM`. It should include a list with two names `PTM` and `PROTEIN`. Each of these list values is also a list with two names `ProteinLevelData` and `FeatureLevelData`, which correspond to two data.tables. The columns in these two data.tables are listed below. The variables are as follows:

- FeatureLevelData :
  - ProteinName : MS run ID
  - PSM : Protein ID with modification site mapped in. Ex. Protein\_1002\_S836
  - censored: Protein-level summarized abundance
  - predicted : Labeling information (126, ... 131)
  - log2Intensity : Condition (ex. Healthy, Cancer, Time0)
  - Run : Unique ID for biological subject.
  - Channel : Unique ID for technical replicate of one TMT mixture.
  - BioReplicate : Unique ID for TMT mixture.
  - Condition : Unique ID for TMT mixture.
  - Mixture : Unique ID for TMT mixture.
  - TechRepMixture : Unique ID for TMT mixture.
  - PeptideSequence : Unique ID for TMT mixture.
  - Charge : Unique ID for TMT mixture.
- ProteinLevelData :
  - Mixture : MS run ID
  - TechRepMixture : Protein ID with modification site mapped in. Ex. Protein\_1002\_S836

- Run: Protein-level summarized abundance
- Channel : Labeling information (126, ... 131)
- Protein : Condition (ex. Healthy, Cancer, Time0)
- Abundance : Unique ID for biological subject.
- BioReplicate : Unique ID for technical replicate of one TMT mixture.
- Condition : Unique ID for TMT mixture.

### Usage

```
summary.data.tmt
```

### Format

A list of two lists with four data.tables.

### Examples

```
head(summary.data.tmt)
```

---

tidyFasta	<i>Read and tidy a FASTA file</i>
-----------	-----------------------------------

---

### Description

tidyFasta reads and tidys FASTA file. Use this function as the first step in identifying modification sites.

### Usage

```
tidyFasta(path)
```

### Arguments

path                      A string of path to a FASTA file.

### Value

A data.table with columns named header, sequence, uniprot\_ac, uniprot\_iso, entry\_name.

### Examples

```
tidyFasta(system.file("extdata", "013297.fasta", package="MSstatsPTM"))
```

# Index

## \* datasets

- fragpipe\_annotation, 21
- fragpipe\_annotation\_protein, 22
- fragpipe\_input, 23
- fragpipe\_input\_protein, 23
- maxq\_lf\_annotation, 32
- maxq\_lf\_evidence, 32
- maxq\_tmt\_annotation, 33
- maxq\_tmt\_evidence, 34
- pd\_annotation, 42
- pd\_psm\_input, 43
- pd\_testing\_output, 44
- raw.input, 49
- raw.input.tmt, 50
- spectronaut\_annotation, 55
- spectronaut\_input, 55
- summary.data, 56
- summary.data.tmt, 57

## \* internal

- .calculatePowerPTM, 3
- .getNumSamplePTM, 4
- .joinFasta, 5
- .locateSites, 5
- .removeCutoffSites, 6
- MSstatsPTM, 36
- .calculatePowerPTM, 3
- .fixTerminus, 4
- .getNumSamplePTM, 4
- .joinFasta, 5
- .locateSites, 5
- .removeCutoffSites, 6

annotSite, 6

dataProcess, 10

dataProcessPlotsPTM, 7, 37

dataProcessPTM, 9

dataSummarizationPTM, 7, 10, 26, 37

dataSummarizationPTM\_TMT, 7, 13, 26, 37

designSampleSizePTM, 14

DIANNtoMSstatsPTMFormat, 16

fragpipe\_annotation, 21

fragpipe\_annotation\_protein, 22

fragpipe\_input, 23

fragpipe\_input\_protein, 23

FragPipetoMSstatsPTMFormat, 18, 36

groupComparisonPlotsPTM, 24, 37

groupComparisonPTM, 24, 26, 37

locateMod, 27

locatePTM, 28

maxq\_lf\_annotation, 32

maxq\_lf\_evidence, 32

maxq\_tmt\_annotation, 33

maxq\_tmt\_evidence, 34

MaxQtoMSstatsPTMFormat, 29, 36

MetamorpheusToMSstatsPTMFormat, 34

MSstatsPTM, 36

MSstatsPTM-package (MSstatsPTM), 36

MSstatsPTMSiteLocator, 38

pd\_annotation, 42

pd\_psm\_input, 43

pd\_testing\_output, 44

PDtoMSstatsPTMFormat, 37, 39

ProgenesistoMSstatsPTMFormat, 37, 44

ProteinProspectortoMSstatsPTMFormat, 46

proteinSummarization, 10

PStoMSstatsPTMFormat, 37, 48

raw.input, 49, 56

raw.input.tmt, 50, 57

SkylinetoMSstatsPTMFormat, 37, 51

spectronaut\_annotation, 55

spectronaut\_input, 55

SpectronauttoMSstatsPTMFormat, 37, 52

summary.data, 56

summary.data.tmt, 57

tidyFasta, 58